



Switcher compacto para vídeo de alta calidad

AV-HSW10

IP Live Switcher con un diseño intuitivo y compacto de nueva generación.

Key Features

Varias Interfaces para cubrir una amplia gama de necesidades

Diferentes keys incluidos para vídeos más atractivos

Multivisor con 10 patrones seleccionables

Mando a distancia con software del panel de control

AV-HSW10

<https://latam.connect.panasonic.com/ar/es/products/broadcast-proav/av-hsw10>

Video Input	3G-SDI
	Baseband mode: 4 or 3
	IP mode: 1
	HDMI
	Baseband mode: 1 or 2
	IP mode: 1
	NDI®*1*2/Streaming
	Baseband mode: 2
	IP mode: 3
Video Output	3G-SDI
	Baseband mode: 2
	IP mode: 2
	HDMI
	Baseband mode: 1
	IP mode: 2
	NDI®*1*2/Streaming
	Baseband mode: 2
	IP mode: 2
Video Format	
3G-SDI	1080/59.94p,50p,29.97p,25p,24p,23.98p 1080/59.94i,50i 720/59.94p,50p
Audio	IN: RCA x 2, OUT: φ3.5 mm TRS
Frame Synchronizer	All inputs
CC/UC/DC	i/P converter, DC/UC (1080-720P), CC
Keyer	2 (PinP, Linear key, Luminance key, Chroma key)
AUX	2
USB Video Class Output	USB Type-C, 1 ch
Genlock	BB or Tri-level (Input/through output)
PTZ Link	Switcher Link, TSL5.0
VMEM	Still x 2
Shot MEM	Max. 12 presets
USB	USB-Type A x 1 (USB Memory)
Dimensions (W x H x D) (excluding protrusions)	254 mm x 175 mm x 67 mm (10 inches x 6-7/8 inches x 2-5/8 inches)
Power Consumption	45 W (TBD) 1080/59.94p,50p,29.97p,25p,24p,23.98p 720/59.94p,50p 1920 x 1080p, 1280 x 720p