



Controlador de cámaras remotas

AW-RP60GJ

Equipado con una pantalla que permite ver los menús de la interfaz gráfica de usuario con una gran nitidez, además de un joystick para un control intuitivo. Controlador compacto de cámaras remotas compatible con PoE* para conexión con un solo cable.

Key Features

Equipado con una pantalla LCD de tipo 3,5

Funciones de personalización flexibles

Nuevo joystick con funcionalidad mejorada

Compatible con PoE+/Ajuste de cámara avanzado

Control de hasta 200 cámaras de red remotas



AW-RP60GJ

<https://latam.connect.panasonic.com/ar/es/productos/broadcast-y-proav/aw-rp60gj>

Power Requirements	12 V DC (10.8 V to 13.2 V)
PoE*	IEEE802.3af standard: 42 V to 57 V DC (Camera Input)
Current Consumption	0.9 A (XLR connector input), 0.3 A (PoE power supply)
Mass	1.5 kg (3.31 lbs)
Dimensions (W x H x D) (mm)	W 210 mm x H 92 mm x D 177 mm (excluding protrusions)
Dimensions (W x H x D) (inch)	8-9/32 inches x 3-5/8 inches x 6-31/32 inches (excluding protrusions)
Display	3.5-type liquid crystal (QHD 960 x 540)
Connection Specifications	No. of Connectable Cameras :
	200 (IP), 5 (RS422)
	*Up to 100 for cameras other than the AW-UE150
	Remote Camera Selection :
	5 (6 to 200 controlled from the LCD)
	No. of Camera Groups :
	40 (5 units/group)
	No. of Memory Presets :
	100
Note	*PoE is the abbreviation for Power over Ethernet.