



The CCU supports UHD and HD simultaneous output while still having a compact size. HD mode enables output in 240p, 180p and 120p during normal filming.

AK-UCU600

With the AK-UCU600 Camera Control Unit (CCU), uncompressed longdistance transmission of 4K/HD video signals via optical fiber is supported. The AK-HRP1000GJ/1005GJ Remote Operation Panels (ROP) are equipped with a color LCD display that provides excellent visibility and functions for quick response. This system achieves high-quality video and excellent operability. In cases where power is supplied by the CCU, it is possible to transmit at a long distance of up to approx. 2,000 m between the camera and the CCU. The distance can be extended up to 10,000 m by providing a local power supply at the camera head and using general-purpose single mode optical fiber.

Key Features

Contains a dual UHD 12G-SDI system, and supports 3G-SDI quad link and two-sample interleave

Optical fiber transmission of uncompressed video signals over a distance of approx. 2,000 m between camera and CCU

Supports TICO over SDI (4K over 3G-SDI) output (4K signal can be transferred by a conventional 3G-SDI cable)

Supports HDR/SDR simultaneous output and HDR BT2020/B709 simultaneous output

Supports IP streaming (100 Base-T)





AK-UCU600

<https://latam.connect.panasonic.com/ar/es/ak-ucu600>

Camera Control Unit (CCU) -> General	AK-UCU600PJ/AK-UCU600PSJ 100 V - 120 V AC, 50 Hz/60 Hz
-> Power Supply	AK-UCU600EJ/AK-UCU600ESJ 100 V - 240 V AC, 50 Hz/60 Hz
Camera Control Unit (CCU) -> General	500 W (Without camera connected: 90 W)
-> Power Consumption	
Camera Control Unit (CCU) -> General	240 V AC (tolerance: 5 %), 1.46 A, 50 Hz / 60 Hz
-> Capacity for Supplying Power to a Camera	
Camera Control Unit (CCU) -> General	0 °C to 40 °C (32 °F to 104 °F)
-> Operating Temperature	
Camera Control Unit (CCU) -> General	10 % to 90 % (no condensation)
-> Humidity	
Camera Control Unit (CCU) -> General	Approx. 8.9 kg (19.6 lb)
-> Weight	
Camera Control Unit (CCU) -> General	W 424 mm x H 88 mm x D 401 mm (16-5/8 inches x 3-7/16 inches x 15-13/16 inches)
-> Dimensions	(excluding protrusions)
Camera Control Unit (CCU) -> Input/Output -> Video Output	3G/HD-SDI:5 lines (embedded audio is supported only for HD signals) 12G/6G/3G/HD-SDI:2 lines HD-SDI:1 line (shared with picture monitor output) Analog composite:2 lines (1 line shared with picture monitor output *1)
Camera Control Unit (CCU) -> Input/Output	HD-SDI 1 line (HD TRUNK output) 3G/HD-SDI 1 line (TICO output)
Camera Control Unit (CCU) -> Input/Output -> Return Input	3G-HD/HD/SD-SDI 4 lines (RET1 input has active-through output) Analog composite 1 line
Camera Control Unit (CCU) -> Input/Output -> Prompter Input	HD-SDI 1 line (with active-through output) Analog composite 2 lines (through output of 1 and input of 2 share the connector *1) It is not terminated when the unit is turned OFF. No through output.
Camera Control Unit (CCU) -> Input/Output -> Reference Input	BB (black burst) / tri-level *3: 1 line (automatic termination, connect to upper connector; BB signal and tri-level *3 signal automatically recognized, with loop-through output)
Camera Control Unit (CCU) -> Input/Output -> Microphone Output	0 dBm/600 Ω, 2 lines (XLR, 3-pin, male)
Camera Control Unit (CCU) -> Input/Output -> Communication	Intercom input/output (ENG / PROD, 0 dBm, 600 Ω (4 W) / 1 V [p-p], 200 Ω (RTS), 4 W / RTS / CLRCOM); 2 lines *1 PGM input (0 dBm/600 Ω); 2 lines *1 Tally input (red, green, yellow); 1 input each
Camera Control Unit (CCU) -> Input/Output -> AUX	WFM control 6-bit (open collector output *1, terminal shared with camera microphone gain setting *1) Camera microphone gain setting input 5-bit (photo-coupler input *1, terminal shared with WFM control *1) Down-conversion system setting input 2-bit (photo-coupler input)
Camera Control Unit (CCU) -> Input/Output -> TRUNK	RS-422 / RS-232C 2 lines
Camera Control Unit (CCU) -> Input/Output -> ROP	RS-422 1 line, 16 V DC output (only one of this and FRONT/REAR ROP can be selected at one time via the menu or the [ROP FRONT/REAR] selection switch on the front panel)
Camera Control Unit (CCU) -> Input/Output -> MSU	RS-422 1 line, GPI for control
Camera Control Unit (CCU) -> Input/Output -> LAN TRUNK	LAN connection with camera side via an optical cable *4 1 line, 100BASE-TX, 1000BASE-T
Camera Control Unit (CCU) -> Input/Output -> LAN	Personal computer connection for distribution via the Web *4 1 line, 10BASE-T, 100BASE-TX (use a crossover cable when connecting directly with a personal computer)
IP/12G/3G Interface Kit AK-NP600G -> General -> Operating Temperature	-> 0 °C to 40 °C (32 °F to 104 °F)
IP/12G/3G Interface Kit AK-NP600G -> General -> Operating Humidity	-> 10% to 90% (no condensation)
IP/12G/3G Interface Kit AK-NP600G -> General -> Weight	-> Approx. 284 g (0.63 lbs) (including radiator fins)
IP/12G/3G Interface Kit AK-NP600G -> General -> Dimensions	-> W 175.5 mm x H 28.8 mm x D 138.5 mm (6-29/32 inches x 1-1/8 inches x 5-7/16 inches)
IP/12G/3G Interface Kit AK-NP600G -> Input/Output -> < UHD/HS/HD SDI OUT1 > terminal	BNC x 1, 12G / 6G / 3G / 1.5G HD SDI : 0.8 V [p-p], 75 Ω
IP/12G/3G Interface Kit AK-NP600G -> Input/Output -> < UHD/HS/HD SDI OUT2 > terminal	BNC x 1, 12G / 6G / 3G / 1.5G HD SDI : 0.8 V [p-p], 75 Ω
IP/12G/3G Interface Kit AK-NP600G -> Input/Output -> < UHD/HS/HD SDI OUT3 > terminal	BNC x 1, 3G / 1.5G HD SDI : 0.8 V [p-p], 75 Ω

IP/12G/3G Interface Kit AK-NP600G - BNC x 1, 3G / 1.5G HD SDI: 0.8 V [p-p], 75 Ω	
> Input/Output - > < UHD/HS/HD SDI OUT4 > terminal	
IP/12G/3G Interface Kit AK-NP600G - BNC x 1, 1.5G HD SDI when HD TRUNK, 3G / 1.5G HD SDI when TICO : 0.8 V [p-p], 75 Ω	
> Input/Output - > < HD TRUNK/TICO OUT > terminal	
IP/12G/3G Interface Kit AK-NP600G - BNC x 1, 1.5G HD SDI: 0.8 V [p-p], 75 Ω	
> Input/Output - > < HD SDI/PROMPT IN > terminal	
IP/12G/3G Interface Kit AK-NP600G - SFP+ x 1, 10GBASE-LR	
> Input/Output - > < SFP+1 > slot	
IP/12G/3G Interface Kit AK-NP600G - SFP+ x 1, 10GBASE-LR	
> Input/Output - > < SFP+2 > slot	
IP/12G/3G Interface Kit AK-NP600G - RJ-45 x 1	
> Input/Output - > < LAN2 > terminal	
IP/12G/3G Interface Kit AK-NP600G -> Pillar (M3 x H20) x 1, Options rear panel x 1, Power cable x 1, Heat-transfer sheet x 1,	
Bundled Items	asks x 2
Footnote Description	<ol style="list-style-type: none"> 1. Depending on the setting, only one of them can be selected at one time. 2. For details on output formats, please see the "Supported formats". 3. The BB (black burst) signal and tri-level sync signal of the reference input are recognized automatically. 4. IP video cannot be transmitted when [CCU MODE] is set to [2160/23.98p], [2160/23.98PsF], [1080/23.98p], or [1080/23.98PsF].