

## Controlador de câmera remoto compacto

# AW-RP60GJ

Equipado com uma tela de menu GUI para visibilidade clara e um joystick para controle intuitivo. Controlador de câmera remoto compacto com suporte PoE\* para conexão de cabo único.

### Key Features

---

Equipado com uma tela LCD tipo 3,5

---

Recursos de personalização flexíveis

---

Novo Joystick com operabilidade aprimorada

---

Suporte PoE\*1/Ajuste avançado de câmera

---

\*1: PoE é a abreviatura de Power over Ethernet



## AW-RP60GJ

<https://latam.connect.panasonic.com/ar/pt/produtos/broadcast-proav/aw-rp60gj>

<b>General -&gt; Power Requirements</b>	12 V DC (10.8 V to 13.2 V)
<b>General -&gt; PoE</b>	PoE
	42 V to 57 V DC
<b>General -&gt; Current Consumption</b>	0.9 A (XLR connector input), 0.3 A (PoE power supply)
<b>General -&gt; Ambient Operating Temperature</b>	0 °C to 40 °C (32 °F to 104 °F)
<b>General -&gt; Ambient Operating Humidity</b>	20 % to 90 % (no condensation)
<b>General -&gt; Storage Temperature</b>	-20 °C to 50 °C (-4 °F to 122 °F)
<b>General -&gt; Weight</b>	1.5 kg (3.31 lbs)
<b>General -&gt; Dimensions</b>	W 210 mm x H 92 mm x D 177 mm  (8-9/32 inches x 3-5/8 inches x 6-31/32 inches)  (excluding protrusions)
<b>General -&gt; LCD Display</b>	3.5 inch LCD (QHD: 960 x 540)
<b>Input Connector -&gt; DC IN</b>	DC 12 V IN, XLR 4-pin
<b>Input/Output Connector -&gt; LAN (IP CONT)</b>	10BASE-T/100BASE-TX, PoE input
	Connecting cable: LAN cable, max. 100 m (328 ft)
	• When connecting the unit via a switching hub:  Straight cable (category 5e), STP (Shielded Twisted Pair) cable recommended
	• When connecting the unit directly:  Crossover cable (category 5e), STP (Shielded Twisted Pair) cable recommended
	• REMOTE:  Available only for LAN (RJ45) control
<b>Input/Output Connector -&gt; LAN (SERIAL CONT)</b>	RS-422 (control signals for remote cameras), TALLY OUT
	Connecting cable:  Straight cable (category 5e), max. 1000 m (3280 ft)
	TALLY OUT:  Open collector output (negative logic)
	Maximum voltage resistance DC 24 V, Maximum current 50 mA

<b>Input/Output Connector -&gt; TALLY / GPIO 1</b>	D-sub 25-pin, female, inch thread
	TALLY IN: Contact input (Status operation)
	GPIO IN: Contact input (Trigger operation)
	GPIO OUT: Open collector output (negative logic)
	Maximum voltage resistance DC 24 V, Maximum current 10 mA
<b>Connection Specifications -&gt; No. of Connectable Cameras</b>	200 (IP), 5 (RS422)
<b>Connection Specifications -&gt; No. of Camera Selection Buttons</b>	5 (6 to 200 controlled from the LCD)
<b>Connection Specifications -&gt; No. of Camera Groups</b>	40 (5 units/group)
<b>Memory -&gt; Preset Memory</b>	100

