



## Controle de Câmera Intuitivo para Facilidade de Uso e Melhor Visibilidade

### AW-RP150GJ

O AW-RP150 será o mais novo controlador remoto de câmeras para complementar a linha completa de câmeras PTZ profissionais da Panasonic. Ele mantém a excelente funcionalidade dos modelos AW-RP120 e AW-RP50, e se junta à linha com melhorias significativas em relação a esses modelos, incluindo um novo joystick para operação com uma mão (controlando PTZ ou foco) e uma grande tela LCD sensível ao toque para monitoramento e configuração de menus.

#### Key Features

Tela grande e sensível ao toque para fácil utilização.

Novo joystick para operação com uma única mão.

Predefinições de câmera PTZ simplificadas e memória de rastreamento.

Elementos de design intuitivos baseados em feedback direto de operadores de câmeras robóticas no cotidiano.

Saída ativa de 3G-SDI em passagem, 5 x RS-422, LAN PoE+, 2 x GPIOs



## AW-RP150GJ

<https://latam.connect.panasonic.com/ar/pt/produtos/broadcast-proav/aw-rp150gj>

<b>General -&gt; Power Requirements</b>	12 V DC (10.8 V to 13.2 V)
<b>General -&gt; PoE</b>	PoE+
	DC 42 V to 57 V (Camera Input,)
<b>General -&gt; Current Consumption</b>	1.0 A (Connector Input), 0.6 A (PoE+ power supply)
<b>General -&gt; Ambient Operating Temperature</b>	0 °C to 40 °C (32 °F to 104 °F)
<b>Humidity</b>	
<b>General -&gt; Storage Temperature</b>	10 % to 90 % (no condensation)
<b>General -&gt; Weight</b>	-20 °C to 50 °C (-4 °F to 122 °F)
<b>General -&gt; Dimensions</b>	Approx. 3.2 kg (7.05 lb)
	W 342 mm x H 178 mm x D 245 mm
	(13-15/32 inches x 7 inches x 9-21/32 inches)
	(excluding protrusions)
<b>Input Connector -&gt; DC IN</b>	DC 12 V IN, XLR 4-pin
<b>Input Connector -&gt; 3G-SDI IN</b>	SMPTE424M/SMPTE292 / 75 Ω (BNC x 1)
	Supported formats:
	1080/59.94p*2, 1080/50p*3, 1080/59.94i, 1080/50i, 1080/23.98p, 1080/25p, 1080/23.98PsF, 1080/25PsF
<b>Output Connector -&gt; 3G-SDI ACTIVE THROUGH OUT</b>	SMPTE424M/SMPTE292 / 75 Ω (BNC x 1)
	Supported formats:
	1080/59.94p*2, 1080/50p*3, 1080/59.94i, 1080/50i, 1080/23.98p, 1080/25p, 1080/23.98PsF, 1080/25PsF
<b>Input/Output Connector -&gt; LAN (IP CONT)</b>	100BASE-TX
	PoE+ input
	Connection cable: LAN cable, max. 100 m (328 ft)
	• When connecting the unit via a switching hub: Straight cable or a cross cable (category 5 cable), STP (Shielded Twisted Pair) cable recommended
	• When connecting the unit directly: Crossover cable (category 5 cable), STP (Shielded Twisted Pair) cable recommended
<b>Input/Output Connector -&gt; LAN (SERIAL CONT)</b>	RS-422 (control signals for remote cameras)
	Connecting cable:
	Straight cable (category 5e or better shielded cable), max. 1000 m (3280 ft)
<b>Input/Output Connector -&gt; TALLY OUT</b>	Open collector output (negative logic)
	Maximum voltage resistance DC 24 V, Maximum current 50 mA
<b>Input/Output Connector -&gt; TALLY / GPIO 1</b>	D-sub 25-pin, female, inch thread
	TALLY IN : 10 inputs (for receiving photocoupler signals)
	GPI : 6 inputs (for receiving photocoupler signals)
	GPIO : 5 inputs (for receiving photocoupler signals) or 5 outputs (open collector outputs, negative logic)
	• Input/output switched with menu settings
<b>Input/Output Connector -&gt; GPIO 2</b>	D-sub 25-pin, female, inch thread
	GPI : 10 inputs (for receiving photocoupler signals)
	GPIO : 10 inputs (for receiving photocoupler signals) or 10 outputs (open collector outputs, negative logic)
	• Input/output switched with menu settings
	Reserve connectors: 2 connectors (For future expansion feature)
<b>Input/Output -&gt; LCD Display</b>	7-inch Touch Panel GUI Monitor (WGA(800×480))
<b>Input/Output -&gt; SD Memory Card Slot</b>	SDHC / SDXC Memory Card Slot x 1
<b>Connection Specifications -&gt; No. of Connectable Cameras</b>	200 (IP), 5 (RS422)
<b>Connection Specifications -&gt; No. of Camera Selection Buttons</b>	10
<b>Connection Specifications -&gt; No. of Camera Groups</b>	20 (10 units per 1 group)
<b>Memory -&gt; Preset Memory</b>	No. of memory presets 100
<b>Memory -&gt; Tracing Memory</b>	No. of cameras: Cam1 to Cam10
	Recording time, no. of memory settings: Maximum 5 min. total per camera, maximum of 10 settings per camera

---

**Other Functions -> No. of User** 6 + up to 10 on the LCD menu

**Assignable Buttons**

---

**Other Functions -> Pan / Tilt Speed** 7 levels

**Adjustment**

---

**Other Functions -> TALLY LED Display** green / red

**Color:**

