Panasonic CONNECT



Flexible Options for Diverse Expression Based on Your Imagination

AW-UB10

AW-UB50/UB10 box-style 4K multi-purpose cameras boast large sensors that deliver exceptional detail and vibrant expression to diverse needs and preferences as well location scale. Panasonic's popular PTZ camera series, commonly used in broadcasting and other professional settings, can be seamlessly integrated to enhance the operational efficiency of video productions.

Key Features

10.2M MOS sensor for capturing multiple subjects in a single frame (AW-UB10)

Wide dynamic range with V-Log (AW-UB10: 13 stops)

Compact design (height, width & depth each less than 10cm, excluding lens)

Unified IP control protocol compatible with Panasonic PTZ camera systems

Compatible with Media Production Suite for multi-camera setups with PTZ cameras

Planned support for IP transmission standards including NDI(8) HX2, RTMPS, and SRT





AW-UB10

https://latam.connect.panasonic.com/bo/en/products/broadcast-proav/aw-ub10







Lens Mount	Micro four-thirds mount
Recording Media	SD Memory Card, SDHC Memory Card,* and SDXC Memory Card* for dual-slot recording
	*Slots 1 and 2 compatible with UHS-I/UHS-II UHS Speed Class 3 and UHS-II Video Speed Class 90 $$
Image Sensor	Four-thirds MOS sensor
	(Approx. 11.90 megapixels, square pixel color MOSsolid-state image sensor, primary colo filter)
Effective Pixels	Approx. 10.30 megapixels
Latitude	V-Log L: 13 stops
Video Format	MP4: H.264/MPEG-4 AVC and H.265/HEVC
	MOV: H.264/MPEG-4 AVC and H.265/HEVC
Photo Style	PTZ camera (UE160): Standard, Vivid, Natural, Flat, Landscape, Portrait, Cine-like D2,
	Cine-like V2, 709-like, V-LOG, 2100-like (HLG) and MY Photo Style 1-10
Genlock In	ON / OFF
Power Supply	When using Lithium-ion battery pack: 7.28 V
	When using included AC adapter: 12 V/3 A When using PoE+ compatible hub: IEEE802.3at compliant
Weight	Approx. 545 g (1.20 lb) (body only, without lens cap)
Dimensions (W x H x D)	Approx. 93.0 mm x 93.0 mm x 78.0 mm
	(3-21/32 inches x 3-21/32 inches x 3-5/64 inches)
Supported Protocols	RTP / RTSP
Included Accessories	SAE0011AM AC adaptor
Software	Media Production Suite
	LUMIX Tether
	ON / OFF supported
	ON / OFF supported

ON / OFF supported