



La serie PT-RZ690 ofrece el brillo, la resolución y el color que los diseñadores necesitan para mejorar las exposiciones con imágenes brillantes, llamativas y nítidas

## PT-RZ690

Mejora la capacidad envolvente de cualquier entorno con unos colores intensos y precisos de hasta 10 000 lm\*1 de brillo gracias al armonizador cromático de cuarteto y a la tecnología de imagen de 1 chip DLP™. Compatibles con señales de entrada 4K/60p, terminales independientes DIGITAL LINK y LAN y diversos objetivos opcionales, estos proyectores reducen las molestias de la instalación gracias a su

### Key Features

Láser de 1 chip DLP, 6,200 lm (en el centro) / 6,000 lm (ANSI), WUXGA

Tecnología Quartet Colour Harmonizer para una reproducción cromática más precisa

No necesita mantenimiento durante un mínimo de 20.000 horas, con un bloque óptico resistente a la entrada de polvo y un motor láser duradero

Compatible con entrada de señal 4K/60p y terminales independientes DIGITAL LINK y LAN





## PT-RZ690

<https://latam.connect.panasonic.com/bo/es/products/projectors/pt-rz690>

<b>Projector type</b>	1-Chip DLP™ projector
<b>DLP™ Chip   Panel Size</b>	17.0 mm (0.67 in) diagonal ( Panel size 16:10 aspect ratio)
<b>DLP™ Chip   Display Method</b>	DLP™ chip x 1, DLP™ projection system
<b>DLP™ chip   Number of Pixels</b>	2,304,000 (1920 x 1200 pixels)
<b>Light Source</b>	Laser diodes
<b>Light output</b>	6,000 lm (Normal)*1 / 6,200 lm (Center)*2 / 4,800 lm (Eco)*1 / 2,400 lm (Long Life 1)*1 / 2,000 lm (Long Life 2)*1 / 1,600 lm (Long Life 3)*1
<b>Time until light output declines to 50 %*3</b>	20,000 hours (Normal)/24,000 hours (Eco)
<b>Resolución</b>	1920 x 1200 pixels
<b>Contrast Ratio*1</b>	10,000:1 (Full On/Full Off, Dynamic Contrast [3] )
<b>Screen size [diagonal]</b>	1.27–15.24 m (50–600 in), 1.27–5.08 m (50–200 in) with ET-DLE055, 2.54–8.89 m (100–350 in) with ET-DLE035, 2.54–10.16 m (100–400 in) with ET-DLE020, 16:10 aspect ratio
<b>Center-to-corner zone ratio*1</b>	90 %
<b>Lens</b>	With supplied lens: Powered zoom (throw ratio 1.71–2.41:1), powered focus F 1.7–1.9, f 25.6–35.7 mm Without lens: Optional powered zoom/focus lenses
<b>Lens shift*4   Vertical(From the origin point of the lens mounter)</b>	+50 %, -16 % (+40 %, -16 % with ET-DLE060) (powered)
<b>Lens shift*4   Horizontal(From the origin point of the lens mounter)</b>	+30 %, -10 % (+10 %, -20 % with ET-DLE020, +19 %, -10 % with ET-DLE060, +28 %, -10 % with ET-DLE105/ET-DLE085) (powered)
<b>Keystone Correction Range</b>	Vertical: ±40 ° (±5 ° with ET-DLE020, ±16 ° with ET-DLE060, ±22 ° with ET-DLE105/ET-DLE085/ET-DLE055, +5 ° with ET-DLE035), Horizontal: ±15 ° (±10 ° with ET-DLE060) (cannot be operated with ET-DLE035/ET-DLE020)
<b>Keystone correction range with optional ET-UK20 Upgrade Kit</b>	Vertical: ±45 ° (±16 ° with ET-DLE060, ±40 ° with ET-DLE150/ET-DLE250/ET-DLE170, ±22 ° with ET-DLE105/ET-DLE085/ET-DLE055), Horizontal: ±40 ° (±10 ° with ET-DLE060, ±15 ° with ET-DLE105/ET-DLE085/ET-DLE055) When [VERTICAL KEYSTONE] and [HORIZONTAL KEYSTONE] are used simultaneously, correction cannot be made exceeding a total of 55 °.
<b>Terminals   SDI In</b>	BNC x 1: 3G/HD/SD-SDI input
<b>Terminals   HDMI In</b>	HDMI 19-pin x 1 (Compatible with HDCP 2.2, Deep Color, 4K/60p signal input*5 )
<b>Terminals   DVI-D In</b>	DVI-D 24-pin x 1 (DVI 1.0 compliant, compatible with HDCP, compatible with single link only)
<b>Terminals   RGB 1 In</b>	RGB x 1 (BNC x 5): RGB/YBPBR/YCBCR
<b>Terminals   RGB 2 In</b>	D-sub HD 15-pin (female) x 1: RGB/YBPBR/YCBCR
<b>Terminals   Serial/Multi Projector Sync In</b>	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
<b>Terminals   Serial/Multi Projector Sync Out</b>	D-sub 9-pin (male) x 1 for link control
<b>Terminals   REMOTE 1 IN</b>	M3 x 1 for wired remote control
<b>Terminals   REMOTE 1 OUT</b>	M3 x 1 for link control (for wired remote control)
<b>Terminals   Remote 2 In</b>	D-sub 9-pin (female) x 1 for external control (parallel)
<b>Terminals   DIGITAL LINK</b>	RJ-45 x 1 for network and DIGITAL LINK connections (HDBase™ compliant), PjLink™ (Class 2) compatible, 100Base-TX, Art-Net compatible, HDCP 2.2 compatible, Deep Color compatible, 4K/60p signal input*5
<b>Terminals   LAN</b>	RJ-45 x 1 for network connection, PjLink™ (Class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible
<b>Power Supply</b>	AC 100–240 V, 50/60 Hz
<b>Power Consumption</b>	490 W (Normal)/395 W (Eco)/ 200 W (Long Life 1)/180 W (Long Life 2)/ 160 W (Long Life 3)
<b>Operation noise*1</b>	35 dB (Normal)
<b>Dimensiones (AnxAxBxP)</b>	With supplied lens: 498 x 200*6 x 581 mm (19 19/32" x 7 7/8" *6 x 22 7/8") Without lens: 498 x 200*6 x 538 mm (19 19/32" x 7 7/8" *6 x 21 3/16")
<b>Weight*7</b>	With supplied lens: Approx. 22.1 kg (48.7 lbs) Without lens: Approx. 21.3 kg (47.0 lbs)
<b>Operating Environment</b>	Operating temperature: 0–45 °C (32–113 °F)*8 , operating humidity: 10–80 % (no condensation)
<b>Applicable Software</b>	Logo Transfer Software, Multi Monitoring & Control Software, Early Warning Software, Geometry Manager Pro (ET-UK20 Upgrade Kit, ET-CUK10 Auto Screen Adjustment Kit), Smart Projector Control for iOS/Android™

**Note**  
\*1 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2012 international standards. Value is average of all products when shipped. \*2 Average light-output value of all shipped products measured at center of screen in NORMAL Mode. \*3 Around this time, light output will have decreased by approximately 50 %. IEC62087: 2008 Broadcast contents, NORMAL Mode, Dynamic Contrast [ON], under conditions with 35 °C (95 °F), 700 m (2,297 ft) above sea level, and 0.15 mg/m3 of particulate matter. Estimated time until light output declines to 50 % varies depending on environment. \*4 Lens shift is not supported on the ET-DLE055, and the optical axis is fixed with the ET-DLE035. \*5 4K signals are converted to the projector's resolution (1920 x 1200 pixels) upon projection. Supported terminals: DIGITAL LINK/HDMI @. \*6 Excluding legs. \*7 Average value. May differ depending on the actual unit.

