Panasonic CONNECT



**Zoom lens for PT-MZ16K/PT-MZ13K/PT-MZ10K**

# ET-EMU100

Throw Ratio 0.330 – 0.353:1 (Aspect 16:10)0.329 – 0.353:1 (Aspect 16:9)0.396 – 0.425:1 (Aspect 4:3)

**Key Features**

- Ultra-Short-Throw Versatility with Zero Offset
- Flexibility Streamlines Installation Workflow
- Durability for Peace of Mind

Panasonic CONNECT

# ET-EMU100

https://latam.connect.panasonic.com/bo/es/et-emu100

| | |
|---|---|
| **Lens type** | Ultra-Short-Throw Zoom Lens |
| **F-number** | 1.9 |
| **Focal length (f)** | 7.23 mm - 7.73 mm [9/32 - 5/16"] |
| **Screen size** | 100–400 inches |
| **Throw ratio -> WUXGA** | 0.330 - 0.353:1 |
| **Lens-shift -> Vertical** | PT-MZ16K/PT-MZ13K/PT-MZ10K : +50 % – -20 % *1 |
| **Lens-shift -> Horizontal** | PT-MZ16K/PT-MZ13K/PT-MZ10K : ±20 % *1 |
| **Zoom** | x1.07 |
| **Dimensions -> (W)** | 200 mm (7 7/8″) |
| **Dimensions -> (H)** | 200 mm (7 7/8″) |
| **Dimensions -> (D)** | 509 mm (20 1/32″) |
| **Weight** | 7.20 kg (15.87 lbs) |
| **Applicable projectors** | PT-MZ16KL/PT-MZ13KL/PT-MZ10KL |
| **Throw ratio -> WXGA** | 0.330 - 0.353:1 |
| **Throw ratio -> XGA** | 0.396 - 0.425:1 |
| **Dimensions(WxHxD)** | 200 × 200 × 509 mm (7-7/8 × 7-7/8 × 20-1/32") |
| **Throw Ratio** | WUXGA (0.330–0.353:1) |
| **Compatibiliy** | PT-MZ20KL, PT-MZ17KL, PT-MZ14KL, PT-MZ11KL |
| **Footnote Description** | * When PT-RQ50K's handle is attached, vertical lens-shift range is -8 % – +50 %. Vertical lens-shift range is -50 % – +50 % with PT-RQ50K's supplied handle removed. Please refer to instruction guide for details on how to remove the handle. |