Panasonic CONNECT



LCD Colour Viewfinder

AK-HVF100

Light weight and high resolution (9-type IPS LCD 1920*1080, 1,100 TV lines) viewfinder with built-in mechanical lift versatile assist functions

Key Features

- Focus assist functions
- External HD-SDI Input and 12V 4-pin XLR input
- Four assignable function switches
- Contrast, brightness and peaking are adjustable

Panasonic CONNECT






AK-HVF100

https://latam.connect.panasonic.com/bo/es/ak-hvf100

General -> Power Supply	DC 12 V (supplied from camera or XLR)
General -> Power Consumption	18 W
General -> Operating Temperature	0 °C to 45 °C (32 °F to 113 °F)
General -> Operating Humidity	10% - 85% (no condensation)
General -> Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
General -> Weight	Approx. 2.6 kg (5.73 lbs.) (not including hood) / Approx. 3.0 kg (6.61 lbs.) (including hood)
General -> Dimensions	W 340 mm x H 234 mm x D 193 mm (13-13/32 inches x 9-7/32 inches x 7-5/8 inches) (not including hood) W 340 mm x H 234 mm x D 231 mm (13-13/32 inches x 9-7/32 inches x 9-1/8 inches) (including hood)
Display Panel -> Dimensions	22.9cm (9.0 inches)
Display Panel -> Number of Pixels	1920 x 1080 (FHD)
Display Panel -> Display Color	Approx. 16.77 million colors
Switch Functions and Connectors -> Operation	<POWER> switch, <MENU> button, <SELECT> dial button, <F1>/<F2>/<F3>/<F4> buttons, <BRIGHT> knob, <CONTRAST> knob, <PEAKING> knob, <INPUT> switch
Switch Functions/Connectors -> Connector	Camera I/F connector (D-sub 29 pins x 1) SDI IN connector (BNC x 1) DC IN connector (XLR 4 pins x 1)
Supported Signal Format -> CAM	1080/59.94i, 1080/50i
Supported Signal Format -> SDI	1080/59.94p, 1080/50p, 1080/59.94i, 1080/50i, 720/59.94p, 720/50p