



**Easy-to-Manage, Super Simple 1 Chip DLP™ Laser Projector delivers Clear Pictures in Bright Rooms with Flexible Integration in diverse installation environments**

## PT-FRZ55

DLP™ imaging technology, Quartet Colour Harmonizer, Rich Colour Enhancer, and digitally modulated Dynamic Contrast 2 optimization coalesce in images of surpassing brightness, colour, and clarity regardless of ambient light levels. Powered 0.8:1 short-throw lens for rear projection joins DIGITAL LINK and CEC-ready HDMI® terminals

### Key Features

---

Laser 1-chip DLP, 5,000 lumens, WUXGA

---

DLP™ imaging technology, Quartet Colour Harmonizer, Rich Colour Enhancer, and digitally modulated Dynamic Contrast 2 optimization

---

Maintenance free up to 20,000 hours with dust-resistant optical block and long lasting laser engine

---

0.8:1 short-throw lens

---

Supports uncompressed 4K/60p input signals via HDCP 2.2-compliant HDMI® inputs or DIGITAL LINK terminal





## PT-FRZ55

<https://latam.connect.panasonic.com/bo/es/productos/proyectores/pt-frz55>

<b>Projector type</b>	1-Chip DLP™ projector
<b>Display method</b>	DLP™ chip x 1, DLP™ projection system
<b>Display Device -&gt; Panel size</b>	17.0 mm (0.67 in) diagonal (16:10 aspect ratio)
<b>Display Device -&gt; Number of pixels</b>	2,304,000 (1920 x 1200 pixels)
<b>Light source</b>	Laser diodes
<b>Light output</b>	5,000 lm
<b>Light output (ANSI)</b>	5,000 lm
<b>Light output (Center) *2 *4</b>	5,200 lm (Center)
<b>Time until light output declines to</b>	20,000 hours [NORMAL]
<b>50 % -&gt; NORMAL</b>	
<b>Resolution</b>	1920 x 1200 pixels
<b>Contrast Ratio (typ.)</b>	20,000:1 (Full On/Full Off, Picture Mode: Dynamic, Dynamic Contrast 1, Operating Mode: Normal)
<b>Screen size (diagonal)</b>	1.02-7.62 m (40-300 in), 16:10 aspect ratio
<b>Center-to-corner zone ratio</b>	85%
<b>Lens</b>	Fixed (throw ratio: 0.8:1), powered focus, F1.75, f 11.9 mm
<b>Lens shift -&gt; Vertical (from center) ±4.4 % (powered) of screen)</b>	
<b>Lens shift -&gt; Horizontal (from center of screen)</b>	±2.1 % (powered)
<b>Keystone correction range</b>	Vertical: ±25 °, Horizontal: ±20 °
<b>Installation</b>	Ceiling/floor, front/rear, free 360-degree installation
<b>Terminals -&gt; HDMI™ IN</b>	HDMI™ 19-pin x 2 (Compatible with HDCP 2.3, Deep Color, 4K/60p signal input*4), CEC supported
<b>Terminals -&gt; COMPUTER IN (D- SUB 15pin )</b>	D-sub HD 15-pin (female) x 1 (RGB/YPBPR/YCBCR)
<b>Terminals -&gt; COMPUTER OUT (D- D-sub HD 15-pin (female) x 1 (RGB/YPBPR/YCBCR) SUB 15pin )</b>	
<b>Terminals -&gt; VIDEO IN</b>	Pin jack x 1 (composite video)
<b>Terminals -&gt; AUDIO IN(M3 Stereo Mini Jack)</b>	Pin jack x 1 (L, R)
<b>Terminals -&gt; AUDIO IN(Pin Jack L/R)</b>	M3 x 1 / M3 x 1
<b>Terminals -&gt; AUDIO OUT(M3 Stereo Mini Jack)</b>	M3 x 1 (Variable)
<b>Terminals -&gt; SERIAL IN</b>	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
<b>Terminals -&gt; DIGITAL LINK IN / LAN</b>	RJ-45 x 1 for network and DIGITAL LINK connections (HDBaseT™ compliant), PJLink™ (Class 2) compatible, 100Base-TX, Art-Net compatible, HDCP 2.3 compatible, Deep Color compatible, 4K/60p signal input*4
<b>Terminals -&gt; LAN</b>	RJ-45 x 1 for network connection, PJLink™ (Class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible
<b>Terminals -&gt; USB TYPE A</b>	USB connector (Type A) x 1 (Output 5 V/2 A)
<b>Power supply</b>	AC 100-240 V, 50/60 Hz
<b>Maximum power consumption</b>	465 W (5.0-2.0 A)
<b>On-mode power</b>	[NORMAL] 370 W
<b>consumption(Operating mode) -&gt; Normal</b>	
<b>On-mode power</b>	[ECO] 295 W
<b>consumption(Operating mode) -&gt; Eco</b>	
<b>On-mode power</b>	[QUIET] 295 W
<b>consumption(Operating mode) -&gt; Quiet</b>	
<b>Standby power consumption -&gt; Normal</b>	10 W (Standby Mode) [NORMAL]
<b>Standby power consumption -&gt; ECO</b>	0.5 W (Standby Mode) [ECO]
<b>Cabinet materials</b>	Molded plastic
<b>Filter</b>	No
<b>Operation noise -&gt; Normal</b>	32 dB [NORMAL]
<b>Operation noise -&gt; Quiet</b>	27 dB [QUIET]
<b>Dimensions (W x H x D)</b>	498 x 168*5 x 481 mm (19 5/8" x 6 5/8" *5 x 18 15/16")
<b>Dimensions -&gt; Width (including protruding parts)</b>	498 mm (19 5/8")
<b>Dimensions -&gt; Height (including protruding parts)</b>	168 mm (6 5/8")
<b>Dimensions -&gt; Depth (including lens)</b>	481 mm (18 15/16")

<b>Weight</b>	Approx. 16.4 kg (36.1 lbs)
<b>Operating environment -&gt;</b>	0-45 °C (32-113 °F)
<b>Operating temperature</b>	
<b>Operating Environment -&gt;</b>	10-80 % (no condensation)
<b>Operating humidity (No condensation)</b>	
<b>Applicable software</b>	Logo Transfer Software, Multi Monitoring & Control Software, Early Warning Software
<b>Footnote Description</b>	<p>1. When [PICTURE MODE] is set to [DYNAMIC], [DAYLIGHT VIEW] is set to [OFF], [DYNAMIC CONTRAST] is set to [OFF], [LIGHT OUTPUT] is set to [100%], and [AUTO POWER SAVE] is set to [OFF].</p> <p>2. Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is the average of all products when shipped.</p> <p>3. Measurement, measuring conditions, and method of notation all comply with American National Standards Institute standards. Value is the average of all products when shipped.</p> <p>4. Average light-output value of all shipped products measured at the center of the screen.</p> <p>5. Around this time, light output will have decreased by approximately 50 %. IEC62087: 2008 Broadcast Contents, Normal Mode, Dynamic Contrast 2, temperature 30 °C (86 °F), elevation 700 m (2,297 ft) with 0.15 mg/m<sup>3</sup> of airborne particulate matter. Estimated time until light output declines to 50 % varies depending on environment.</p> <p>6. 4K signals are converted to the projector's resolution (1920 x 1200 pixels) upon projection. Supported terminals: DIGITAL LINK/HDMI®.</p> <p>7. With legs at shortest position.</p> <p>8. Average value. May differ depending on the actual unit.</p>

<b>Body Colour</b>	Black
<b>NFC</b>	<a href="https://docs.connect.panasonic.com/projector/products/smartpjcontrol/regional.html#regional">https://docs.connect.panasonic.com/projector/products/smartpjcontrol/regional.html#regional</a>