Panasonic CONNECT



**El proyector de 8.000 lm*1 más pequeño y ligero del mundo mejora la comunicación en espacios muy iluminados**

# PT-VMZ62

Presentamos la serie VMZ82: el proyector más pequeño y ligero del mundo en su clase1, que ofrece hasta 8.000lm2 para obtener imágenes nítidas y vibrantes en espacios bien iluminados. Estos intuitivos proyectores LCD se integran a la perfección en cualquier diseño, minimizando las distracciones y simplificando la instalación con características exclusivas. Con un cuerpo elegante que contiene plástico reciclado y está diseñado para un funcionamiento eficiente y de bajo mantenimiento, la serie VMZ82 revitaliza la calidad de la comunicación en oficinas, aulas y más.

**Key Features**

- Proyección nítida adaptada a cada espacio
- Instalación flexible y sin estrés
- Diseño eficiente y respetuoso con el medio ambiente

Panasonic CONNECT



# PT-VMZ62

https://latam.connect.panasonic.com/bo/es/productos/proyectores/pt-vmz62

| | |
|---|---|
| **Projector type** | LCD projectors |
| **Display method** | Transparent LCD panel (x 3, R/G/B) |
| **Display Device -> Panel size** | 16.3 mm (0.64 inch) (16:10 aspect ratio) |
| **Display Device -> Number of pixels** | 2,304,000 (1920 x 1200) pixels x 3 |
| **Light source** | Laser diodes |
| **Light output** *1 *2 | VMZ82 : 8,000 lm*2<br>VMZ72 : 7,200 lm*2<br>VMZ62 : 6,500 lm*2 |
| **Light output (ANSI)** *1 *3 | VMZ82 : 8,000 lm (ANSI)*3<br>VMZ72 : 7,200 lm (ANSI)*3<br>VMZ62 : 6,500 lm (ANSI)*3 |
| **Time until light output declines to 50 % -> NORMAL** *5 | 20,000 hours [NORMAL] |
| **Time until light output declines to 50 % -> ECO** *5 | 24,000 hours [ECO] |
| **Time until light output declines to 50 % -> QUIET** *5 | 20,000 hours [QUIET] |
| **Resolution** | WUXGA (1920 x 1200 pixels) |
| **Contrast Ratio (typ.)** *2 | 5,000,000:1 (Full On/Full O) (When [PICTURE MODE] is set to [DYNAMIC] and [DYNAMIC CONTRAST] is set to [1].) |
| **Screen size (diagonal)** | 0.76–7.62 m (30–300 in), 16:10 aspect ratio |
| **Center-to-corner zone ratio** *2 | 85 % |
| **Lens** | 1.6x manual zoom (throw ratio: 1.09–1.77:1), manual focus lens, F=1.58-1.91, f=15.30–24.60 mm |
| **Digital Zoom Extender** *6 | Throw Ratio 1.09–2.21:1*6 (Corresponding value. When used together with optical zoom.) |
| **Lens shift -> Vertical(from center of screen)** | +44 % |
| **Lens shift -> Horizontal(from center of screen)** | ±20 % |
| **Keystone correction range** | Vertical ±25 %, Horizontal ±35 % |
| **Terminals -> HDMI™ IN** | HDMI™ 19-pin x 2 (Compatible with HDCP, Deep Color, 4K/30p*7 signal input), CEC supported*8 |
| **Terminals -> COMPUTER IN (D-SUB 15pin)** | D-sub 15-pin (female) (RGB/$YP_BP_R$/$YC_BC_R$) |
| **Terminals -> AUDIO IN(M3 Stereo Mini Jack)** | M3 stereo mini-jack x 1 |
| **Terminals -> AUDIO OUT(M3 Stereo Mini Jack)** | M3 stereo mini-jack x 1 |
| **Terminals -> SERIAL IN** | D-sub 9-pin (female) x 1 for computer control (RS-232C compliant) |
| **Terminals -> DIGITAL LINK IN / LAN** | RJ-45 x 1 for network and DIGITAL LINK connection (video/network/serial control) (HDBaseT™ compliant), 100Base-TX (Compatible with PJLink™ [Class 2],HDCP, Deep Color, 4K/30p*7 signal input) |
| **Terminals -> LAN** | RJ-45 x 1 for network control, 10Base-T, 100Base-TX, compatible with PJLink™[Class 2] |
| **Terminals -> USB TYPE A** | USB Connector Type A x 1 for Memory Viewer function, optional AJ-WM50 Series Wireless Module, power supply (DC 5 V, maximum 2 A*9) |
| **Protocol versions** | IPv4, IPv6*10 |
| **Power supply** | AC 100–240 V, 50/60 Hz |
| **Maximum power consumption** *12 | 320 W (3.3 A) (325 VA)<br>(Power consumption is 305 W at 200–240 V) |
| **On-mode power consumption(Operating mode) -> Normal** *12 | 280 W (100–240 V), 270 W (200–240 V) [NORMAL] |
| **On-mode power consumption(Operating mode) -> Eco** *12 | 215 W (100–240 V), 205 W (200–240 V) [ECO] |
| **On-mode power consumption(Operating mode) -> Quiet** *12 | 245 W (100–240 V), 235 W (200–240 V) [QUIET1]<br>210 W (100–240 V), 200 W (200–240 V) [QUIET2] |
| **Built-in speaker** | 10 W monaural |
| **Cabinet materials** | Molded plastic |
| **Filter** *13 | Included |
| **Estimated filter maintenance cycle** | Approx. 20,000 hours |
| **Operation noise -> Normal** *2 | 35 dB [NORMAL] |
| **Operation noise -> Eco** *2 | 35 dB [ECO] |

| | |
|---|---|
| **Operation noise -> Quiet** *2 | 30 dB [QUIET1]<br>25 dB [QUIET2] |
| **Dimensions (W x H x D)** | 399 mm x 115 mm x 348 mm (15 23/32″ x 4 17/32″ x 13 11/16″ ) (not including protruding parts)<br>399 mm x 133 mm x 348 mm (15 23/32″ x 5 1/4″ x 13 11/16″ ) (with feet at shortest position) |
| **Weight** *14 | Approx. 6.9 kg (15.2 lbs) |
| **Operating environment -> Operating temperature** *15 *16 | 0–45 °C (32–113 °F)*14,*15 |
| **Operating Environment -> Operating humidity (No condensation)** | 20–80 % (no condensation) |
| **Applicable software** | Multi Monitoring & Control Software, Projector Network Setup Software, Presenter Light Software for Windows®*16, Wireless Projector App for iOS/Android™*17 |
| **Terminals -> SDI IN** | – |
| **Terminals -> DVI-D IN** | – |
| **Terminals -> DisplayPort™ IN** | – |
| **Body Colour** | PT-VMZ62-WhitePT-VMZ62EJ-WhitePT-VMZ62B-BlackPT-VMZ62BEJ-BlackPT-VMZ62J-WhitePT-VMZ62D8-White |
| **Gross Dimensions (W x H x D in mm)** | VMZ62/VMZ62B/VMZ62J/VMZ62D8: Approx. 538 x 260 x 466 mm<br>VMZ62EJ/VMZ62BEJ: Approx. 546 x 276 x 474 mm |
| **Gross Weight (Kg)** | VMZ62/VMZ62B: 10.4 kg (23.0 lbs)VMZ62J: 9.7 kg (21.4 lbs)VMZ62D8: 11.0 kg (24.2 lbs)VMZ62EJ/VMZ62BEJ: 11.4 kg (25.2 lbs) |
| **NFC** | No |
| **Active 3D** | No |
| **SDM** | No |
| **EAN** | PT-VMZ62: 5025232969333<br>PT-VMZ62EJ: 5025232969326<br>PT-VMZ62B: 5025232969364<br>PT-VMZ62BEJ: 5025232969340<br>PT-VMZ62D8: 8887549898921 |
| **Footnote Description** | 1. When [PICTURE MODE] is set to [DYNAMIC] and [LIGHT POWER] is set to [NORMAL].<br>2. Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped.<br>3. Measurement, measuring conditions, and method of notation all comply with American National Standards Institute standards. Value is the average of all products when shipped.<br>4. Around this time, light output will have decreased to approximately 50 % of its original level ([PICTURE MODE]: [DYNAMIC], [DYNAMIC CONTRAST] set to [2]). Estimated time until li ght output declines to 50 % varies depending on environment.<br>5. Resolution decreases when using Digital Zoom Extender. Grid Adjustment, 6-Point Screen Correction, V/H Keystone Correction, and curved-screen correction are not available when using this function. The range of corner adjustment is limited.<br>6. When Digital Zoom Extender is set to 80 %.<br>7. 4K signals are converted to the projector's resolution upon projection.<br>8. Depending on the connected CEC command compatible device, the link control may not operate normally.<br>9. On standby, power supply is available with Quick Startup set to ON or Power Management set to Ready.<br>10. The optional AJ-WM50 Series Wireless Module does not support IPv6.<br>11. Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. On-mode power consumption measured at 25 °C (77 °F) operating temperature at an altitude of 700 m (2,297 ft).<br>12. Filter cleaning cycle varies depending on the environment. The filter can be washed and reused up to two times. Filter cleaning cycle: 20,000 hours (under dust conditions of 0.08 mg/m3), 10,000 hours (under dust conditions of 0.15 mg/m3).<br>13. Average value. May differ depending on the actual unit.<br>14. Light output is limited at operating temperatures higher than 30 °C (86 °F), and projectors cannot be operated at altitudes higher than 2,700 m (8,858 ft) above sea level.<br>15. When the optional AJ-WM50 Series Wireless Module is attached, the operating temperature range becomes 0–40 °C (32–104 °F).<br>16. When using Presenter Light Software, images are projected with 1280 x 800 dots or 1024 x 768 dots onto the screen. Also, your PC display resolution may be forcibly changed, and audio playback disrupted or become noisy while images and sound are being transmitted.<br>17. When using the Wireless Projector app, display resolution di§ers depending on your iOS/Android™ device and the display device. The maximum supported display resolution is WXGA (1280 x 800). |