



Various production types are supported through high-speed and highly efficient mounting of oddform components.

NPM-TT2

High-speed and highly efficient placement of odd-form components is achieved by arranging the tray feeders at front/rear, thus contributing to total productivity improvement

Key Features

Direct connectivity with NPM-D3/W2

Placement heads (lightweight 8-nozzle head, 3-nozzle head v2)

Selectable and configurable supply unit specifications

Adoption of multi-mode recognition camera

Alternate and independent mounting support



NPM-TT2

https://latam.connect.panasonic.com/br/en/npm-tt2

Model Number	NM-EJM1E
PCB dimensions (mm)	PC sizeSingle-lane mode: L 50 mm × W50 mm to L 510 mm × W 590 mmDual-lane mode: L 50 mm × W50 mm to L 510 mm × W 300 mmM sizeSingle-lane mode: L 50 mm × W50 mm to L 510 mm × W 510 mmDual-lane mode: L 50 mm × W 510 mm V W 260 mm
PCB exchange	Single-lane mode: 4.0 s (With no component mounted on the reverse side of PCB)Dual-lane mode: 0 s (No 0s when cycle time is 4.0 s or less)
Electric Source	3-phase AC 200 , 220 , 380 , 400 , 420 , 480 V 2.5 kVA
Pneumatic Source	Min.0.5 MPa、200 L / min (A.N.R.) (Only for main body)
Dimension	W 1 300 mm × D 2 798 mm × H 1 444 mm Note : Machine dimensions and mass for standard configuration(NPM-TT2 and Tray feeder x 2).They differ depending on the optional configuration.W 1 300 mm × D 2 781 mm × H 1 444 mm Note : Dimensions and mass of the machine andtwo ASF carts (34-slot).They differ depending on the optional configuration.
Mass	3 090 kgNote: Machine dimensions and mass for standard configuration (NPM-TT2 and Tray feeder x 2). They differ depending on the optional configuration. 2 880 kgNote: Dimensions and mass of the machine and two ASF carts (34-slot). They differ depending on the optional configuration.
Placement Head	Lightweight 8-nozzle head 3-nozzle head V2
Stick	Max.28 (Single stick feeder)
Tray	Max.40
Placement Head max Speed	PC sizeLightweight 8-nozzle head (Per head): 18 000 cph (0.20 s / chip)3-nozzle head V2 (Per head): 7 200 cph(0.50 s / chip) 5 900 cph (0.61 s / QFP)* at optimum conditionsM sizeLightweight 8-nozzle head (Per head): 17 460 cph (0.21 s / chip)3-nozzle head V2 (Per head): 6 984 cph (0.52 s / chip) 5 723 cph (0.63 s / QFP)* at optimum conditions
Placement Head Placement Accuracy (Cpk≥1)	Lightweight 8-nozzle head : $\pm40~\mu$ m / chip $\pm30~\mu$ m / QFP* at optimum conditions3-nozzle head V2: $\pm40~\mu$ m / chip $\pm30~\mu$ m / QFP* at optimum conditions
Placement Head Component Dimensions (mm)	Lightweight 8-nozzle head : 0402 chip to L 45 \times W 45 \times T 12or L 100 \times W 40 \times T 123-nozzle head V2: 0603 chip to L 120 \times W 90 \times T 30 or L 150 \times W 25 \times T 30or L 135 \times W 135 \times T 13 (\square 135 mm is option.)
Component Supply Taping	Lightweight 8-nozzle head : Tape : $4/8/12/16/24/32/44/56/72$ mm3-nozzle head V2: Tape : 4 to $72/88/104$ mm