



## Control Panel Standard Type

### AT-KC10C1

The “Kairos Control” panel is available in two models: 24XPT standard layout (AT-KC10C1) and 12XPT compact layout (AT-KC10C2).\* The panels allow functions to be assigned freely. Indicators show the functions assigned to individual buttons. Multi-scene operation is supported with two ME layouts and two faders. Multiple panels can be used simultaneously within a single system.

#### Key Features

24XPT standard layout. The panels allow functions to be assigned freely.

Multi-scene operation is supported with two ME layouts and two faders.

Indicators show the functions assigned to individual buttons.

Multiple panels can be used simultaneously within a single system.

A transition fader of the panel supports A/B mode in addition to PGM/PST mode.

AT-KC10C1

<https://latam.connect.panasonic.com/br/en/kc10c1>

General	
Power Requirement	DC 12V, 8.0A - XLR 4pin x 2 (Redundant)
Operating Temperature	0 to 40 degree Celsius
Operating Humidity	10% to 90% (no condensation)
Weight	Approx. 15.4 kg / 33.95 lb
Dimensions (W x H x D)	1140 mm x 94 mm x 420 mm 44.9 in. x 3.7 in. x 16.5 in. Excluding protrusion
Control Terminals	
LAN (Rear Panel)	RJ-45 x 1, 1GbE
USB (Control Panel)	USB2.0 typeA x 1
USB (Rear Panel)	USB2.0 typeA x 1