



## PT-MZ20KL

Introducing the smallest, lightest, and quietest LCD laser projector in its class with up to 20,000 lm\* , compact 23 kg\*2 (50.7 lbs) body, and quiet 42 dB\*3 operation.

### Key Features

---

World's Smallest, Lightest, and Quietest 20,000 lm LCD Projector

---

Long-Life Energy-Saving Design Minimizes Problems

---

Delivering up to 20,000 lm on AC 100-240 V, a World First



## PT-MZ20KL

<https://latam.connect.panasonic.com/br/en/products/projectors/pt-mz20kl>

|   |   |
|---|---|
| <b>Projector type</b>   | LCD projector   |
| <b>LCD Panel   Panel Size</b>   | 25.4 mm (1.0 in) diagonal (16:10 aspect ratio)  |
| <b>LCD Panel   Display System</b>   | Transparent LCD panel (x 3, R/G/B)  |
| <b>LCD Panel   Drive Method</b>   | Active matrix method  |
| <b>LCD Panel   Pixels</b>   | 2,304,000 (1920 x 1200 pixels)  |
| <b>Light Source</b>   | Laser diode   |
| <b>Light Output*1 *2</b>  | 20,000 lm   |
| <b>Time until light output declines to 50 %*3</b>                             | 20,000 hours (NORMAL/QUIET)   |
| <b>Resolution</b>   | WUXGA (1920 x 1200 pixels)  |
| <b>Contrast Ratio*1</b>   | 3,000,000:1 (Full On/Full Off) (When [PICTURE MODE] is set to [DYNAMIC] and [DYNAMIC CONTRAST] set to [3].)   |
| <b>Screen Size (Diagonal)</b>   | 2.03–15.24 m (80–600 in), 2.54–10.16 m (100–400 in) with ET-EMU100, 16:10 aspect ratio  |
| <b>Center-to-corner zone ratio*1</b>  | 85 %  |
| <b>Lens</b>   | Optional (no lens included with this model)   |
| <b>Lens shift   Vertical (from center of screen)</b>                          | ±60 % (+50 %, -20 % with ET-EMU100, ±40 % with ET-EMW200, ±50 % with ET-EMW300) (powered)   |
| <b>Lens shift   Horizontal (from center of screen)</b>                        | ±20 % (±19 % with ET-EMW200) (powered)  |
| <b>Keystone Correction Range</b>  | Vertical: ±45 ° (±5 ° with ET-EMU100, ±14 ° with ET-EMW200/ET-EMW300, ±22 ° with ET-EMW400/ET-EMW500), Horizontal: ±40 ° (±0 ° with ET-EMU100, ±8 ° with ET-EMW200/ET-EMW300, ±15 ° with ET-EMW400/ET-EMW500). When [VERTICAL KEYSTONE] and [HORIZONTAL KEYSTONE] are used simultaneously, correction cannot be made exceeding a total of 55 °. |
| <b>Terminals   SDI In</b>   | BNC x 1: 3G/HD-SDI input  |
| <b>Terminals   HDMI In</b>  | HDMI 19-pin x 2 (Compatible with HDCP 2.3, Deep Color, 4K/60p signal input5), CEC supported   |
| <b>Terminals   Serial/Multi Projector Sync In</b>                             | D-sub 9-pin (female) x 1 for external control (RS-232C compliant)   |
| <b>Terminals   Serial/Multi Projector Sync Out</b>                            | D-sub 9-pin (male) x 1 for link control (RS-232C compliant)   |
| <b>Terminals   REMOTE 1</b>   | D-sub 9-pin (female) x 1 for external control (parallel)  |
| <b>Terminals   Remote 2 In</b>  | M3 x 1 for wired remote control   |
| <b>Terminals   Remote 2 Out</b>   | M3 x 1 for link control (for wired remote control)  |
| <b>Terminals   DIGITAL LINK</b>   | RJ-45 x 1 for network and DIGITAL LINK connection (video/network/serial control) (HDBase™ compliant), 100Base-TX (Compatible with PLink™ [Class 2], Art-Net, HDCP 2.3, Deep Color, 4K/60p signal input*5 )  |
| <b>Terminals   LAN</b>  | RJ-45 x 1 for network connection, 10Base-T, 100Base-TX (Compatible with PLink™ [Class 2], Art-Net)  |
| <b>Terminals   DC Out</b>   | USB connector (Type A) x 1 for power supply (Output: 5 V / 2 A)   |
| <b>Terminals   USB</b>  | USB connector (Type A) x 1 for optional AJ-WM50 Series Wireless Module, for USB memory  |
| <b>Power Supply</b>   | AC 100–240 V, 50/60 Hz  |
| <b>Power consumption*6   Maximum power consumption</b>                        | 1100 W (11.2–4.6 A) (1120 VA)   |
| <b>Power consumption*6   On-mode power consumption (Light power) [Normal]</b> | 1050 W (AC 100–120 V),<br>1000 W (AC 200–240 V)   |
| <b>Power consumption*6   On-mode power consumption (Light power) [Quiet]</b>  | 630 W (AC 100–120 V),<br>610 W (AC 200–240 V)   |
| <b>Filter</b>   | Included (Estimated maintenance time: approx. 20,000 hours *7)  |
| <b>Operation noise*1</b>  | 42 dB (NORMAL), 36 dB (QUIET)   |
| <b>Dimensions (W x H x D)</b>   | Approx. 650 x 185 x 440 mm (25 19/32" x 7 9/32" x 17 5/16" ) (excluding feet and protrusions),<br>650 x 211 x 440 mm (25 19/32" x 8 5/16" x 17 5/16" ) (excluding protrusions, feet at shortest position)   |
| <b>Weight*8</b>   | Approx. 23.0 kg (50.7 lbs)  |
| <b>Operating Environment</b>  | Operating temperature: 0–45 °C (32–113 °F)*9, operating humidity: 10–80 % (no condensation)   |
| <b>Applicable Software</b>  | Logo Transfer Software, Multi Monitoring & Control Software, Early Warning Software, Geometry Manager Pro, Projector Network Setup Software, Smart Projector Control for iOS/Android™   |

---

**Note**

\*1 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped. \*2 When [OPERATING MODE] is set to [NORMAL]. This is the value when the Zoom Lens (Model No.: ET-EMS650) is used. The value varies depending on the lens. \*3 Around this time, light output will have decreased by approximately 50%. IEC62087: 2008 Broadcast contents, NORMAL Mode, [DYNAMIC CONTRAST] set to [3], under conditions with 30 °C (86 °F), 700 m (2,297 ft) above sea level, and 0.15 mg/m<sup>3</sup> of particulate matter. Estimated time until light output decreases to 50% will vary depending on environment. \*4 ET-EMT800 is compatible with PT-MZ17KL/MZ14KL/MZ11KL only. It cannot be used with PT-MZ20KL. \*5 4K signals are converted to the projector's resolution (1920 x 1200 pixels) upon projection. 4K/60p and 4K/50p signals input via DIGITAL LINK are supported in YPBPR 4:2:0 format only. \*6 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. On-mode power consumption measured at 25 °C (77 °F) operating temperature at an altitude of 700 m (2,297 ft). \*7 Under conditions of 0.15 mg/m<sup>3</sup> of particulate matter. Estimated maintenance time varies depending on environment. Filter can be washed and reused up to two times. \*8 Average value. May differ depending on the actual unit. \*9 Note that the projector cannot be used at altitudes 2,700 m (8,858 ft) or higher above sea level. In the following operating environments, light output may be reduced to protect the projector: when the projector is used at altitudes below 1,400 m (4,593 ft) and ambient temperature is 35 °C (95 °F) or higher; when the projector is used at altitudes between 1,400 m (4,593 ft) and 2,700 m (8,858 ft) exclusive and ambient temperature is 30 °C (86 °F) or higher. The operating environment temperature should be between 0 °C (32 °F) and 40 °C (104 °F) when the optional AJ-WM50 Series Wireless Module is attached.