



Compact Remote Camera Controller

AW-RP60GJ

Equipped with a GUI menu screen for clear visibility and a joystick for intuitive control. Compact Remote Camera Controller with PoE* support for single cable connection.

Key Features

Equipped with a 3.5-type LCD screen

Flexible customization features

New Joystick with enhanced operability

PoE*1 support/Advanced camera adjustment

*1: PoE is the abbreviation for Power over Ethernet



AW-RP60GJ

<https://latam.connect.panasonic.com/br/en/products/broadcast-proav/aw-rp60gj>

| | |
|--------------------------------------|---|
| Power Requirements | 12 V DC (10.8 V to 13.2 V) |
| PoE* | IEEE802.3af standard: 42 V to 57 V DC (Camera Input) |
| Current Consumption | 0.9 A (XLR connector input), 0.3 A (PoE power supply) |
| Mass | 1.5 kg (3.31 lbs) |
| Dimensions (W x H x D) (mm) | W 210 mm x H 92 mm x D 177 mm (excluding protrusions) |
| Dimensions (W x H x D) (inch) | 8-9/32 inches x 3-5/8 inches x 6-31/32 inches (excluding protrusions) |
| Display | 3.5-type liquid crystal (QHD 960 x 540) |
| Connection Specifications | No. of Connectable Cameras : |
| | 200 (IP), 5 (RS422) |
| | *Up to 100 for cameras other than the AW-UE150 |
| | Remote Camera Selection : |
| | 5 (6 to 200 controlled from the LCD) |
| | No. of Camera Groups : |
| | 40 (5 units/group) |
| | No. of Memory Presets : |
| | 100 |
| Note | *PoE is the abbreviation for Power over Ethernet. |