Panasonic CONNECT



Master Setup Unit (MSU)

AK-MSU1000

Master Setup Unit (MSU) - Maximum of 20 CCU can be connected and controlled from an AK-MSU100 Plus Versatile Assist Functions Transmission Camera System to Be Configured at Low Cost

Key Features

- Large scale 7-type color LCD Touch Panel
- Master control of precise camera settings for the entire camera system
- Serial & IP control (6x serial and up to 99 cameras by IP)
- Camera/CCU Information Output (1080i)
- HD SDI Input (Monitoring, 1080i)

Panasonic CONNECT

AK-MSU1000

https://latam.connect.panasonic.com/br/en/ak-msu1000

General -> Power Supply	12 V DC (Power supply from camera: 10 V - 16 V DC) 42 V - 57 V DC (PoE power supply)
General -> Power Consumption	1.6 A (Power supply: 12 V DC) 0.6 A (PoE+ power supply)
General -> Operating Temperature	0 °C to 40 °C (32 °F to 104 °F)
General -> Operating Humidity	90% or less
General -> Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
General -> Weight	Approx. 4.0 kg (8.82 lb)
General -> Dimensions	W 482 mm x H 222 mm x D 81.5 mm (18-31/32 inches x 8-3/4 inches x 3-7/32 inches) (Including mounting brackets and dial heights)
Adjustment Functions	Scene file, ND filter, CC filter, Color temperature (COLOR TEMP), Master gain (MASTER GAIN), Shutter (SHUTTER), Master pedestal (MPED), Iris (IRIS), Camera selection
CCU Control	RS422 or IP
Maximum Cable Length	When CCU is connected: 50 m (164 ft)