



## 4K Memory Card Camera Recorder

# AG-CX350

Industrial Lightest Weight 4.2 lbs\*1. and Highest Sensitivity of F12/F13\*2 in the Fixed-Lens Camcorders, and Direct Connection Capability to Live Streaming Service/NDI®\*3 HX(pre-installed)\*4

### Key Features

New 1.0" 15M Sensor brings 2000TV-lines and F12/F13 Sensitivity.

Superb 4K Image with 10bit Codec: ALL-I, 422LongG and New HEVC LongG

Supporting HLG (Hybrid Log Gamma) and SDR Monitoring

Industry's Widest Class Lens with 32x Intelligent Zoom and 5-Axis Hybrid I.S.

HD Live Streaming to Connect Directly to Facebook and YouTube Live





## AG-CX350

<https://latam.connect.panasonic.com/br/es/productos/broadcast-y-proav/ag-cx350>

<b>General -&gt; Power Supply</b>	DC 7.28 V (when the battery is used) DC 12 V (when the AC adaptor is used)
<b>General -&gt; Power Consumption</b>	17 W (when the LCD monitor is used) 11.5 W (1080i / 422ALL-I 100M recording, when the LCD monitor is used, no external device connection)
<b>General -&gt; Operating Temperature</b>	0 °C to 40 °C (32 °F to 104 °F)
<b>General -&gt; Operating Humidity</b>	10 % to 80 % (no condensation)
<b>General -&gt; Weight</b>	Body: approx. 1.9 kg (4.19 lb) (body only, excluding lens hood, battery, and accessories) Shooting: approx. 2.3 kg (5.07 lb) (including lens hood, battery, and microphone holder)
<b>General -&gt; Dimensions</b>	W 180 mm x H 173 mm x D 311 mm (7-1/8 inches x 6-13/16 inches x 12-1/4 inches) (excluding protrusion and eye cup)
<b>Camera Unit -&gt; Image Sensor</b>	1.0-type (effective size) MOS solid state image sensor
<b>Camera Unit -&gt; Number of Pixels</b>	15,030,000 pixel
<b>Camera Unit -&gt; Lens</b>	Optical image stabilizer lens, optical 20x motorized zoom F value: F2.8 to F4.5 Focal length: f=8.8 mm to 176 mm, 35 mm equivalent: 24.5 mm to 490 mm
<b>Camera Unit -&gt; Iris</b>	Auto / Manual
<b>Camera Unit -&gt; Filter Diameter</b>	67 mm
<b>Camera Unit -&gt; Shortest Shooting Distance(M.O.D.)</b>	Approx. 10 cm (W), 1.0 m (T) from the front lens
<b>Camera Unit -&gt; Optical Filter -&gt; ND Filter</b>	Clear, 1/4, 1/16, 1/64
<b>Camera Unit -&gt; Optical Filter -&gt; IR Filter</b>	Incorporates the ON/OFF control function
<b>Camera Unit -&gt; Gain Setting</b>	L/M/H selector switch GAIN/ISO mode = dB -3 dB to 18 dB (adjustable in 1 dB steps) 24 dB, 30 dB, 36 dB switched (when assigning [S. GAIN] to the USER button) GAIN/ISO mode = ISO ISO 400, ISO 500, ISO 640, ISO 800, ISO 1000, ISO 1250, ISO 1600, ISO 2000, ISO 2500, ISO 3200, ISO 4000, ISO 5000, ISO 6400, ISO 8000, ISO 10000, ISO 12800
<b>Camera Unit -&gt; Color Temperature Setting</b>	ATW, ATW LOCK, A ch, B ch, preset 3200 K/preset 5600 K/VAR (2000 K to 15000 K)
<b>Camera Unit -&gt; Shutter Speed -&gt; [59.94] 59.94i/59.94p mode</b>	[59.94] 1/60 sec. (shutter off), 1/100 sec., 1/120 sec., 1/250 sec., 1/500 sec., 1/1000 sec., 1/2000 sec., 1/4000 sec., 1/8000 sec., 1/10000 sec.
<b>Camera Unit -&gt; Shutter Speed -&gt; [50.00] 50i/50p mode</b>	[50.00] 1/50 sec. (shutter off), 1/60 sec., 1/100 sec., 1/120 sec., 1/250 sec., 1/500 sec., 1/1000 Hz) 1/2000 sec., 1/4000 sec., 1/8000 sec., 1/10000 sec.
<b>Camera Unit -&gt; Shutter Speed -&gt; [59.94] 59.94p mode</b>	[59.94] 1/30 sec., 1/50 sec. (shutter off), 1/60 sec., 1/100 sec., 1/120 sec., 1/250 sec., 1/500 sec., 1/1000 sec., 1/2000 sec., 1/4000 sec., 1/8000 sec., 1/10000 sec.
<b>Camera Unit -&gt; Shutter Speed -&gt; [50.00] 50p mode</b>	[50.00] 1/25 sec., 1/50 sec. (shutter off), 1/60 sec., 1/100 sec., 1/120 sec., 1/250 sec., 1/500 Hz) 1/1000 sec., 1/2000 sec., 1/4000 sec., 1/8000 sec., 1/10000 sec.
<b>Camera Unit -&gt; Shutter Speed -&gt; [59.94] 59.94p mode</b>	[59.94] 1/24 sec., 1/48 sec., 1/50 sec. (shutter off), 1/60 sec., 1/100 sec., 1/120 sec., 1/250 sec., 1/500 sec., 1/1000 sec., 1/2000 sec., 1/4000 sec., 1/8000 sec., 1/10000 sec.
<b>Camera Unit -&gt; Shutter Speed (Slow Shutter) -&gt; [59.94 Hz] 59.94i/59.94p mode</b>	1/1 sec., 1/2 sec., 1/4 sec., 1/6 sec., 1/15 sec., 1/30 sec.
<b>Camera Unit -&gt; Shutter Speed (Slow Shutter) -&gt; [50.00 Hz] 50i/50p mode</b>	1/50.0 sec. to 1/7200 sec.
<b>Camera Unit -&gt; Shutter Speed (Slow Shutter) -&gt; [59.94 Hz] 59.94p mode</b>	1/1 sec., 1/2 sec., 1/4 sec., 1/6 sec., 1/15 sec.
<b>Camera Unit -&gt; Shutter Speed (Slow Shutter) -&gt; [50.00 Hz] 50p mode</b>	1/25.0 sec. to 1/7200 sec.
<b>Camera Unit -&gt; Shutter Speed (Slow Shutter) -&gt; [59.94 Hz] 59.94p mode</b>	1/1 sec., 1/2 sec., 1/4 sec., 1/6 sec., 1/12 sec.
<b>Camera Unit -&gt; Shutter Open Angle</b>	3.0 deg to 180.0 deg to 360.0 deg (in 0.5 deg steps)
<b>Camera Unit -&gt; VFR Recording Frame Rate -&gt; [59.94 Hz] 59.94i/59.94p mode</b>	1, 2, 4, 6, 9, 12, 15, 18, 20, 21, 22, 24, 25, 26, 27, 28, 30, 32, 34, 36, 40, 44, 48, 54, 60 (fps)
<b>Camera Unit -&gt; VFR Recording Frame Rate -&gt; [50.00 Hz] 50p mode</b>	1, 2, 4, 6, 9, 12, 15, 18, 20, 21, 22, 23, 24, 25, 26, 27, 28, 30, 32, 34, 37, 42, 45, 48, 50 (fps)
<b>Camera Unit -&gt; Super Slow Recording -&gt; [SYSTEM MODE] = 59.94 Hz</b>	1920 x 1080 (FHD): shooting frame rate 120 fps
<b>Camera Unit -&gt; Super Slow Recording -&gt; [SYSTEM MODE] = 50.00 Hz</b>	1920 x 1080 (FHD): shooting frame rate 100 fps

<b>Camera Unit -&gt; Horizontal Resolution</b>	2000 TV or higher (UHD: center) 1000 TV or higher (FHD: center)
<b>Camera Unit -&gt; i.Zoom</b>	x32 (FHD), x24 (UHD)
<b>Camera Unit -&gt; Digital Zoom</b>	x2/ x5/ x10
<b>Camera Unit -&gt; Lens Hood</b>	Hood with lens cover
<b>Memory Card Recorder -&gt; Recording Media</b>	SDHC memory card, SDXC memory card UHS-I/UHS-II UHS Speed Class 3 supported, Video Speed Class V90 supported microP2 card (A series, B series) *2>Please see the "Available Memory Card" table.
<b>Memory Card Recorder -&gt; Recording Slot</b>	microP2/SDXC UHS-II card slot x 2
<b>Memory Card Recorder -&gt; Recording Pixels</b>	3840 × 2160 (UHD), 1920 × 1080 (FHD), 1280 × 720 (HD) (AVC-Intra50: 1440 × 1080, 960 × 720) 720 × 480 (SD), 720 × 576 (SD)
<b>Memory Card Recorder -&gt; System Frequency</b>	59.94 Hz/50.00 Hz
<b>Memory Card Recorder -&gt; Recording File Format</b>	MOV (AVC), MOV (HEVC), AVCHD, P2 MXF
<b>Memory Card Recorder -&gt; Recording Format</b>	Please see the "Recording Format" table.
<b>Memory Card Recorder -&gt; Recording Time</b>	Please see the "Recording Time" table.
<b>Memory Card Recorder -&gt; 2 Slot Functions</b>	Relay Rec, Simultaneous Rec, Background Rec
<b>Memory Card Recorder -&gt; Special Recording Functions</b>	Pre Rec, Interval Rec, Time Stamp
<b>Digital Video -&gt; Quantization -&gt; P2</b>	4:2:2 10 bit/4:2:0 10 bit (AVC-intra50)/4:2:0 8 bit (AVC-LongG12)
<b>Digital Video -&gt; Quantization -&gt; MOV</b>	4:2:2 10 bit/4:2:0 8 bit/4:2:0 10 bit (HEVC)
<b>Digital Video -&gt; Quantization -&gt; AVCHD</b>	4:2:0 8 bit
<b>Digital Video -&gt; Video Compression Format -&gt; P2: AVC-Intra200</b>	MPEG-4 AVC/H.264 Intra Profile
<b>Digital Video -&gt; Video Compression Format -&gt; P2: AVC-Intra100/AVC-Intra50</b>	MPEG-4 AVC/H.264 Intra Profile
<b>Digital Video -&gt; Video Compression Format -&gt; P2: AVC-Intra422/AVC-LongG50/AVC-LongG25/AVC-LongG12</b>	MPEG-4 AVC/H.264 High Profile
<b>Digital Video -&gt; Video Compression Format -&gt; MOV</b>	H.264/MPEG-4 AVC High Profile, H.265/MPEG-H HEVC Main10 Profile
<b>Digital Audio -&gt; Recording Audio Signal -&gt; P2</b>	48 kHz/24 bit, 4 ch (excluding AVC-LongG12) 48 kHz/16 bit, 4 CH (AVC-Intra100/AVC-Intra50 *3/AVC-LongG12)
<b>Digital Audio -&gt; Recording Audio Signal -&gt; MOV</b>	48 kHz/24 bit, 4 ch, Linear PCM
<b>Digital Audio -&gt; Recording Audio Signal -&gt; AVCHD</b>	48 kHz/16 bit, 2 ch, Dolby Audio™
<b>Digital Audio -&gt; Headroom</b>	12 dB/18 dB/20 dB switchable (menu)
<b>AVC Proxy -&gt; File Format</b>	MOV
<b>AVC Proxy -&gt; Video Compression Format</b>	H264/AVC High Profile
<b>AVC Proxy -&gt; Audio Compression Format</b>	AAC-LC
<b>AVC Proxy -&gt; Recording Time&lt;sup&gt;*2&lt;/sup&gt;</b>	Approx. 13 min. per 1 GB of AVC-G6 2CH MOV
<b>Streaming -&gt; Video Compression Format</b>	H.264/MPEG-4 AVC Main Profile, H.264/MPEG-4 AVC High Profile
<b>Streaming -&gt; Video Resolution</b>	3640 x 2160 (UHD), 1920 x 1080 (FHD), 1280 x 720 (HD), 640 x 360, 360 x 180
<b>Streaming -&gt; Streaming Method</b>	Unicast, Multicast
<b>Streaming -&gt; Frame Rate</b>	System frequency = 59.94 Hz: 24 fps, 30 fps, 60 fps System frequency = 50.00 Hz: 25 fps, 50 fps
<b>Streaming -&gt; Bit Rate</b>	3640 x 2160 (UHD): 75 Mbps, 50 Mbps, 25 Mbps, 12 Mbps, 8 Mbps Other than those above: 24 Mbps, 20 Mbps, 16 Mbps, 14 Mbps, 8 Mbps, 6 Mbps, 4 Mbps, 3 Mbps, 2 Mbps, 1.5 Mbps, 1 Mbps, 0.7 Mbps, 0.5 Mbps
<b>Streaming -&gt; Audio Compression Format</b>	AAC-LC, 48 kHz/16 bit, 2 ch
<b>Streaming -&gt; Network Protocol</b>	RTSP/RTP/RTMP/RTMPS/SRT
<b>Video Output -&gt; SDI OUT</b>	BNC x 1, SDI REC REMOTE supported HD: 0.8 V [p-p], 75 Ω SD: 0.8 V [p-p], 75 Ω, Output format (4:2:2 10 bit): • 1920 x 1080: 59.94p, 50p, 59.94i, 50i, 29.97Psf, 25Psf, 23.98Psf • 1280 x 720: 59.94p, 50p • 720 x 480: 59.94i • 720 x 576: 50i

<b>Video Output -&gt; HDMI</b>	HDMI x 1, Type A, HDMI REC REMOTE supported, VIERA Link not supported  Output format (4:2:2 10 bit): • 3840 x 2160: 59.94p, 50p, 29.97p, 25p, 23.98p • 1920 x 1080: 59.94p, 50p, 59.94i, 50i, 29.97p, 25p, 23.98p • 1280 x 720: 59.94p, 50p • 720 x 480: 59.94p • 720 x 576: 50p
<b>Video Output -&gt; VIDEO OUT</b>	3.5 mm diameter mini jack, composite 1.0 V [p-p], 75 Ω
<b>Audio Input/Output -&gt; Built-in Microphone</b>	Stereo microphone
<b>Audio Input/Output -&gt; AUDIO IN</b>	XLR (3-pin) x 2 (INPUT1, INPUT2)  Input high impedance, LINE/MIC/MIC+48V (switchable SW)  MIC: -40 dBu/-50 dBu/-60 dBu (switchable menu)  LINE: +4 dBu/0 dBu (switchable menu)
<b>Audio Input/Output -&gt; SDI OUT</b>	Linear PCM 4 ch
<b>Audio Input/Output -&gt; HDMI OUT</b>	Linear PCM 2 ch/4 ch (switchable menu)
<b>Audio Input/Output -&gt; Headphone</b>	3.5 mm diameter stereo mini jack x 1
<b>Audio Input/Output -&gt; AV OUT</b>	3.5 mm diameter stereo mini jack x 1, Output level: 600Ω, 316 mV
<b>Audio Input/Output -&gt; Built-in Speaker</b>	20 mm diameter, round x 1
<b>Other Input/Output -&gt; TC IN/OUT</b>	BNC x 1, Used as the input and output terminals (switchable menu)  Input: 1.0 V to 4.0 V [p-p] 10 kΩ  Output: 2.0 V ± 0.5 V [p-p] low impedance
<b>Other Input/Output -&gt; DC IN</b>	DC 12 V EIAJ Type 4
<b>Other Input/Output -&gt; REMOTE</b>	2.5 mm diameter super mini jack
<b>Other Input/Output -&gt; LAN</b>	RJ-45: 1000BASE-T/100BASE-TX/10BASE-T  NDI® HX supported *6
<b>Other Input/Output -&gt; USB 3.0 (DEVICE)</b>	USB 3.1 GEN1 Type-C, USB Mass storage function  No USB bus power function
<b>Other Input/Output -&gt; USB 2.0 (HOST)</b>	Type-A, 4-pin (5 V, 0.5 A) for Wireless Module (option)
<b>Monitor/Viewfinder -&gt; LCD Monitor</b>	3.2 type TFT LCD color monitor (3:2), approx. 1,620,000 dots,  Touch panel video display (16: 9) area: Approx. 1,370,000 dots
<b>Monitor/Viewfinder -&gt; Viewfinder</b>	0.39 type OLED (organic EL display), approx. 2,360,000 dots,  video display (16: 9) area: approx. 1,770,000 dots
<b>Included Accessories</b>	Battery (AG-VBR59), Battery charger (AG-BRD50), AC adaptor, AC cable, Microphone holder kit, Shoulder strap, Eye cup, Lens hood *7, Grip belt *7 and Operating instructions

#### Footnote Description

Weight and dimensions shown are approximate.

The production of microP2 cards have been discontinued. When recording to SD memory cards in P2 format, please use SDXC memory cards with video speed class V90 or faster. Please use the latest version of the camera recorder software.

24 bit/16 bit switch by menu

These are reference values for continuous recording using the Panasonic products. The recording time may differ depending on the scene or the number of clips.

The analog control remote controller used with previous Panasonic models may not be used with this device.

To use this function, an activation keycode from NewTek is required. Keycodes can be purchased from the website.

Items come already attached to the camera.