



**Primera cámara PTZ 4K 60p/50p\*1 compatible con NDI®\*2 y SRT\*3 del mundo\*4**

## AW-UE100

Admite NDI® de alto ancho de banda para la transmisión de baja latencia de video 4K 60p / 50p \* 1 de alta calidad, y SRT \* 3 para transmisión estable y de alta calidad, y también es compatible con la salida 12G-SDI para su uso en una amplia gama de situaciones, desde transmisión en vivo de eventos hasta producción de estudio.

### Key Features

Admite una amplia variedad de protocolos de transmisión IP, incluidos NDI®\*2, NDI® | HX\*5 y SRT\*3

Admite disparos 4K 60p / 50p \* 1 y salida 12G-SDI

Objetivo de gran angular con campo de visión de 74,1° y zoom óptico de 24x

Soporta FreeD\*1 para construir sistemas AR/VR\*2

Adopta un nuevo giro/inclinación mecánico para mejorar la capacidad de respuesta y el silencio





## AW-UE100

<https://latam.connect.panasonic.com/br/es/products/broadcast-proav/aw-ue100>

<b>General</b>	
<b>Power Requirements</b>	Main unit: DC 12 V±10% (10.8 V to 13.2 V), AC adaptor: AC 100 V to 240 V
<b>PoE+</b>	Complies with IEEE802.3bt: DC 42 V to 57 V (camera end) (supports software authentication (LLDP communication))
<b>Current Consumption</b>	Main unit: 3.0 A (DC jack input), 1.2 A (PoE+ power supply), AC adaptor (included): 3.0 A
<b>Peso</b>	Approx. 2.2 kg (4.85lbs) (excluding cable cover, direct ceiling mount bracket)
<b>Dimensions</b>	Approx. 2.3 kg (5.07lbs) (excluding direct ceiling mount bracket) 169.2 mm x 170.6 mm x 204.6 mm (6.66 inches x 6.72 inches x 8.06 inches) (excluding protrusions, cable cover, and direct ceiling mount bracket)
<b>Camera Unit</b>	
<b>Image Sensor</b>	1/2.5-type 4K MOS x 1
<b>Lens</b>	Electric powered 24x optical zoom F1.8 to F4.0 (f = 4.12 mm to 98.9 mm, converted to 35 mm: 25.0 mm to 600.0 mm)  i.Zoom (UHD: 28x, FHD: 36x) (*switches from optical 24x i.Zoom digital zoom)
<b>Field of View Range</b>	Horizontal field of view: 74.1° (wide) to 3.3° (tele)  Vertical field of view: 46.0° (wide) to 1.9° (tele)  Diagonal field of view: 81.8° (wide) to 3.8° (tele)
<b>Horizontal Resolution</b>	1,400 TV lines Typ (center area)
<b>Output Formats</b>	[4K formats] 2160/59.94p, 2160/50p, 2160/29.97p (native), 2160/25p (native), 2160/24p (native), 2160/23.98p (native)  [HD formats] 1080/59.94p, 1080/50p, 1080/29.97p (native), 1080/29.97PsF, 1080/25p (native), 1080/25PsF, 1080/23.98p over 59.94i, 1080/24p (native), 1080/23.98p (native), 1080/23.98PsF, 1080/59.94i, 1080/50i, 720/59.94p, 720/50p
<b>Output</b>	
<b>HDMI</b>	HDMI 2.0 connector  4:2:2/10 bit*3*4
<b>12G-SDI OUT</b>	SMPT2082-1, SMPT292 compliant/75 Ω (BNC x 1)*5
<b>3G-SDI OUT</b>	SMPT292/75 Ω (BNC x 1)*5
<b>Input/Output</b>	
<b>LAN</b>	LAN for IP control and video transmission/PoE+ terminal (RJ-45)
<b>RS-422</b>	CONTROL IN RS422A (RJ-45)
<b>MIC/Line Input</b>	Supported (SDI/HDMI/IP), AAC compatible (IP only) O3.5 mm stereo mini jack  For mic input, input level: -40 dBV (0 dB = 1 V/Pa, 1 kHz) plug-in power compatible, supply voltage: 2.5 V ±0.5 V  For line input, input level: -10 dBV  Input volume variable range: -36 dB to 12 dB (3 dB step)  embedded audio output level: -12 dBFS  Sampling frequency: 48 kHz  Quantified bit count: 24bit (SDI, HDMI), 16bit (IP)
<b>Pan Tilt Head Unit</b>	
<b>Panning Range</b>	±175°
<b>Tilting Range</b>	-30° to 210°*6
<b>IP Streaming</b>	
<b>Video Compression Format</b>	JPEG (MJPEG), H.264, H.265, NDI®  HX, High bandwidth NDI®
<b>Resolución</b>	3840 x 2160, 1920 x 1080, 1280 x 720, 640 x 360, 320 x 180
<b>New Functions</b>	
<b>NDI Support</b>	NDI®, NDI®  HX: Included as standard*7*8
<b>Mechanical Pan/Tilt</b>	Direct Drive system
<b>Note</b>	*Product specifications are subject to change without notice for reasons of improvement, etc. *3: HDCP not supported. *4: VIERA Link not supported. *5: Level-A/Level-B supported. *6: The main unit may appear in video, depending on the pan/tilt position. *7: High bandwidth NDI® and high efficiency low bandwidth NDI®  HX cannot be used simultaneously. *8: NDI®: High bandwidth NDI®, NDI®  HX: High efficiency low bandwidth NDI®  HX. *NDI® and NDI®  HX, a technology of NewTek, Inc. NDI® and NDI®  HX are registered trademarks of NewTek, Inc.* The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries.* "YouTube" and the "YouTube logo" are registered trademarks of Google Inc.* "Facebook" is a registered trademark of Facebook, Inc.

