



**4K PTZ Camera for an era of enhanced creativity and the pursuit of visual expression.**

## AW-UE160

The AW-UE160 4K PTZ camera features a newly developed 4K 1" MOS sensor that offers the highest sensitivity of Panasonic's entire PTZ lineup. Production teams shooting in a concert venue or a church can easily capture clear images even in the most challenging lighting conditions. Meanwhile, the UE160's new optical low pass filter reduces the effect of moiré for clearer picture quality when shooting against an LED wall, which is especially important for rental and staging or worship environments. Its high-speed frame rate will help sports broadcasters capture slow motion shots in HD for replays, while seamless integration with the robotic camera system brings live broadcast-style movements to the PTZ, resulting in a dynamic and highly engaging video production.

### Key Features

- Uncompromising shooting performance and operability
- Optical low-pass filter significantly reduces moiré
- Newly developed 4K Sensor offering superior sensitivity
- Significantly improved Autofocus with advanced technology
- SMPTE 2110 Support with purchase of additional software key
- Realize next-generation video production with various shooting methods and functions.
- Ease of use and versatility reduces stress of shooting on-site.





## AW-UE160

<https://latam.connect.panasonic.com/br/es/products/broadcast-proav/aw-ue160>

<b>General -&gt; Power Requirements</b>	12 V DC $\pm$ 10% (10.8 V to 13.2 V)
<b>General -&gt; PoE</b>	PoE++
	IEEE802.3bt standard: DC 42 V to 57 V (Camera Input)
	(Software authentication (LLDP) is supported).
<b>General -&gt; Current Consumption</b>	5.0A (XLR IN connector), 1.5A (PoE++ power supply)
<b>General -&gt; Ambient Operating Temperature</b>	0 °C to 40 °C (32 °F to 104 °F)
<b>General -&gt; Ambient Operating Humidity</b>	20 % to 90 % (no condensation)
<b>General -&gt; Storage Temperature</b>	-20 °C to 50 °C (-4 °F to 122 °F)
<b>General -&gt; Weight</b>	Approx. 4.6 kg (10.14 lbs) (excluding mount bracket)
<b>General -&gt; Dimensions</b>	W 213 mm x H 277 mm x D 240 mm
	(8.39 inches x 10.91 inches x 9.45 inches)
	(excluding protrusions, ceiling mount bracket)
<b>General -&gt; Finish</b>	AW-UE160W: Pearl white
	AW-UE160K: Black
<b>General -&gt; Controller Supported *1</b>	See the "Compatibility Chart for Operation Devices and Application Software" page
<b>Camera Unit -&gt; Imaging Sensor</b>	1-type 4K MOSx1
<b>Camera Unit -&gt; Effective Pixels</b>	Approx. 9,620,000 pixels
<b>Camera Unit -&gt; Zoom</b>	<ul style="list-style-type: none"> <li>Optical zoom: 20x</li> <li>i.Zoom: UHD 24x, FHD 32x</li> <li>D.Extender zoom: 1.4x, 2x</li> </ul>
<b>Camera Unit -&gt; Lens</b>	Motorized Optical 20x zoom, F2.8 to F4.5
	[f=8.8 mm (1 1/32 inches) to 176.0 mm (6-15/16 inches),
	35 mm (1-3/8 inches) equivalent: 24.5 mm (31/32 inches) to 490.0 mm (19-9/32 inches)]
<b>Camera Unit -&gt; Conversion Lens</b>	Not supported
<b>Camera Unit -&gt; Angle of View Range</b>	Horizontal angle of view: 75.1° (wide) to 4.0° (tele)
	Vertical angle of view: 46.7° (wide) to 2.3° (tele)
	Diagonal angle of view: 82.8° (wide) to 4.6° (tele)
<b>Camera Unit -&gt; Optical Filter -&gt; ND Filter</b>	Through, 1/4, 1/16, 1/64 *4, (Through is used as "Night mode")
<b>Camera Unit -&gt; Focus</b>	Switching between auto and manual
<b>Camera Unit -&gt; Focus Distance</b>	Entire zooming range: 1000 mm (3.3 ft)
	Wide end: 100 mm (0.33 ft)
<b>Camera Unit -&gt; Color Separation Optical System</b>	1MOS
<b>Camera Unit -&gt; Standard Sensitivity</b>	F14 / 2,000lx (Low Light), F11 / 2,000lx (Normal) (59.94Hz)
	F15 / 2,000lx (Low Light), F12 / 2,000lx (Normal) (50Hz)
<b>Camera Unit -&gt; Horizontal Resolution &gt; 4K</b>	1,600 TV lines Typ (Center area)
<b>Camera Unit -&gt; Gain Selection *2</b>	Auto, -6 dB to 12 dB *5
<b>Camera Unit -&gt; Frame Mix *3</b>	Auto, 0 dB, 6 dB, 12 dB, 18 dB, 24 dB *6
<b>Camera Unit -&gt; Electronic Shutter Speed -&gt; 60p</b>	1/60, 1/100, 1/120, 1/125, 1/250, 1/500, 1/1000, 1/1500, 1/2000

Camera Unit -> Electronic Shutter Speed -> 59.94p/59.94i	1/60, 1/100, 1/120, 1/125, 1/250, 1/500, 1/1000, 1/1500, 1/2000
Camera Unit -> Electronic Shutter Speed -> 50p/50i	1/60, 1/100, 1/125, 1/250, 1/500, 1/1000, 1/1500, 1/2000
Camera Unit -> Electronic Shutter Speed -> 29.97p	1/48, 1/50, 1/60, 1/96, 1/100, 1/120, 1/125, 1/250, 1/500, 1/1000, 1/1500, 1/2000
Camera Unit -> Electronic Shutter Speed -> 25p	1/48, 1/50, 1/60, 1/96, 1/100, 1/125, 1/250, 1/500, 1/1000, 1/1500, 1/2000
Camera Unit -> Electronic Shutter Speed -> 23.98p/24p	1/48, 1/50, 1/60, 1/96, 1/100, 1/200, 1/125, 1/250, 1/500, 1/1000, 1/1500, 1/2000
Camera Unit -> Electronic Shutter Speed -> 59.94p/120fps	1/125, 1/250, 1/500, 1/1000, 1/1500, 1/2000
Camera Unit -> Electronic Shutter Speed -> 50p/100fps	1/125, 1/250, 1/500, 1/1000, 1/1500, 1/2000
Camera Unit -> Synchro Scan -> 60p	60.00 Hz to 7200 Hz
Camera Unit -> Synchro Scan -> 59.94p/59.94i	60.00 Hz to 7200 Hz
Camera Unit -> Synchro Scan -> 50p/50i	50.00 Hz to 7200 Hz
Camera Unit -> Synchro Scan -> 29.97p	30.00 Hz to 7200 Hz
Camera Unit -> Synchro Scan -> 25p	25.00 Hz to 7200 Hz
Camera Unit -> Synchro Scan -> 23.98p/24p	24.00 Hz to 7200 Hz
Camera Unit -> Synchro Scan -> 59.94p/120fps	120.00 Hz to 7200 Hz
Camera Unit -> Synchro Scan -> 50p/100fps	100.00 Hz to 7200 Hz
Camera Unit -> Gamma	HD / NORMAL / CINEMA1 / CINEMA2 *7
	MASTER GAMMA (0.15 ~ 0.75)
	R GAMMA (-75 ~ +75)
	B GAMMA (-75 ~ +75)
	R BLACK GAMMA (-20 ~ +20)
	B BLACK GAMMA (-20 ~ +20)
Camera Unit -> White Balance	ATW *8: 3200K, 5600K
	AWB : AWB-A / AWB-B
	VAR (selectable between 2000K and 15000K by designating a value)
Camera Unit -> Chroma Amount Variability	OFF, -100 % to 40 %
Camera Unit -> Scene File	Scene1 to 8
Camera Unit -> Color Bar	SMPTE, FULL
	ARIB (FHD): Output of base band type only
	ARIB (UHD): Output of base band type UHD only
	ARIB (2020/HLG): Output of base band type UHD only
	*IP display color bars do not conform with SMPTE
Camera Unit -> Output Format (SDI) -> 4K	2160/60p, 2160/59.94p, 2160/50p, 2160/29.97p (Native), 2160/25p (Native), 2160/24p (Native), 2160/23.98p (Native)
Camera Unit -> Output Format (SDI) -> HD	1080/119.88p *10 *11, 1080/100p *10 *11, 1080/60p, 1080/59.94p, 1080/50p, 1080/29.97p (Native), 1080/25p (Native), 1080/24p (Native), 1080/23.98p (Native), 1080/59.94i, 1080/50i, 720/59.94p, 720/50p
Camera Unit -> Output Format (HDMI) -> 4K	2160/60p, 2160/59.94p, 2160/50p, 2160/29.97p (Native), 2160/25p (Native), 2160/24p (Native), 2160/23.98p (Native)
Camera Unit -> Output Format (HDMI) -> HD	1080/119.88p, 1080/100p, 1080/60p, 1080/59.94p, 1080/50p, 1080/29.97p (Native), 1080/25p (Native), 1080/24p (Native), 1080/23.98p (Native), 1080/59.94i, 1080/50i, 720/59.94p, 720/50p
Camera Unit -> Output Format (Fiber (video only)) -> 4K	2160/59.94p, 2160/50p, 2160/29.97p (Native), 2160/25p (Native), 2160/24p (Native), 2160/23.98p (Native)
Camera Unit -> Output Format (Fiber (video only)) -> HD	1080/60p, 1080/59.94p, 1080/50p, 1080/29.97p (Native), 1080/25p (Native), 1080/24p (Native), 1080/23.98p (Native), 1080/59.94i, 1080/50i, 720/59.94p, 720/50p
Camera Unit -> Output Format (ST 2110) *12	1080/60p, 1080/59.94p, 1080/50p, 1080/29.97p (Native), 1080/25p (Native), 1080/24p (Native), 1080/23.98p (Native), 720/59.94p, 720/50p
Synchronization System	Internal/External synchronization (BBS/Tri-level sync)
Input Connector -> DC IN	DC 12 V IN
Input Connector -> G/L IN	BBS (Black Burst Sync), tri-level sync supported

---

**Input Connector -> AUDIO INPUT -> XLR** XLR (2ch) or MIC/LINE Input compatibles (SDI/HDMI/IP)

AAC compatibility (compatible with IP only)

XLR 3-pin female balanced input: 2ch

• During MIC input

Input level: -50 dBu or -60 dBu/-40 dBu (0 dB=1 V/Pa, 1 kHz)

Phantom power compatible, Supply voltage: 47 V±2 V

Input impedance: Approx. 10kΩ

• During LINE input

Input level: 0 dBu (or +4 dBu/-20 dBu)

Input impedance: Approx. 10kΩ

• Input volume variable range: -40 dB to 0 dB to +20 dB (1 dB step)

• Embedded audio output level: -12 dBFS/-18 dBFS/-20 dBFS

• Sampling frequency: 48 kHz

• Quantization bit rate: 24 bit (SDI/HDMI), 16bit (IP)

---

**Output Connector -> HDMI** HDMI 2.0 standard

4:2:2/10bit \*13 \*14

---

**Output Connector -> 12G-SDI OUT** SMPTE2082\_1, SMPTE424M/SMPTE292M/ 75 Ω (BNC x 1) \*15

---

**Output Connector -> 3G-SDI OUT1** SMPTE424M/SMPTE292M/ 75 Ω (BNC x 1) \*15

---

**Output Connector -> 3G-SDI OUT2/PM** SMPTE424M/SMPTE292M/ 75 Ω (BNC x 1) \*15

---

**Output Connector -> SFP+** SFP+ compliant (Single Fiber) \*16, MSA standard compliant product

---

**Output Connector -> USB** USB3.0 HOST 5G mobile router (with USB tethering support \*17

---

**Input/Output Connector -> LAN** LAN connector for IP control (RJ-45) 100BASE-TX/1000BASE-T

---

**Input/Output Connector -> RS-422** CONTROL IN RS-422A (RJ-45)

---

**Input/Output Connector -> SFP+ (ST 2110 )** \*12  
Compatible protocol:

• ST 2120-10/-20/-21/-22/-30

• PTP ST 2059-1/2

• NMOS IS-04/IS-05

Number of outputs:

[Uncompressed] Video x3 (Main line, Crop, Monitor), Audio x2

[JPEG XS] Video x1 (Main line, Crop), Audio x2

Number of inputs: Video x1 (RETURN)

Video format: FHD, UHD \*18

---

Please refer to the operating instruction manual.

---

<b>Pan-tilt Head Unit -&gt; IP connecting cable</b>	<ul style="list-style-type: none"> <li>• With PoE++ ethernet hub</li> </ul> <p>LAN cable <sup>*19</sup>(category 5e or above, straight cable) up to 100 m</p> <ul style="list-style-type: none"> <li>• Without PoE++ ethernet hub</li> </ul> <p>LAN cable <sup>*19</sup>(category 5e or above, straight cable) up to 100 m <sup>*20</sup></p>
<b>Pan-tilt Head Unit -&gt; AW protocol connecting cable</b>	LAN cable <sup>*19</sup> (category 5e or above, straight cable) up to 1000 m
<b>Pan-tilt Head Unit -&gt; Installation Method</b>	Stand-alone (Desktop) or suspended (Hanging) <sup>*21</sup>
<b>Pan-tilt Head Unit -&gt; Pan/tilt Operation Speed</b>	0.08 °/s to 180°/s (Normal mode) <sup>*22</sup>
	Maximum speed:
	Normal mode: 60°/s, Fast1 mode: 90°/s, Fast2 mode: 180°/s
<b>Pan-tilt Head Unit -&gt; Panning Range</b>	±175°
<b>Pan-tilt Head Unit -&gt; Tilting range</b>	-30° to 210° <sup>*22</sup>
<b>Pan-tilt Head Unit -&gt; Quietness</b>	NC35 or less <sup>*23</sup>
<b>Supported Operating Systems and Web Browsers -&gt; Windows <sup>*11</sup></b>	Windows@10
	Microsoft Edge
	Google Chrome
<b>Supported Operating Systems and Web Browsers -&gt; Mac <sup>*11</sup></b>	macOS 10.13 / Safari 13
	macOS 10.14 / Safari 13
	macOS 10.15 / Safari 13
	macOS 10.15 / Google Chrome
<b>Supported Operating Systems and Web Browsers -&gt; iPhone/iPad <sup>*11</sup></b>	iOS
	Safari
	iPadOS
<b>Supported Operating Systems and Web Browsers -&gt; Android <sup>*9</sup></b>	Android OS
	Google Chrome
<b>IP Streaming -&gt; Image Streaming Mode</b>	JPEG (MJPEG), H.264, H.265, NDI® High Bandwidth, NDI® HX <sup>*24 *25</sup>
<b>IP Streaming -&gt; Image Resolution</b>	3840x2160, 1920x1080, 1280x720, 640x360
<b>IP Streaming -&gt; Image Transmission Setting (JPEG)</b>	Frame Rate: Maximum 30 fps <sup>*26 *27</sup>
	Image quality (Fine / Normal)
<b>IP Streaming -&gt; Image Transmission Setting (H.264) -&gt; Transmission Type</b>	Unicast port (AUTO)
	Unicast port (MANUAL)
	Multicast port
<b>IP Streaming -&gt; Image Transmission Setting (H.264) -&gt; Transmission mode</b>	CBR, VBR
<b>IP Streaming -&gt; Image Transmission Setting (H.264) -&gt; Frame Rate</b>	[60Hz] 5fps / 15fps / 30fps / 60fps (UHD: 30fps, 60fps)
	[50Hz] 5fps / 12.5fps / 25fps / 50fps (UHD: 25fps, 50fps)
<b>IP Streaming -&gt; Image Transmission Setting (H.264) -&gt; Max Bit Rate</b>	2048kbps / 4096kbps / 8192kbps / 10240kbps / 12288kbps / 14336kbps / 20480kbps / 24576kbps / 51200kbps / 76800kbps
<b>IP Streaming -&gt; Image Transmission Setting (H.265) -&gt; Transmission Type</b>	Unicast port (AUTO)
	Unicast port (MANUAL)
	Multicast port
<b>IP Streaming -&gt; Image Transmission Setting (H.265) -&gt; Transmission mode</b>	CBR, VBR
<b>IP Streaming -&gt; Image Transmission Setting (H.265) -&gt; Frame Rate</b>	[60Hz] 30fps / 60fps
	[50Hz] 25fps / 50fps

<b>IP Streaming -&gt; Image Transmission Setting (H.265) -&gt; Max Bit Rate</b>	2048kbps / 4096kbps / 8192kbps / 10240kbps / 12288kbps / 14336kbps / 20480kbps / 24576kbps / 51200kbps / 76800kbps
<b>IP Streaming -&gt; Audio Compression Format</b>	AAC-LC, 48 kHz / 16 bit / 2ch
<b>IP Streaming -&gt; Supported Protocol -&gt; Network Protocol</b>	ICMP, ARP, GARP, MLD
<b>IP Streaming -&gt; Supported Protocol -&gt; Transmission Protocol</b>	TCP/IP, UDP/IP
<b>IP Streaming -&gt; Supported Protocol -&gt; IPv6</b>	IPv4: HTTP, HTTPS, DNS, NTP, DHCPv6, MDNS, SNMP, 802.1X
<b>IP Streaming -&gt; Supported Protocol -&gt; IPv4</b>	IPv6: HTTP, HTTPS, DNS, NTP, DHCPv4, MDNS, SNMP, 802.1X
<b>IP Streaming -&gt; Supported Protocol -&gt; Video Streaming Protocol</b>	RTP / RTCP over RTSP, RTMP, RTMPS, SRT, MPEG2-TS over UDP, NDI® high bandwidth, NDI® HX
<b>IP Streaming -&gt; Supported Protocol -&gt; External Device Cooperation Protocol</b>	FreeD, TSL5.0, SNMP
<b>NDI® Support -&gt; NDI® Support</b>	NDI®(High Bandwidth NDI®, NDI®  HX Ver.2) *24 *25
<b>NDI® Support -&gt; Output Format (NDI® High bandwidth) -&gt; 4K</b>	2160/59.94p, 2160/50p, 2160/29.97p, 2160/25p, 2160/24p, 2160/23.98p
<b>NDI® Support -&gt; Output Format (NDI® High bandwidth) -&gt; HD</b>	1080/60p, 1080/59.94p, 1080/50p, 1080/29.97p, 1080/25p, 1080/24p, 1080/23.98p, 720/59.94p, 720/50p
<b>NDI® Support -&gt; Image Resolution (NDI® HX)</b>	1920x1080, 1280x720 *29
<b>NDI® Support -&gt; Image Streaming Setting (NDI® High bandwidth) -&gt; Transmission Type</b>	Transmission Type: TCP/UDP Unicast/Multicast
<b>NDI® Support -&gt; Image Streaming Setting (NDI® High bandwidth) -&gt; Max Bit Rate</b>	Max 250 Mbps
<b>NDI® Support -&gt; Image Streaming Setting (NDI® HX) -&gt; Transmission Type</b>	TCP/UDP Unicast/Multicast
<b>NDI® Support -&gt; Image Streaming Setting (NDI® HX) -&gt; Flame rate</b>	[60Hz] 5fps / 15fps / 30fps / 60fps [50Hz] 5fps / 12.5fps / 25fps / 50fps
<b>NDI® Support -&gt; Image Streaming Setting (NDI® HX) -&gt; Max Bit Rate</b>	512kbps / 768kbps / 1024kbps / 1536kbps / 2048kbps / 3072kbps / 4096kbps / 6144kbps / 8192kbps / 10240kbps / 12288kbps / 14336kbps / 16384kbps / 20480kbps / 24576kbps
<b>NDI® Support -&gt; Audio Compression Type (NDI® High bandwidth)</b>	AAC, 48 kHz, 2 ch
<b>NDI® Support -&gt; Audio Compression Type (NDI® HX)</b>	AAC-LC, 48 kHz, 16 bit, 2 ch
<b>Other Function -&gt; VR Support (IP/RS422)</b>	Supported
<b>ST 2110 -&gt; Supported Format</b>	ST 2110: 10/20/21/30 PTP: ST2059-2 NMOS: IS-04/IS-05
<b>ST 2110 -&gt; Number of Outputs (TX) -&gt; Video</b>	3 channels (Full x 1, MONI x 1, Crop x 1)
<b>ST 2110 -&gt; Number of Outputs (TX) -&gt; Audio</b>	2 channels
<b>ST 2110 -&gt; Number of Outputs (TX) -&gt; Auxiliary data</b>	No output
<b>ST 2110 -&gt; Number of Inputs (RX) -&gt; Video</b>	1 channel (RETURN) *30
<b>ST 2110 -&gt; Number of Inputs (RX) -&gt; Audio</b>	No input
<b>ST 2110 -&gt; Number of Inputs (RX) -&gt; Auxiliary data</b>	No input
<b>ST 2110 -&gt; Output Format -&gt; Video format</b>	Full x1, MONI x1, Crop x1, all the same format 1080/60p, 1080/59.94p, 1080/50p, 1080/59.94i, 1080/50i, 1080/29.97p (Native), 1080/25p (Native), 1080/24p, 1080/23.98p (Native), 720/59.94p, 720/50p
<b>ST 2110 -&gt; Output Format -&gt; Audio specifications (MIC1/2)</b>	PCM / 48kHz / 24bit / 1 ch x2
<b>ST 2110 -&gt; Input Format</b>	1080/60p, 1080/59.94p, 1080/50p, 1080/59.94i, 1080/50i, 1080/29.97p (Native), 1080/25p (Native), 1080/24p, 1080/23.98p (Native), 720/59.94p, 720/50p
<b>Optional Accessories -&gt; Wireless Remote Controller</b>	AW-RM50AG (Size "AA" dry battery x2, obtained separately)

1. Limited in function when PoE used.
2. IP only.
3. Connection with digest authentication is not guaranteed to work in a case where you are using a Panasonic Controller ( AW-RP150, AW-RP60 ). Smooth operation may be diminished when connection with digest authentication. Use host authentication or the HTTPS function.
4. Equipped with Low pass filter.
5. Can be set in 1 dB step increments.
6. If format is set in 2160/29.97p, 2160/23.98p, 2160/24p, 2160/25p, 1080/29.97p, 1080/25p, it cannot be set.
7. HLG is set in other menu.
8. ATW Speed 3-stage variables
9. The color bar on the IP display is not compliant with SMPTE.
10. 1080/119.88p and 1080/100p use two 3G SDI OUT1/2 channels.
11. No output from 12G/SDI.
12. Requires activation with the separately sold Operational Software Key AW-SFU60.
13. HDCP is not supported.
14. Viera Link is not supported.
15. Compatible with Level-A/Level-B.
16. Optical signal input not supported.
17. Limited power supply to USB\_Wifi dongle.
18. Follows the system format.
19. STP (Shielded Twisted Pair) is recommended.
20. Use Category 6 or higher for 4K video transmission.
21. For safety reasons, it must be secured with the included mounting hardware.
22. Depending on the PAN/TILT position, the main unit may be reflected in the video image.
23. NC25 or less when P/T is stationary.
24. NDI® is a new live video production workflow support protocol for IP use developed by NewTek, Inc.
25. NDI® is a registered trademark of NewTek, Inc. in the United States and other countries.
26. No bit rate specified.
27. JPEG and H.264, JPEG and H.265 simultaneous operation depends on bit rate.
28. NDI® has no image resolution specifications.
29. NDI® |HX has no output format specifications.
30. Output from 3G SDI OUT2 (Video is changed in the OSD menu)

