



Control Panel Standard Type

AT-KC10C1

The “Kairos Control” panel is available in two models: 24XPT standard layout (AT-KC10C1) and 12XPT compact layout (AT-KC10C2).* The panels allow functions to be assigned freely. Indicators show the functions assigned to individual buttons. Multi-scene operation is supported with two ME layouts and two faders. Multiple panels can be used simultaneously within a single system.

Key Features

24XPT standard layout. The panels allow functions to be assigned freely.

Multi-scene operation is supported with two ME layouts and two faders.

Indicators show the functions assigned to individual buttons.

Multiple panels can be used simultaneously within a single system.

A transition fader of the panel supports A/B mode in addition to PGM/PST mode.



AT-KC10C1

<https://latam.connect.panasonic.com/br/es/kc10c1>

| | |
|------------------------------------------|------------------------------------------------------------------------------------------|
| General -> Power Requirement | DC 12V, 8.0A |
| General -> Operating Temperature | 0 to 40 °C |
| General -> Operating Humidity | 10% to 90%, no condensation |
| General -> Weight | Approx. 15.4 kg / 33.95 lb (without accessories & options) |
| General -> Dimensions | W 1140 mm x H 94 mm x D 420 mm(44.9 x 3.7 x 16.5 inches)(excluding protrusion) |
| Control Terminals -> LAN (Rear Panel) | RJ-45 x 1, 1GbE |
| Control Terminals -> USB (Control Panel) | USB2.0 typeA x 1 |
| Control Terminals -> USB (Rear Panel) | USB2.0 typeA x 1 |
| Footnote Description | NDI® is a registered trademark of Vizrt NDI AB in the United States and other countries. |