



Cámara PTZ 4K con salida simultánea 3G-SDI, HDMI y USB

AW-UE20

La AW-UE20 cuenta con una carcasa compacta de nuevo diseño que facilita su manejo e instalación en cualquier tipo de entorno, especialmente cuando se instala en truss, techo o montajes en pared para aulas y salas de reuniones.

Key Features

Cámara PTZ 4K

Salida simultánea 3G-SDI, HDMI y USB

Tamaño compacto y gran angular

Transmisión de vídeo de alta calidad para una comunicación online más cómoda

Excelente flexibilidad del sistema para un cableado inteligente y un funcionamiento intuitivo





AW-UE20

<https://latam.connect.panasonic.com/br/es/products/broadcast-proav/aw-ue20>

General	
Power Requirements	DC12 V ± 10 % (10.8 V to 13.2 V) (Supplied AC adapter)
PoE+	IEEE802.3 at compliant
Current Consumption	TBD
Ambient Operating Temperature	0 °C to 40 °C (32°F to 104°F)
Ambient Operating Humidity	20 % to 90 % (no condensation)
Storage Temperature	-20°C to 50°C (-4 °F to 122 °F)
Mass	TBD
Dimensions (H x W x D)	TBD
Finish	AW-UE20W: WhiteAW-UE20K: Black
Controller Supported	AW-RP150GJ, AW-RP60GJ, AW-RM50AG
Camera Unit	
Image Sensor	1/2.8-type MOS×1
Lens	Electric 12 x optical zoom F1.6 ~ F2.8 (f = 3.9 mm ~ 46.8 mm)
Zoom	Optical zoom: 12 x
Angle of View Range	Horizontal angle of view: 71° (wide) to 6° (tele)
	Vertical angle of view: 43° (wide) to 3° (tele)
	Diagonal angle of view: 79° (wide) to 7° (tele)
Minimum Illumination	TBD
S/N	TBD
Horizontal Resolution	TBD
Output Format	
Output Format HDMI 4K	2160/30p, 2160/29.97p, 2160/25p
Output Format HDMI HD	1080/60p, 1080/59.94p, 1080/50p, 1080/60i, 1080/59.94i, 1080/50i, 1080/30p, 1080/29.97p,
	1080/25p, 720/60p, 720/59.94p, 720/50p
Output Format SDI HD	1080/60p, 1080/59.94p, 1080/50p, 1080/60i, 1080/59.94i, 1080/50i, 1080/30p, 1080/29.97p,
	1080/25p, 720/60p, 720/59.94p, 720/50p
Input	DC 12 V IN
Output	
Video Output	HDMI, 3G-SDI OUT
Input/Output	
Input/Output Connector	LAN, RS-422, AUDIO IN, USB, RS-232C IN, RS-232C OUT
Pan Tilt Head Unit	
Installation Method	Stand-alone (Desktop) or suspended (Hanging)*2
Panning Range	±170°
Tilting Range	-30° ~ 90° *3
Quietness	NC40 or less
Supported operating systems and web browsers	*4
Windows	Windows 10 Windows® Internet Explorer® 11 (32 bit / 64 bit) Microsoft Edge Google Chrome
Mac	Mac OS 10.15 Mac OS 10.14 Mac OS 10.13 Mac OS 10.12 Safari Google Chrome
IP Streaming	
Image Streaming Mode	JPEG(MJPEG), H.264, H.265
Image Resolution	3840×2160, 1920×1080, 1280×720, 640×360
Image Transmission Setting	

Note

- *1 The main unit may appear in the video depending on the pan/tilt position.
- *2 To ensure safety, the unit must be secured using the mount bracket supplied.
- *3 The main unit may appear in the video depending on the pan/tilt position.
- *4 Supported OS indicated are for browsers current as of September 2021. See "Service and Support / PASS" for the latest information on browser support.