Panasonic CONNECT



Zero Offset Ultra Short Throw Zoom Lens

ET-DLE020（for 1-Chip DLP™ Laser Projectors）

0.280-0.299:1 throw ratio (WUXGA) Ultra Short Throw Lens for PT-RQ7L, PT-RQ6L, PT-RZ7L, PT-RZ6L

Key Features

- Superior Flexibility for Easy Installation
- Fits Easily in Tight Exhibition Spaces
- High Reliability for Continuous Operation
- On-Axis Rear Projection
- Zero Offset and Flexible Setup for Multi-Screen Projection

Panasonic CONNECT

ET-DLE020 (for 1-Chip DLP™ Laser Projectors)

https://latam.connect.panasonic.com/br/pt/et-dle020for-1-chip-dlptm-laser-projectors

Lens type	Ultra-Short-Throw Zoom Lens
F-number	2
Focal length (f)	4.1–4.4 mm (5/32–11/64")
Screen size	100–400 inches
Throw ratio -> WUXGA	0.280–0.299:1
Throw ratio -> WXGA	0.294–0.314:1
Throw ratio -> XGA	0.290–0.309:1
Lens-shift -> Vertical *1	+50 % – -16 %
Lens-shift -> Horizontal *1	+10 % – -20 %
Zoom	Yes
Dimensions -> (W)	170 mm (6 11/16″)
Dimensions -> (H)	170 mm (6 11/16″)
Dimensions -> (D)	391 mm (15 13/32″)
Weight	Approx. 3.2 kg (7.05 lbs)
Applicable projectors *2	PT-RQ7L / PT-RQ6L / PT-RZ7L / PT-RZ6L / PT-RZ990 / PT-RZ890 / PT-RZ790 / PT-RZ690 / PT-RCQ10 / PT-RCQ80 / PT-RZ120 / PT-RZ970 / PT-RW930 / PT-RX110 / PT-RZ870 / PT-RZ770 / PT-RW730 / PT-RZ660 / PT-RW620
Dimensions(WxHxD)	170 × 170 × 391 mm (6-11/16 × 6-11/16 × 15-13/32")
Throw ratio -> 4K	0.279–0.297:1
Throw Ratio	WUXGA(0.280-0.299:1)
Compatibiliy	PT-RQ7L, PT-RQ6L, PT-RZ7L, PT-RZ6L
Footnote Description	1. Value is for ceiling installations at WUXGA resolution. Lens-shift value will vary by model. Please see the Throw Distance Calculator for more information. For floor installations, up and right shift will be defined as a positive value. Down and left shift will be defined as a negative value. 2. The lens fixed attachment included with the ET-DLE020 cannot be attached to the RQ7 Series. When using the ET-DLE020, the included bracket is not required. Other compatible projector models require the Lens Fixed Attachment bracket.