



## Control Panel Compact Type

### AT-KC10C2

The “Kairos Control” panel is available in two models: 24XPT standard layout (AT-KC10C1) and 12XPT compact layout (AT-KC10C2).\* The panels allow functions to be assigned freely. Indicators show the functions assigned to individual buttons. Multi-scene operation is supported with two ME layouts and two faders. Multiple panels can be used simultaneously within a single system.

#### Key Features

12XPT standard layout. The panels allow functions to be assigned freely.

Multi-scene operation is supported with two ME layouts and two faders.

Indicators show the functions assigned to individual buttons.

Multiple panels can be used simultaneously within a single system.

A transition fader of the panel supports A/B mode in addition to PGM/PST mode.



AT-KC10C2

<https://latam.connect.panasonic.com/br/pt/kc10c2>

|                                       |  |
|---------------------------------------|--|
| General -> Power Requirement          | DC 12V, 4.0A   |
| General -> Operating Temperature      | 0 to 40 °C   |
| General -> Operating Humidity         | 10% to 90%, no condensation  |
| General -> Weight                     | Approx. 8.5 kg / 18.74 lb (without accessories & options)                                |
| General -> Dimensions                 | W 600 mm x H 90 mm x D 420 mm(23.7 x 3.5 x 16.5 inches)(excluding protrusion)            |
| Control Terminals -> LAN (Rear Panel) | RJ-45 x 1, 1GbE  |
| Control Terminals -> USB (Rear Panel) | USB2.0 typeA x 1   |
| Footnote Description                  | NDI® is a registered trademark of Vizrt NDI AB in the United States and other countries. |