



Painel de controle tipo compacto

AT-KC10C2

O painel “Kairos Control” está disponível em dois modelos: layout padrão 24XPT (AT-KC10C1) e layout compacto 12XPT (AT-KC10C2).* Os painéis permitem que funções sejam atribuídas livremente. Os indicadores mostram as funções atribuídas a botões individuais. A operação multicena é suportada com dois layouts ME e dois faders. Vários painéis podem ser usados simultaneamente em um único sistema.

Key Features

Layout padrão 12XPT. Os painéis permitem atribuir funções livremente.

A operação multicena é suportada com dois layouts ME e dois faders.

Os indicadores mostram as funções atribuídas a botões individuais.

Vários painéis podem ser usados simultaneamente em um único sistema.

Um fader de transição do painel suporta o modo A/B além do modo PGM/PST.

AT-KC10C2

<https://latam.connect.panasonic.com/br/pt/products/broadcast-proav/kc10c2>

| | |
|---|--|
| General -> Power Requirement | DC 12V, 4.0A |
| General -> Operating Temperature | 0 to 40 °C |
| General -> Operating Humidity | 10% to 90%, no condensation |
| General -> Weight | Approx. 8.5 kg / 18.74 lb (without accessories & options) |
| General -> Dimensions | W 600 mm x H 90 mm x D 420 mm (23.7 x 3.5 x 16.5 inches) (excluding protrusion) |
| Control Terminals -> LAN (Rear Panel) | RJ-45 x 1, 1GbE |
| Control Terminals -> USB (Rear Panel) | USB2.0 typeA x 1 |
| Footnote Description | NDI® is a registered trademark of Vizrt NDI AB in the United States and other countries. |