Panasonic CONNECT



1/5-type rack size remote operation panel which supports PoE and IP control

AK-HRP1015

Remote Operation Panel 1/5-type rack size remote operation panel which supports PoE and IP control *Product Availability may vary depending on country

Key Features

- 1/5-type rack size remote operation panel
- Colour LCD display allows GUI operation, and also supports PoE* and IP control
- Camera serial control and IP control (RJ45 LAN cable) are supported.
- Can be used for remote control of Panasonic studio camera, camera recorders, convertible cameras, and HD integrated cameras.
- Functions for studio camera scene file store and load.
- SD memory card slot for saving user files, scene file and updating firmware versions.
- The robust LAN connector.






AK-HRP1015

https://latam.connect.panasonic.com/br/pt/produtos/broadcast-proav/ak-hrp1015

General -> Power Supply	12 V DC (Power supply from camera: 10 V - 16 V DC) 42 V - 57 V DC (PoE power supply)
General -> Power Consumption	0.44 A (Power supply from camera: 10 V - 16 V DC) 0.11 A (PoE power supply)
General -> Operating Temperature	0 °C to 40 °C (32 °F to 104 °F)
General -> Operating Humidity	90 % or less
General -> Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
General -> Weight	Approx. 1.5 kg (3.3 lb)
General -> Dimensions	W 82 mm x H 355 mm x D 124.4 mm (3-1/4 inches x 14 inches x 4-7/8 inches)
General -> Camera/CCU Control	Control signals (camera, CCU control) Power supply 16 V DC (when CCU connected) *1, 12 V DC (when camera connected) *1
General -> Maximum Cable Length	When camera connected: 20 m (65.7 ft) When CCU connected: 50 m (164 ft)
Input/Output -> CCU connector	10-pin, male x 1
Input/Output -> PREVIEW connector	9-pin, female x 1
Input/Output -> LAN connector	RJ-45 x 1 (equipped with a robust LAN terminal connector)
Footnote Description	1. Can be provided from CCU.