



**World's most compact 50,000 lumen Laser Projector  
with Native 4K Resolution**

## PT-RQ50K

The PT-RQ50K is an all-in-one projector built to create breath-taking experiences with ease and reassurance. It combines Panasonic's finest image quality and long-proven reliability.

### Key Features

Laser 3-chip DLP, 50,000 lumens, Native 4K

Lamp-free laser projection with hermetically sealed optics and filter-less design, for 20,000 hours maintenance free operation

Compact body allows for simplified transport, install and adjustment

Dualised design provides the ultimate in backup and reliability

20,000:1 contrast ratio...





## PT-RQ50K

<https://latam.connect.panasonic.com/br/pt/produtos/projetores/pt-rq50k>

<b>Projector type</b>	3-Chip DLP™ projector
<b>Display method</b>	DLP™ chip x 3, DLP™ projection system
<b>Display Device -&gt; Panel size</b>	35.1 mm (1.38 in) diagonal (17:9 aspect ratio)
<b>Display Device -&gt; Number of pixels</b>	8,847,360 (4096 x 2160 pixels) x 3
<b>Light source</b>	Laser diodes (Blue LD, Red LD)
<b>Light output</b>	50,000 lm
<b>Light output (ANSI)</b>	50,000 lm
<b>Light output (Center) *5</b>	51,000 lm (Center)
<b>Time until light output declines to 50 %</b>	20,000 hours [NORMAL]
<b>-&gt; NORMAL</b>	
<b>Time until light output declines to 50 %</b>	24,000 hours [ECO]
<b>-&gt; ECO</b>	
<b>Resolution</b>	Native 4K (4096 x 2160 pixels)
<b>Contrast Ratio (typ.)</b>	20,000:1 (Full On/Full Off, Dynamic Contrast Mode: 3)
<b>Screen size (diagonal)</b>	2.54–38.1 m (100–1,500 in) with new optional lens for PT-RQ50K, 17:9 aspect ratio
<b>Center-to-corner zone ratio</b>	90%
<b>Lens</b>	New optional lenses for PT-RQ50K (no lens included with this model)
<b>Lens shift -&gt; Vertical (from center of screen)</b>	±45 % (±25 % with ET-D3QT600, ±30 % with ET-D3QT700/ET-D3QT800, ±40 % with ET-D3QW300) (powered)
<b>Lens shift -&gt; Horizontal (from center of screen)</b>	±16 % (±8 % with ET-D3QT600, ±10 % with ET-D3QT700/ET-D3QT800, ±14 % with ET-D3QW300) (powered)
<b>Keystone correction range</b>	Vertical: ±40 ° (±28 ° with ET-D3QW300), Horizontal: ±40 ° (±15 ° with ET-D3QW300)
<b>Installation</b>	Horizontal/vertical, free 360-degree installation
<b>Terminals -&gt; MULTI PROJECTOR SYNC IN</b>	BNC x 1
<b>Terminals -&gt; MULTI PROJECTOR SYNC OUT</b>	BNC x 1
<b>Terminals -&gt; SERIAL IN</b>	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
<b>Terminals -&gt; SERIAL OUT</b>	D-sub 9-pin (male) x 1 for link control (RS-232C compliant)
<b>Terminals -&gt; REMOTE 1 IN</b>	M3 stereo mini-jack x 1 for wired remote control
<b>Terminals -&gt; REMOTE 1 OUT</b>	M3 stereo mini-jack x 1 for link control
<b>Terminals -&gt; REMOTE 2 IN</b>	D-sub 9-pin (female) x 1 for external control (parallel)
<b>Terminals -&gt; DIGITAL LINK IN / LAN</b>	RJ-45 x 1 for network and DIGITAL LINK connections (HDBase™ compliant), PJLink™ (Class 2) compatible, 100Base-TX, Art-Net compatible, HDCP 2.2 compatible, Deep Color compatible
<b>Terminals -&gt; LAN</b>	RJ-45 x 1 for network connection, PJLink™ (Class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible
<b>Terminals -&gt; DC OUT</b>	USB Connector (Type A) x 2 for power supply only (DC 5 V, total of 2 A)
<b>Terminals -&gt; USB TYPE A</b>	USB connector (Type A) x 1 for optional Wireless Module (AJ-WM50 Series) / USB Memory Stick
<b>Terminals -&gt; SLOT</b>	SLOT1 : Interface Board for 12G-SDI (ET-MDN12G10) supplied SLOT2 : Optional interface boards, SLOT NX compatible
<b>Power supply</b>	AC 200–240 V, 50/60 Hz; AC 100–120 V, 50/60 Hz
<b>Maximum power consumption</b>	4,100 W (AC 100–120 V: 1,100 W)
<b>On-mode power consumption (Operating mode) -&gt; Normal</b>	3,970 W
<b>On-mode power consumption (Operating mode) -&gt; Eco</b>	3,110 W
<b>Standby power consumption -&gt; Normal</b>	6 W
<b>Cabinet materials</b>	Fabricated metal and molded plastic
<b>Filter</b>	No
<b>Operation noise -&gt; Normal</b>	52 dB [NORMAL]
<b>Dimensions (W x H x D)</b>	720 x 445 x 1,070 mm (28 11/32" x 17 17/32" x 42 1/8") (excluding handle, adjuster feet, and other protruding parts)
<b>Dimensions (W x H x D) -&gt; Width (not including protruding parts)</b>	720 mm (28 11/32")
<b>Dimensions -&gt; Height (not including protruding parts)</b>	445 mm (17 17/32")
<b>Dimensions -&gt; Depth (not including protruding parts)</b>	1,070 mm (42 1/8")
<b>Weight</b>	Approx. 126 kg (278 lbs) (without lens)
<b>Operating environment -&gt; Operating temperature</b>	0–45 °C (32–113 °F)
<b>Operating Environment -&gt; Operating humidity (No condensation)</b>	10–80 % (no condensation)

---

<b>Applicable software</b>	Logo Transfer Software, Multi Monitoring & Control Software, Geometry Manager Pro, Smart Projector Control for iOS/Android™
----------------------------	---

---

**Footnote Description**

1. When [OPERATING MODE] is set to [NORMAL].
2. Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118:2020 international standards. Value is the average of all products when shipped.
3. Measurement, measuring conditions, and method of notation all comply with American National Standards Institute standards. Value is the average of all products when shipped.
4. Average light-output value of all shipped products measured at the center of the screen.
5. Around this time, light output will have decreased by approximately 50 %. IEC62087:2008 Broadcast contents, NORMAL Mode, Dynamic Contrast [3], under conditions with 35 °C (95 °F), 700 m (2,297 ft) above sea level, and 0.15 mg/m<sup>3</sup> of particulate matter. Estimated time until light output declines to 50 % varies depending on environment.
6. Average value. May differ depending on the actual unit.
7. The operating environment temperature should be between 0 °C (32 °F) and 40 °C (104 °F) if the projector is used at an altitude between 1,400 m (4,593 ft) and 4,200 m (13,780 ft).
8. When optional AJ-WM50 wireless module is attached, operating temperature range becomes 0–40 °C (32–104 °F).
9. When using the projector at an altitude lower than 2,700 m (8,858 ft) above sea level, and the operating environment temperature becomes 30 °C (86 °F) or higher, the light output may be reduced to protect the projector. When using the projector at an altitude between 2,700 m (8,858 ft) and 4,200 m (13,780 ft), and the operating environment temperature becomes 25 °C (77 °F) or higher, the light output may be reduced to protect the projector.