



## Compact Remote Camera Controller

# AW-RP60GJ

Equipped with a GUI menu screen for clear visibility and a joystick for intuitive control. Compact Remote Camera Controller with PoE\* support for single cable connection.

### Key Features

---

Equipped with a 3.5-type LCD screen

---

Flexible customization features

---

New Joystick with enhanced operability

---

PoE\*1 support/Advanced camera adjustment

---

\*1: PoE is the abbreviation for Power over Ethernet



## AW-RP60GJ

<https://latam.connect.panasonic.com/co/en/products/broadcast-proav/aw-rp60gj>

<b>Power Requirements</b>	12 V DC (10.8 V to 13.2 V)
<b>PoE*</b>	IEEE802.3af standard: 42 V to 57 V DC (Camera Input)
<b>Current Consumption</b>	0.9 A (XLR connector input), 0.3 A (PoE power supply)
<b>Mass</b>	1.5 kg (3.31 lbs)
<b>Dimensions (W x H x D) (mm)</b>	W 210 mm x H 92 mm x D 177 mm (excluding protrusions)
<b>Dimensions (W x H x D) (inch)</b>	8-9/32 inches x 3-5/8 inches x 6-31/32 inches (excluding protrusions)
<b>Display</b>	3.5-type liquid crystal (QHD 960 x 540)
<b>Connection Specifications</b>	No. of Connectable Cameras :
	200 (IP), 5 (RS422)
	*Up to 100 for cameras other than the AW-UE150
	Remote Camera Selection :
	5 (6 to 200 controlled from the LCD)
	No. of Camera Groups :
	40 (5 units/group)
	No. of Memory Presets :
	100
<b>Note</b>	*PoE is the abbreviation for Power over Ethernet.