Panasonic CONNECT



## LCD Colour Viewfinder

# AK-HVF100

Light weight and high resolution (9-type IPS LCD 1920*1080, 1,100 TV lines) viewfinder with built-in mechanical lift versatile assist functions

**Key Features**

- Focus assist functions
- External HD-SDI Input and 12V 4-pin XLR input
- Four assignable function switches
- Contrast, brightness and peaking are adjustable

Panasonic CONNECT






# AK-HVF100

https://latam.connect.panasonic.com/co/es/ak-hvf100

| | |
|---|---|
| **General -> Power Supply** | DC 12 V (supplied from camera or XLR) |
| **General -> Power Consumption** | 18 W |
| **General -> Operating Temperature** | 0 °C to 45 °C (32 °F to 113 °F) |
| **General -> Operating Humidity** | 10% - 85% (no condensation) |
| **General -> Storage Temperature** | -20 °C to 60 °C (-4 °F to 140 °F) |
| **General -> Weight** | Approx. 2.6 kg (5.73 lbs.) (not including hood) / Approx. 3.0 kg (6.61 lbs.) (including hood) |
| **General -> Dimensions** | W 340 mm x H 234 mm x D 193 mm<br>(13-13/32 inches x 9-7/32 inches x 7-5/8 inches)<br>(not including hood)<br>W 340 mm x H 234 mm x D 231 mm<br>(13-13/32 inches x 9-7/32 inches x 9-1/8 inches)<br>(including hood) |
| **Display Panel -> Dimensions** | 22.9cm (9.0 inches) |
| **Display Panel -> Number of Pixels** | 1920 x 1080 (FHD) |
| **Display Panel -> Display Color** | Approx. 16.77 million colors |
| **Switch Functions and Connectors -> Operation** | <POWER> switch, <MENU> button, <SELECT> dial button, <F1>/<F2>/<F3>/<F4> buttons, <BRIGHT> knob, <CONTRAST> knob, <PEAKING> knob, <INPUT> switch |
| **Switch Functions/Connectors -> Connector** | Camera I/F connector (D-sub 29 pins x 1) SDI IN connector (BNC x 1) DC IN connector (XLR 4 pins x 1) |
| **Supported Signal Format -> CAM** | 1080/59.94i, 1080/50i |
| **Supported Signal Format -> SDI** | 1080/59.94p, 1080/50p, 1080/59.94i, 1080/50i, 720/59.94p, 720/50p |