



## PT-MZ17KL

The World's Smallest, Lightest, and Quietest 20,000\*1 lm Projector \*1  
Light output of PT-MZ20KL. As of November 2022, based on publicly available dimensions, weight, and operation noise values for LCD laser projectors with 20,000 lm brightness and above. Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped.

### Key Features

World's Smallest, Lightest, and Quietest 16,500 lm LCD Projector

Long-Life Energy-Saving Design Minimizes Problems

Delivering up to 20,000 lm on AC 100-240 V, a World First



## PT-MZ17KL

<https://latam.connect.panasonic.com/co/es/products/projectors/pt-mz17kl>

|   |   |
|---|---|
| <b>Projector type</b>   | LCD projector   |
| <b>LCD Panel   Panel Size</b>   | 25.4 mm (1.0 in) diagonal (16:10 aspect ratio)  |
| <b>LCD Panel   Display System</b>   | Transparent LCD panel (x 3, R/G/B)  |
| <b>LCD Panel   Drive Method</b>   | Active matrix method  |
| <b>LCD Panel   Pixels</b>   | 2,304,000 (1920 x 1200 pixels)  |
| <b>Light Source</b>   | Laser diode   |
| <b>Light Output*1 *2</b>  | 16,500 lm   |
| <b>Time until light output declines to 50 %*3</b>                             | 20,000 hours (NORMAL/QUIET)   |
| <b>Resolución</b>   | WUXGA (1920 x 1200 pixels)  |
| <b>Contrast Ratio*1</b>   | 3,000,000:1 (Full On/Full Off) (When [PICTURE MODE] is set to [DYNAMIC] and [DYNAMIC CONTRAST] set to [3].)   |
| <b>Screen Size (Diagonal)</b>   | 2.03–15.24 m (80–600 in), 2.54–10.16 m (100–400 in) with ET-EMU100, 2.03–12.70 m (80–500 in) with ET-EMT8004, 16:10 aspect ratio  |
| <b>Center-to-corner zone ratio*1</b>  | 85 %  |
| <b>Lens</b>   | Optional (no lens included with this model)   |
| <b>Lens shift   Vertical (from center of screen)</b>                          | ±60 % (+50 %, -20 % with ET-EMU100, ±40 % with ET-EMW200, ±50 % with ET-EMW300) (powered)   |
| <b>Lens shift   Horizontal (from center of screen)</b>                        | ±20 % (±19 % with ET-EMW200) (powered)  |
| <b>Keystone Correction Range</b>  | Vertical: ±45 ° (±5 ° with ET-EMU100, ±14 ° with ET-EMW200/ET-EMW300, ±22 ° with ET-EMW400/ET-EMW500), Horizontal: ±40 ° (±0 ° with ET-EMU100, ±8 ° with ET-EMW200/ET-EMW300, ±15 ° with ET-EMW400/ET-EMW500). When [VERTICAL KEYSTONE] and [HORIZONTAL KEYSTONE] are used simultaneously, correction cannot be made exceeding a total of 55 °. |
| <b>Terminals   SDI In</b>   | BNC x 1: 3G/HD-SDI input  |
| <b>Terminals   HDMI In</b>  | HDMI 19-pin x 2 (Compatible with HDCP 2.3, Deep Color, 4K/60p signal input5), CEC supported   |
| <b>Terminals   Serial/Multi Projector Sync In</b>                             | D-sub 9-pin (female) x 1 for external control (RS-232C compliant)   |
| <b>Terminals   Serial/Multi Projector Sync Out</b>                            | D-sub 9-pin (male) x 1 for link control (RS-232C compliant)   |
| <b>Terminals   REMOTE 1</b>   | D-sub 9-pin (female) x 1 for external control (parallel)  |
| <b>Terminals   Remote 2 In</b>  | M3 x 1 for wired remote control   |
| <b>Terminals   Remote 2 Out</b>   | M3 x 1 for link control (for wired remote control)  |
| <b>Terminals   DIGITAL LINK</b>   | RJ-45 x 1 for network and DIGITAL LINK connection (video/network/serial control) (HDBase™ compliant), 100Base-TX (Compatible with PLink™ [Class 2], Art-Net, HDCP 2.3, Deep Color, 4K/60p signal input*5 )  |
| <b>Terminals   LAN</b>  | RJ-45 x 1 for network connection, 10Base-T, 100Base-TX (Compatible with PLink™ [Class 2], Art-Net)  |
| <b>Terminals   DC Out</b>   | USB connector (Type A) x 1 for power supply (Output: 5 V / 2 A)   |
| <b>Terminals   USB</b>  | USB connector (Type A) x 1 for optional AJ-WM50 Series Wireless Module, for USB memory  |
| <b>Power Supply</b>   | AC 100–240 V, 50/60 Hz  |
| <b>Power consumption*6   Maximum power consumption</b>                        | 950 W (9.6–4.0 A) (960 VA)  |
| <b>Power consumption*6   On-mode power consumption (Light power) [Normal]</b> | 880 W (AC 100–120 V), 850 W (AC 200–240 V)  |
| <b>Power consumption*6   On-mode power consumption (Light power) [Quiet]</b>  | 580 W (AC 100–120 V), 560 W (AC 200–240 V)  |
| <b>Filter</b>   | Included (Estimated maintenance time: approx. 20,000 hours *7)  |
| <b>Operation noise*1</b>  | 38 dB (NORMAL), 32 dB (QUIET)   |
| <b>Dimensiones (AnxAlxP)</b>  | Approx. 650 x 185 x 440 mm (25 19/32" x 7 9/32" x 17 5/16" ) (excluding feet and protrusions),<br>650 x 211 x 440 mm (25 19/32" x 8 5/16" x 17 5/16" ) (excluding protrusions, feet at shortest position)   |
| <b>Weight*8</b>   | Approx. 22.5 kg (49.6 lbs)  |
| <b>Operating Environment</b>  | Operating temperature: 0–45 °C (32–113 °F)*9, operating humidity: 10–80 % (no condensation)   |
| <b>Applicable Software</b>  | Logo Transfer Software, Multi Monitoring & Control Software, Early Warning Software, Geometry Manager Pro, Projector Network Setup Software, Smart Projector Control for iOS/Android™   |

---

**Note**

\*1 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped. \*2 When [OPERATING MODE] is set to [NORMAL]. This is the value when the Zoom Lens (Model No.: ET-EMS650) is used. The value varies depending on the lens. \*3 Around this time, light output will have decreased by approximately 50%. IEC62087: 2008 Broadcast contents, NORMAL Mode, [DYNAMIC CONTRAST] set to [3], under conditions with 30 °C (86 °F), 700 m (2,297 ft) above sea level, and 0.15 mg/m<sup>3</sup> of particulate matter. Estimated time until light output decreases to 50% will vary depending on environment. \*4 ET-EMT800 is compatible with PT-MZ17KL/MZ14KL/MZ11KL only. It cannot be used with PT-MZ20KL. \*5 4K signals are converted to the projector's resolution (1920 x 1200 pixels) upon projection. 4K/60p and 4K/50p signals input via DIGITAL LINK are supported in YPBPR 4:2:0 format only. \*6 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. On-mode power consumption measured at 25 °C (77 °F) operating temperature at an altitude of 700 m (2,297 ft). \*7 Under conditions of 0.15 mg/m<sup>3</sup> of particulate matter. Estimated maintenance time varies depending on environment. Filter can be washed and reused up to two times. \*8 Average value. May differ depending on the actual unit. \*9 Note that the projector cannot be used at altitudes 2,700 m (8,858 ft) or higher above sea level. In the following operating environments, light output may be reduced to protect the projector: when the projector is used at altitudes below 1,400 m (4,593 ft) and ambient temperature is 35 °C (95 °F) or higher; when the projector is used at altitudes between 1,400 m (4,593 ft) and 2,700 m (8,858 ft) exclusive and ambient temperature is 30 °C (86 °F) or higher. The operating environment temperature should be between 0 °C (32 °F) and 40 °C (104 °F) when the optional AJ-WM50 Series Wireless Module is attached.