

Controlador de câmera remoto compacto

AW-RP60GJ

Equipado com uma tela de menu GUI para visibilidade clara e um joystick para controle intuitivo. Controlador de câmera remoto compacto com suporte PoE* para conexão de cabo único.

Key Features

Equipado com uma tela LCD tipo 3,5

Recursos de personalização flexíveis

Novo Joystick com operabilidade aprimorada

Suporte PoE*1/Ajuste avançado de câmera

*1: PoE é a abreviatura de Power over Ethernet



AW-RP60GJ

<https://latam.connect.panasonic.com/co/pt/produtos/broadcast-proav/aw-rp60gj>

General -> Power Requirements	12 V DC (10.8 V to 13.2 V)
General -> PoE	PoE
	42 V to 57 V DC
General -> Current Consumption	0.9 A (XLR connector input), 0.3 A (PoE power supply)
General -> Ambient Operating Temperature	0 °C to 40 °C (32 °F to 104 °F)
General -> Ambient Operating Humidity	20 % to 90 % (no condensation)
General -> Storage Temperature	-20 °C to 50 °C (-4 °F to 122 °F)
General -> Weight	1.5 kg (3.31 lbs)
General -> Dimensions	W 210 mm x H 92 mm x D 177 mm
	(8-9/32 inches x 3-5/8 inches x 6-31/32 inches)
	(excluding protrusions)
General -> LCD Display	3.5 inch LCD (QHD: 960 x 540)
Input Connector -> DC IN	DC 12 V IN, XLR 4-pin
Input/Output Connector -> LAN (IP CONT)	10BASE-T/100BASE-TX, PoE input
	Connecting cable: LAN cable, max. 100 m (328 ft)
	• When connecting the unit via a switching hub:
	Straight cable (category 5e), STP (Shielded Twisted Pair) cable recommended
	• When connecting the unit directly:
	Crossover cable (category 5e), STP (Shielded Twisted Pair) cable recommended
	• REMOTE:
	Available only for LAN (RJ45) control
Input/Output Connector -> LAN (SERIAL CONT)	RS-422 (control signals for remote cameras), TALLY OUT
	Connecting cable:
	Straight cable (category 5e), max. 1000 m (3280 ft)
	TALLY OUT:
	Open collector output (negative logic)
	Maximum voltage resistance DC 24 V, Maximum current 50 mA

Input/Output Connector -> TALLY / GPIO 1	D-sub 25-pin, female, inch thread
	TALLY IN: Contact input (Status operation)
	GPIO IN: Contact input (Trigger operation)
	GPIO OUT: Open collector output (negative logic)
	Maximum voltage resistance DC 24 V, Maximum current 10 mA
Connection Specifications -> No. of Connectable Cameras	200 (IP), 5 (RS422)
Connection Specifications -> No. of Camera Selection Buttons	5 (6 to 200 controlled from the LCD)
Connection Specifications -> No. of Camera Groups	40 (5 units/group)
Memory -> Preset Memory	100

