



"New Professional-use PTZ Camera: New Standard for Video Expressiveness and Operational Versatility"

AW-UE150A

Panasonic's new 4K PTZ camera (AW-UE150AW/AK) meets the demands for advanced video production by setting new standard for video expressiveness and operational versatility. Building on its predecessor, the widely used AW-UE150W/K released in 2018, the AW-UE150AW/AK introduces new capabilities for enhanced video quality and flexible operation. In addition to improved pan, tilt, and zoom synchronization, it supports NDI® High Bandwidth for optimal remote-production workflows. * NDI® is a video connectivity technology and is registered as a trademark by Vizrt NDI AB in the United States and other countries.

Key Features

Exceptional Performance for Capturing Immersive Moments

Flexible Adaptation to Diverse Environments

Advanced Features for Expanded Creative Possibilities



AW-UE150A

<https://latam.connect.panasonic.com/mx/en/products/broadcast-proav/aw-ue150a>

General ->	DC12 V(10.8 V to 24.0 V)
Power Requirements	
General -> PoE	IEEE802.3 bt standard : DC42 V to 57 V (Software authentication (LLDP) is supported).
General ->	4.0 A (XLR IN connector), 1.2 A (PoE++ power supply)
Current Consumption	
General ->	0 °C to 40 °C (32 °F to 104 °F)
Ambient Operating Temperature	
General ->	20 % to 90 % (no condensation)
Ambient Operating Humidity	
General ->	-20 °C to 50 °C (-4 °F to 122 °F)
Storage Temperature	
General ->	Approx. 4.3 kg (9.48 lbs) (excluding mount bracket)
Weight	
General ->	213 mm x 267 mm x 219 mm (8-3/8 inches x 10-1/2 inches x 8-5/8 inches)
Dimensions	(excluding protrusions, cable cover,direct ceiling mount bracket)
General -> Finish	AW-UE150AW: Pearl white AW-UE150AK: Black
General ->	AW-RP150GJ, AW-RP60GJ, AK-HRP1010GJ*1, AK-HRP1015GJ*1, AK-HRP1000GJ*1, AK-HRP1005GJ*1, AK-HRP250GJ*1
Controller Supported	
Camera Unit ->	1-type 4K MOSx1
Imaging Sensor	
Camera Unit ->	Approx 20,180,000 pixel
Effective Pixels	
Camera Unit ->	• Optical zoom: 20x
Zoom	• i.Zoom: UHD 24x, FHD 32x
Camera Unit ->	Motorized Optical 20x zoom, F2.8 to F4.5
Lens	[f=8.8 mm (11/32 inches) to 176.0 mm (6-15/16 inches); 35 mm (1-3/8 inches) equivalent: 24.5 mm (31/32 inches) to 490.0 mm (19-9/32 inches)]
Camera Unit ->	Not supported
Conversion Lens	
Camera Unit ->	Horizontal angle of view: 75.1° (wide) to 4.0° (tele)
Angle of View	Vertical angle of view: 46.7° (wide) to 2.3° (tele)
Range	Diagonal angle of view: 82.8° (wide) to 4.6° (tele)
Camera Unit ->	Through, 1/4, 1/16, 1/64, IR through (IR through is used as "Night mode")
Optical Filter ->	
ND Filter	
Camera Unit ->	Switching between auto and manual
Focus	
Camera Unit ->	Entire zooming range: 1000 mm (3.3 ft)
Focus Distance	Wide end: 100 mm (0.33 ft)
Camera Unit ->	1MOS
Color Separation	
Optical System	
Camera Unit ->	F9, 2000 lx
Standard Sensitivity	
Camera Unit ->	2 lx (F2.8, 59.94p, 50IRE, 42 dB, without accumulation)
Minimum Illumination	
Camera Unit ->	2,000 TV lines Typ (Center area)
Horizontal Resolution	
Camera Unit ->	Auto, -3 dB to 36 dB
Gain Selection	• 1 dB step increments can be set. Super Gain function equipped : +37 dB to 42 dB
Camera Unit ->	0 dB, 6 dB, 12 dB, 18 dB, 24 dB
Frame Mix *2	
Camera Unit ->	1/60, 1/100, 1/120, 1/250, 1/500, 1/1000, 1/2000, 1/4000, 1/8000, 1/10000
Electronic Shutter Speed ->	
59.94p/59.94i	
Camera Unit ->	1/60, 1/100, 1/120, 1/250, 1/500, 1/1000, 1/2000, 1/4000, 1/8000, 1/10000
Electronic Shutter Speed ->	
50p/50i	

Camera Unit	-> 1/30, 1/60, 1/100, 1/120, 1/250, 1/500, 1/1000, 1/2000, 1/4000, 1/8000, 1/10000
Electronic Shutter	
Speed	-> 29.97p
Camera Unit	-> 1/25, 1/50, 1/60, 1/100, 1/120, 1/250, 1/500, 1/1000, 1/2000, 1/4000, 1/8000, 1/10000
Electronic Shutter	
Speed	-> 25p
Camera Unit	-> 1/24, 1/48, 1/60, 1/100, 1/120, 1/250, 1/500, 1/1000, 1/2000, 1/4000, 1/8000, 1/10000
Electronic Shutter	
Speed	-> 23.98p/24p
Camera Unit	-> 60.00 Hz to 7200 Hz
Synchro Scan	-> 59.94p/59.94i
Camera Unit	-> 50.00 Hz to 7200 Hz
Synchro Scan	-> 50p/50i
Camera Unit	-> 30.00 Hz to 7200 Hz
Synchro Scan	-> 29.97p
Camera Unit	-> 25.00 Hz to 7200 Hz
Synchro Scan	-> 25p
Camera Unit	-> 24.00 Hz to 7200 Hz
Synchro Scan	-> 23.98p/24p
Camera Unit	-> HD / FILMLIKE1 / FILMLIKE2 / FILMLIKE3/ FILM REC / VIDEO REC
Gamma	
Camera Unit	-> ATW: 3200K, 5600K
White Balance	<ul style="list-style-type: none"> • ATW Speed 3-stage variables AWB : AWB-A / AWB-B VAR (selectable between 2000K and 15000K by designating a value)
Camera Unit	-> OFF, -99 % to 99 %
Chroma Amount	
Variability	
Camera Unit	-> Scene1, Scene2, Scene3, Scene4
Scene File	
Camera Unit	-> 2160/59.94p, 2160/50p, 2160/29.97p(Native), 2160/25p(Native), 2160/24p(Native), 2160/23.98p(Native)
Output	
Format(UHD/FHD SDI)	-> 4K *3
Camera Unit	-> 1080/59.94p, 1080/50p, 1080/29.97p(Native), 1080/25p(Native), 1080/24p(Native), 1080/23.98p(Native), 1080/59.94i,
Output	1080/50i, 720/59.94p, 720/50p
Format(UHD/FHD SDI)	-> HD *3
Camera Unit	-> 2160/59.94p, 2160/50p, 2160/29.97p(Native), 2160/25p(Native), 2160/24p(Native), 2160/23.98p(Native)
Output	
Format(UHD/FHD Fiber)	-> 4K *3
Camera Unit	-> 1080/59.94p, 1080/50p, 1080/29.97p(Native), 1080/25p(Native), 1080/24p(Native), 1080/23.98p(Native), 1080/59.94i,
Output	1080/50i, 720/59.94p, 720/50p
Format(UHD/FHD Fiber)	-> HD *3
Synchronization System	Internal/External synchronization (BBS/Tri-level sync)
Input Connector	- • BBS (Black Burst Sync), tri-level sync supported
	> G/L IN
Input Connector	-MIC/LINE input compatible (SDI/HDMI/IP)
	> MIC/LINE Input AAC compatible (compatible with IP only)
	• ø 3.5 mm stereo mini jack (unbalanced)
	• During MIC input
	Input level: -40 dBV (0 dB=1 V/Pa, 1 kHz)
	Plug-in power compatible,
	supply voltage: 2.5 V ± 0.5 V
	Input impedance:
	Approx. 2 kΩ (When plug-in power is ON)
	Approx. 20 kΩ (When plug-in power is OFF)
	• During LINE input
	Input level: -10 dBV
	Input impedance: Approx. 3 kΩ
	• Input volume variable range:
	-36 dB to 12 dB (3 dB step)
	• Embedded audio output level:
	-12 dBFS
	• Sampling frequency:
	48 kHz
	• Quantization bit rate:
	24bit (SDI, HDMI), 16bit (IP)
Output Connector	HDMI 2.0 connector
HDMI	4:2:2/10bit
	• HDCP is not supported.
	• Viera Link is not supported.
Output Connector	SMPTE 2082-1/SMPTE 2081-1/SMPTE 424M /SMPTE 292M / 75 Ω(BNC×1)
12G-SDI OUT	• Level-A/Level-B supported
Output Connector	SMPTE 424M /SMPTE 292M / 75 Ω(BNC×1)
3G-SDI OUT1	• Level-A/Level-B supported
Output Connector	SMPTE 424M /SMPTE 292M / 75 Ω(BNC×1)
3G-SDI OUT2/PM	• Level-A/Level-B supported

IP Streaming ->	[60Hz] 30fps/60fps
Image	[50Hz] 25fps/50fps
Transmission	
Setting (H.265) ->	
Frame Rate	
IP Streaming ->	512kbps/768kbps/1024kbps/1536kbps/2048kbps/3072kbps/4096kbps/6144kbps/8192kbps/10240kbps/12288kbps/14336kbps
Image	
Transmission	
Setting (H.265) ->	
Max Bit Rate	
IP Streaming ->	AAC-LC, 48 kHz / 16 bit / 2ch
Audio	
Compression	
Format	
IP Streaming ->	TCP / IP, UDP / IP, HTTP, HTTPS, DNS, NTP,
Supported	SNMP, DHCPv6, RTP, MLD, ICMP, ARP, RTMP
Protocol -> IPv6	
IP Streaming ->	TCP / IP, UDP / IP, HTTP, HTTPS, RTSP,
Supported	RTP, RTP / RTCP, DHCP, DNS, DDNS, NTP, SNMP,
Protocol -> IPv4	UPnP, IGMP, ICMP, ARP, RTMP, RTMPS, SRT
NDI® Support ->	NDI® HX2, NDI® High Bandwidth
NDI® Support	
NDI® Support ->	2160/59.94p, 2160/50p, 2160/29.97p, 2160/25p, 2160/24p, 2160/23.98p
Output Format	
(NDI® High bandwidth) -> 4K	
NDI® Support ->	1080/59.94p, 1080/50p, 1080/29.97p, 1080/25p, 1080/24p, 1080/23.98p, 720/59.94p, 720/50p
Output Format	
(NDI® High bandwidth) -> HD	
NDI® Support ->	1920x1080, 1280x720
Image Resolution	
(NDI® HX2)	
NDI® Support ->	TCP/UDP
Image Streaming	Unicast/Multicast
Setting (NDI®)	
High bandwidth)	
-> Transmission	
Type	
NDI® Support ->	Max 250 Mbps
Image Streaming	
Setting (NDI®)	
High bandwidth)	
-> Max Bit Rate	
NDI® Support ->	Unicast port (AUTO)
Image Streaming	Unicast port (MANUAL)
Setting (NDI®)	Multicast port
HX2) ->	
Transmission	
Type	
NDI® Support ->	[60Hz] 5fps / 15fps / 30fps / 60fps (UHD:30fps / 60fps)
Image Streaming	[50Hz] 5fps / 12.5fps / 25fps / 50fps (UHD:25fps / 50fps)
Setting (NDI®)	
HX2) -> Flame	
rate	
NDI® Support ->	512kbps / 768kbps / 1024kbps / 1536kbps / 2048kbps / 3072kbps / 4096kbps / 6144kbps / 8192kbps / 10240kbps / 12288kbps /
Image Streaming	14336kbps / 16384kbps / 20480kbps / 24576kbps
Setting (NDI®)	
HX2) -> Max Bit	
Rate	
NDI® Support ->	AAC, 48 kHz, 2 ch
Audio	
Compression	
Type (NDI® High bandwidth)	
NDI® Support ->	AAC-LC, 48 kHz, 16 bit, 2 ch
Audio	
Compression	
Type (NDI® HX2)	
Other Function ->	red / green / yellow
Tally LED Display	
Color	
Footnote	1. Future support planned
Description	2. This cannot be configured when the format is 2160/29.97p, 2160/23.98p, 2160/24p, 2160/25p, 1080/29.97p, 1080/25p. 3. When selecting formats for UHD SDI, HDMI, and Fiber, it is not possible to select different formats for each of them. Furthermore, the formats for FHD SDI and 3G SDI OUT2 are fixed to the formatting method selected for UHD SDI and HDMI. 4. Use of an STP (shielded twisted pair) cable is recommended. 5. Category 6 or more is used when sending 4K images.

* NDI® is a video connectivity technology and is registered as a trademark by Vizrt NDI AB in the United States and other countries.