

**Panasonic**  
**CONNECT**



**ET-DLE020 ( for 1-Chip DLP™  
Laser Projectors )**

ET-DLE020 ( for 1-  
Chip DLP™ Laser  
Projectors )

<https://latam.connect.panasonic.com/mx/es/et-dle020for-1-chip-dlptm-laser-projectors>

<b>Lens type</b>	Ultra-Short-Throw Zoom Lens
<b>F-number</b>	2.0
<b>Focal length (f)</b>	4.1-4.4 mm (5/32-11/64 inches)
<b>Screen size</b>	100-400 inches
<b>Throw ratio -&gt; WUXGA</b>	0.280-0.299:1
<b>Throw ratio -&gt; WXGA</b>	0.294-0.314:1
<b>Throw ratio -&gt; XGA</b>	0.290-0.309:1
<b>Lens-shift -&gt; Vertical</b>	+50 % - -16 % *1
<b>Lens-shift -&gt; Horizontal</b>	+10 % - -20 % *1
<b>Zoom</b>	Yes
<b>Dimensions -&gt; (W)</b>	170 mm (6 11/16")
<b>Dimensions -&gt; (H)</b>	170 mm (6 11/16")
<b>Dimensions -&gt; (D)</b>	391 mm (15 13/32")
<b>Weight</b>	Approx. 3.2 kg (7.05 lbs)
<b>Applicable projectors</b>	PT-RZ990 /
	PT-RZ890 /
	PT-RZ790 /
	PT-RZ690 /
	PT-RCQ10 /
	PT-RCQ80 /
	PT-RZ120 /
	PT-RZ970 /
	PT-RW930 /
	PT-RX110 /
	PT-RZ870 /
	PT-RZ770 /
	PT-RW730 /
	PT-RZ660 /
	PT-RW620

**Footnote Description**

1. Value is for ceiling installations at WUXGA resolution. Lens-shift value will vary by model. Please see the Throw Distance Calculator for more information. For floor installations, up and right shift will be defined as a positive value. Down and left shift will be defined as a negative value.

2. Please use this product with the included lens-bracket attachment.