



Control Panel Compact Type

AT-KC10C2

The “Kairos Control” panel is available in two models: 24XPT standard layout (AT-KC10C1) and 12XPT compact layout (AT-KC10C2).* The panels allow functions to be assigned freely. Indicators show the functions assigned to individual buttons. Multi-scene operation is supported with two ME layouts and two faders. Multiple panels can be used simultaneously within a single system.

Key Features

12XPT standard layout. The panels allow functions to be assigned freely.

Multi-scene operation is supported with two ME layouts and two faders.

Indicators show the functions assigned to individual buttons.

Multiple panels can be used simultaneously within a single system.

A transition fader of the panel supports A/B mode in addition to PGM/PST mode.



AT-KC10C2

<https://latam.connect.panasonic.com/mx/es/kc10c2>

| | |
|---------------------------------------|--|
| General -> Power Requirement | DC 12V, 4.0A |
| General -> Operating Temperature | 0 to 40 °C |
| General -> Operating Humidity | 10% to 90%, no condensation |
| General -> Weight | Approx. 8.5 kg / 18.74 lb (without accessories & options) |
| General -> Dimensions | W 600 mm x H 90 mm x D 420 mm(23.7 x 3.5 x 16.5 inches)(excluding protrusion) |
| Control Terminals -> LAN (Rear Panel) | RJ-45 x 1, 1GbE |
| Control Terminals -> USB (Rear Panel) | USB2.0 typeA x 1 |
| Footnote Description | NDI® is a registered trademark of Vizrt NDI AB in the United States and other countries. |