



**Step Out of the Shadows with Flexible
WUXGA Short-Throw Laser Projection**

PT-TMZ400

Key Features

Project Anywhere Instantly from Short Distances

Efficient Reliability with Minimal Maintenance

Crisp, Sharp Images and Text at WUXGA



PT-TMZ400

<https://latam.connect.panasonic.com/mx/es/productos/proyectores/pt-tmz400>

Projector type	LCD projectors
Display method	Transparent LCD panel (x 3, R/G/B)
Display Device -> Panel size	16.3 mm (0.64 in) diagonal (16:10 aspect ratio)
Display Device -> Drive method	Active matrix method
Display Device -> Number of pixels	2,304,000 (1920 x 1200) pixels
Light source	Laser diodes
Light output	4,000 lm
Light output (ANSI)	4,000 lm
Time until light output declines to	20,000 hours [NORMAL]
50 % -> NORMAL	
Time until light output declines to	24,000 hours [ECO]
50 % -> ECO	
Time until light output declines to	20,000 hours [QUIET]
50 % -> QUIET	
Resolution	WUXGA (1920 x 1200 pixels)
Contrast Ratio (typ.)	3,000,000:1 (Full On/Full Off)(When [PICTURE MODE] is set to [DYNAMIC] and [DYNAMIC CONTRAST] is set to [1].)
Screen size (diagonal)	1.27-2.67 m (50-105 in), 16:10 aspect ratio
Center-to-corner zone ratio	85%
Lens	Fixed zoom, manual focus lens, F = 1.8, f = 6.08 mm, throw ratio: 0.43:1 (Projection distance: 0.73 m [2.40 ft] for 80-inch image)
Digital Zoom Extender	Throw ratio: 0.43-0.54*5 :1 (Corresponding value)
Keystone correction range	Vertical: ±15 ° (Auto, Manual), Horizontal: ±15 ° (Manual)
Installation	Ceiling/floor, front/rear, free 360-degree installation
Terminals -> HDMI™ IN	HDMI™ 19-pin x 2 (Compatible with HDCP 1.4, Deep Color, 4K/30p*6 signal input), CEC supported*7
Terminals -> COMPUTER IN (D-SUB 15pin)	D-sub 15-pin (female) x 1 (RGB/YPBPR/YCBCR)
Terminals -> AUDIO IN(M3 Stereo Mini Jack)	M3 stereo mini-jack x 2
Terminals -> AUDIO OUT(M3 Stereo Mini Jack)	M3 stereo mini-jack x 1
Terminals -> SERIAL IN	D-sub 9-pin (female) x 1 for computer control (RS-232C compliant)
Terminals -> LAN	RJ-45 x 1 for network control, 10Base-T, 100Base-TX
Terminals -> USB TYPE A	USB connector (Type A) x 1 for Memory Viewer function, optional AJ-WM50 Series Wireless Module, power supply (DC 5 V, maximum 2 A)*8
Protocol versions	IPv4, IPv6*9
Power supply	AC 100 V-240 V, 50/60 Hz
Maximum power consumption	240 W
On-mode power consumption(Operating mode) -> Normal	[NORMAL]215 W (100-240 V), 205 W (200-240 V)
On-mode power consumption(Operating mode) -> Eco	[ECO]165 W (100-240 V), 160 W (200-240 V)
On-mode power consumption(Operating mode) -> Quiet	[QUIET]160 W (100-240 V), 155 W (200-240 V)
Built-in speaker	10 W monaural
Cabinet materials	Molded plastic
Filter	Included
Estimated filter maintenance cycle	Approx. 20,000 hours
Operation noise -> Normal	35 dB [NORMAL]
Operation noise -> Eco	35 dB [ECO]
Operation noise -> Quiet	24 dB [QUIET]
Dimensions (W x H x D)	349 mm x 138 mm x 370 mm (13 3/4" x 5 7/16" x 14 9/16") (with feet at shortest position)
Dimensions -> Width (including protruding parts)	349 mm (13 3/4")
Dimensions -> Height (including protruding parts)	138 mm (5 7/16")
Dimensions -> Depth (including lens)	370 mm (14 9/16")
Weight	4.9 kg (10.8 lbs)
Operating environment -> Operating temperature	0-45 °C (32-113 °F)

Operating Environment ->	20-80 % (no condensation)
Operating humidity (No condensation)	
Applicable software	Multi Monitoring & Control Software, Projector Network Setup Software, Logo Transfer Software, Presenter Light Software for Windows®*14, Wireless Projector App for iOS/Android™*15
Control function via LAN	PJLink™ [Class 2], Crestron Connected™, AMX Device Discovery
Footnote Description	<p>1. When [PICTURE MODE] is set to [DYNAMIC], [LIGHT POWER] is set to [NORMAL], [DAYLIGHT VIEW] is set to [OFF], and [AUTO POWER SAVE] is set to [OFF].</p> <p>2. Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped.</p> <p>3. Measurement, measuring conditions, and method of notation all comply with American National Standards Institute standards. Value is the average of all products when shipped.</p> <p>4. Around this time, light output will have decreased to approximately 50 % of its original level ([PICTURE MODE]: [DYNAMIC], [DYNAMIC CONTRAST] set to [2], temperature 30 °C [86 °F], elevation 700 m [2,297 ft] with 0.15 mg/m³ of particulate matter). Estimated time until light output declines to 50 % varies depending on environment.</p> <p>5. Resolution decreases when using this function. V/H Keystone Correction and curved-screen correction are not available when using this function, and range of corner adjustment is limited.</p> <p>6. When Digital Zoom Extender is set to 80 %.</p> <p>7. 4K signals are converted to the projector's resolution upon projection.</p> <p>8. Depending on the connected CEC command-compatible device, the link control may not operate normally.</p> <p>9. On standby, power supply is available with Quick Startup set to ON or Power Management set to Ready.</p> <p>10. Main projector firmware must be Ver. 2.00 or later. The optional AJ-WM50 Series Wireless Module does not support IPv6.</p> <p>11. Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. On-mode power consumption measured at 25 °C (77 °F) operating temperature at an altitude of 700 m (2,297 ft).</p> <p>12. Filter cleaning cycle varies depending on environment. Filter can be washed and reused up to two times. Filter cleaning cycle: 20,000 hours (under dust conditions of 0.08 mg/m³), 10,000 hours (under dust conditions of 0.15 mg/m³).</p> <p>13. Average value. May differ depending on the actual unit.</p> <p>14. Light output is limited at operating temperatures higher than 30 °C (86 °F), and projectors cannot be operated at altitudes higher than 2,700 m (8,858 ft) above sea level. When optional AJ-WM50 Series Wireless Module is attached, operating temperature range becomes 0–40 °C (32–104 °F).</p> <p>15. When using Presenter Light Software, images are projected with 1280 x 800 dots or 1024 x 768 dots onto the screen. Also, your PC display resolution may be forcibly changed, and audio playback disrupted or become noisy, while images and sound are being transmitted.</p> <p>16. When using the Wireless Projector app, display resolution differs depending on your iOS/Android™ device and the display device. The maximum supported display resolution is WXGA (1280 x 800).</p>

Body Colour	White
Gross Dimensions (W x H x D in mm)	TMZ400U/TMZ400EJ: 507 x 469 x 222 mm TMZ400: 497 x 459 x 210 mm
Gross Weight (Kg)	TMZ400EJ: 8.4 kg(18.5 lbs) TMZ400U: 8.2 kg(18.1 lbs) TMZ400: 7.6 kg(16.8 lbs)
NFC	https://docs.connect.panasonic.com/projector/products/smartpjcontrol/regional.html#regional
EAN	TMZ400: 5025232931668 TMZ400EJ: 5025232931682