



Procesadores multimedia que simplifican las instalaciones en experiencias inmersivas con multiproyección

ET-FMP20

Procesadores multimedia que simplifican las instalaciones en experiencias inmersivas con multiproyección

Key Features

Flujo de trabajo optimizado para simplificar los procesos

Ajuste de precisión para una calidad excepcional

Reproducción 4K fluida y continua



ET-FMP20

<https://latam.connect.panasonic.com/mx/es/products/projectors/et-fmp20>

Type	Box-type
Terminals	
LAN	RJ-45 x 1 for network connection, 10Base-T/100Base-TX, 1000Base-T, NDI® compatible, Art-Net compatible
Audio Out	3.5 mm stereo mini-jack
USB	USB 3.0 (Type A) x 2
Video Format	H.264, 8-bit, 3840 x 2160 pixels, 60p, YPBPR 4:2:0, 300 Mbps / H.265, 8-bit, 4096 x 4096 pixels, 60p, YPBPR 4:2:0, 300 Mbps
Audio Format	AAC-LC, 16-bit, stereo
Almacenamiento	512 GB ³
Sistema operativo	Linux
Power Supply	(TBD)
Dimensiones (AnxAlxP)	Approx. 210 mm x 44 mm x 295 mm (8 1/4" x 1 23/32" x 11 5/8") (Including feet) (TBD)
Peso	Approx. 2.0 kg (4.41 lbs) (Excluding AC adapter and cord) (TBD)
Operating Environment	Operating temperature: 0-40 °C (32-104 °F), operating humidity: 10-80 % (no condensation)
Note	1 ET-FMP50 only. Available from CY2024 Q4. 2 When four HDMI™ outputs are used simultaneously. 3 Approximately 30 GB of the total storage space is allocated for system usage and is unavailable to the user.