



MSU para la configuración de sistemas de cámaras de transmisión a un coste reducido

AK-MSU1000

Unidad de configuración maestra (MSU) para conectar y controlar un máximo de 20 CCU, incluidas las funciones de asistencia versátiles, para la configuración de sistemas de cámaras de transmisión a un coste reducido

Key Features

Panel táctil LCD a color de tipo 7 de gran escala

Control maestro de ajustes precisos de la cámara para el conjunto del sistema de cámaras

Control de serie e IP (6 cámaras con conexión de serie y hasta 99 por IP)

Salida de información de cámara/CCU (1080i)

AK-MSU1000

<https://latam.connect.panasonic.com/mx/es/products/broadcast-proav/ak-msu1000>

General -> Power Supply	12 V DC (Power supply from camera: 10 V - 16 V DC) 42 V - 57 V DC (PoE power supply)
General -> Power Consumption	1.6 A (Power supply: 12 V DC) 0.6 A (PoE+ power supply)
General -> Operating Temperature	0 °C to 40 °C (32 °F to 104 °F)
General -> Operating Humidity	90% or less
General -> Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
General -> Weight	Approx. 4.0 kg (8.82 lb)
General -> Dimensions	W 482 mm x H 222 mm x D 81.5 mm (18-31/32 inches x 8-3/4 inches x 3-7/32 inches) (Including mounting brackets and dial heights)
Adjustment Functions	Scene file, ND filter, CC filter, Color temperature (COLOR TEMP), Master gain (MASTER GAIN), Shutter (SHUTTER), Master pedestal (MPED), Iris (IRIS), Camera selection
CCU Control	RS422 or IP
Maximum Cable Length	When CCU is connected: 50 m (164 ft)

