



**Clear and Vivid 7,000 lm Projection from the Lightest and Smallest Body in Class**

## **PT-VMZ71**

Deliver clear, striking images in well-lit open meeting spaces and classrooms from the smallest and lightest LCD laser projector in its class. High 7,000 lm brightness, 3,000,000:1 contrast, and vivid color creates an engaging presentation experience.

### **Key Features**

---

Compact and lightweight LCD laser projector

---

Clear Images That Are Easy to See in Bright Rooms

---

Installation Flexibility Adapts Projection to Any Space

---

Smooth and Effortless Collaboration



## PT-VMZ71

<https://latam.connect.panasonic.com/mx/es/productos/proyectores/pt-vmz71>

|  |  |
|--|--|
| <b>Projector type</b>  | LCD projectors   |
| <b>Display method</b>  | Transparent LCD panel (x 3, R/G/B)   |
| <b>Display Device -&gt; Panel size</b>                                     | 16.3 mm (0.64 in) diagonal (16:10 aspect ratio)  |
| <b>Display Device -&gt; Drive method</b>                                   | Active matrix method   |
| <b>Display Device -&gt; Number of pixels</b>                               | 2,304,000 (1920 x 1200) pixels   |
| <b>Light source</b>  | Laser diodes   |
| <b>Light output *1 *2</b>  | 7,000 lm   |
| <b>Light output (ANSI) *3</b>  | 7,000 lm   |
| <b>Time until light output declines to 50 % -&gt; NORMAL *4</b>            | 20,000 hours [NORMAL]  |
| <b>Time until light output declines to 50 % -&gt; ECO *4</b>               | 24,000 hours [ECO]   |
| <b>Time until light output declines to 50 % -&gt; QUIET *4</b>             | 20,000 hours [QUIET]   |
| <b>Resolution</b>  | WUXGA (1920 x 1200 pixels)   |
| <b>Contrast Ratio (typ.) *2</b>  | 3,000,000:1 (Full On/Full Off)(When [PICTURE MODE] is set to [DYNAMIC] and [DYNAMIC CONTRAST] is set to [1].)  |
| <b>Screen size (diagonal)</b>  | 0.76–7.62 m (30–300 in), 16:10 aspect ratio  |
| <b>Center-to-corner zone ratio *2</b>                                      | 85%  |
| <b>Lens</b>  | 1.6x manual zoom (throw ratio: 1.09–1.77:1), manual focus lens, F 1.60–2.12, f 15.30–24.64 mm  |
| <b>Digital Zoom Extender *5</b>  | Throw Ratio 1.09–2.21:1 (Corresponding value. When used together with optical zoom.)   |
| <b>Lens shift -&gt; Vertical(from center of screen)</b>                    | ±44 %  |
| <b>Lens shift -&gt; Horizontal(from center of screen)</b>                  | ±20 %  |
| <b>Keystone correction range</b>   | Vertical: ±25 °, Horizontal: ±35 °   |
| <b>Installation</b>  | Ceiling/floor, front/rear, free 360-degree installation  |
| <b>Terminals -&gt; HDMI™ IN</b>  | HDMI™TM 19-pin x 2 (Compatible with HDCP, Deep Color, 4K/30p*6 signal input), CEC supported*7  |
| <b>Terminals -&gt; COMPUTER IN ( D-SUB 15pin )</b>                         | D-sub 15-pin (female) x 2 (RGB/Y/P <sub>B</sub> /R/YC <sub>B</sub> /C <sub>R</sub> )   |
| <b>Terminals -&gt; AUDIO IN(M3 Stereo Mini Jack)</b>                       | M3 stereo mini-jack x 2  |
| <b>Terminals -&gt; AUDIO OUT(M3 Stereo Mini Jack)</b>                      | M3 stereo mini-jack x 1  |
| <b>Terminals -&gt; SERIAL IN</b>   | D-sub 9-pin (female) x 1 for computer control (RS-232C compliant)  |
| <b>Terminals -&gt; DIGITAL LINK IN / LAN</b>                               | RJ-45 x 1 for network and DIGITAL LINK connection (video/network/serial control)(HDBase™ compliant), 100Base-TX (Compatible with PLink™ [Class 2],HDCP, Deep Color, 4K/30p*6 signal input) |
| <b>Terminals -&gt; LAN</b>   | RJ-45 x 1 for network control, 10Base-T, 100Base-TX, compatible with PLink™ [Class 2]  |
| <b>Terminals -&gt; USB TYPE A</b>  | USB connector (Type A) x 1 for Memory Viewer function, optional AJ-WM50 Series Wireless Module,power supply (DC 5 V, maximum 2 A*8)  |
| <b>Protocol versions</b>   | IPv4, IPv6   |
| <b>Power supply</b>  | AC 100 V–240 V, 50/60 Hz   |
| <b>Maximum power consumption *10</b>                                       | 420 W (4.5–1.9 A)(455 VA)(Power consumption is 410 W at 200–240 V)   |
| <b>On-mode power consumption(Operating mode) -&gt; Normal *10</b>          | [NORMAL]<br>390 W (100–120 V),<br>375 W (200–240 V)  |
| <b>On-mode power consumption(Operating mode) -&gt; Eco *10</b>             | [ECO]<br>275 W (100–120 V),<br>265 W (200–240 V)   |
| <b>On-mode power consumption(Operating mode) -&gt; Quiet *10</b>           | [QUIET]<br>270 W (100–120 V),<br>260 W (200–240 V)   |
| <b>Built-in speaker</b>  | 10 W monaural  |
| <b>Cabinet materials</b>   | Molded plastic   |
| <b>Filter *11</b>  | Included   |
| <b>Estimated filter maintenance cycle</b>                                  | Approx. 20,000 hours   |
| <b>Operation noise -&gt; Normal *2</b>                                     | 38 dB [NORMAL]   |
| <b>Operation noise -&gt; Eco *2</b>  | 38 dB [ECO]  |
| <b>Operation noise -&gt; Quiet *2</b>                                      | 28 dB [QUIET]  |
| <b>Dimensions (W x H x D)</b>  | 399 mm x 115 mm x 348 mm (15 23/32" x 4 17/32" x 13 11/16" ) (not including protruding parts)399 mm x 133 mm x 348 mm (15 23/32" x 5 1/4" x 13 11/16" ) (with feet at shortest position)   |
| <b>Dimensions (W x H x D) -&gt; Width (not including protruding parts)</b> | 399 mm (15 23/32")   |

|   |  |
|---|--|
| <b>Dimensions -&gt; Width (including protruding parts)</b>              | 399 mm (15 23/32")   |
| <b>Dimensions -&gt; Height (not including protruding parts)</b>         | 115 mm (4 17/32")  |
| <b>Dimensions -&gt; Height (including protruding parts)</b>             | 133 mm (5 1/4")  |
| <b>Dimensions -&gt; Depth (not including protruding parts)</b>          | 348 mm (13 11/16")   |
| <b>Dimensions -&gt; Depth (including lens)</b>                          | 348 mm (13 11/16")   |
| <b>Weight *12</b>   | Approx. 7.0 kg (15.43 lbs)   |
| <b>Operating environment -&gt; Operating temperature *13</b>            | 0–45 °C (32–113 °F)  |
| <b>Operating Environment -&gt; Operating humidity (No condensation)</b> | 20–80 % (no condensation)  |
| <b>Applicable software</b>  | Multi Monitoring & Control Software, Logo Transfer Software, Presenter Light Software for Windows®*15, Wireless Projector App for iOS/Android™*16  |
| <b>Body Colour</b>  | Black/White  |
| <b>Gross Dimensions (W x H x D in mm)</b>                               | VMZ71U/VMZ71E/VMZ71BU/VMZ71BE/VMZ71U7/VMZ71BU7: 563 x 447 x 262 mm<br>VMZ71/VMZ71B: 555 x 439 x 246 mm   |
| <b>Gross Weight (Kg)</b>  | VMZ71E/VMZ71BE: 10.8 kg(23.8 lbs)<br>VMZ71U/VMZ71BU: 10.7 kg(23.5 lbs)<br>VMZ71U7/VMZ71BU7: 10.4 kg(22.9 lbs)<br>VMZ71/VMZ71B: 9.9 kg(21.7 lbs)  |
| <b>NFC</b>  | <a href="https://docs.connect.panasonic.com/projector/products/smartpjcontrol/regional.html#regional">https://docs.connect.panasonic.com/projector/products/smartpjcontrol/regional.html#regional</a>  |
| <b>EAN</b>  | VMZ71: 5025232923250<br>VMZ71E: 5025232923267<br>VMZ71B: 5025232923274<br>VMZ71BE: 5025232923281   |
| <b>Footnote Description</b>   | <ol style="list-style-type: none"> <li>When [PICTURE MODE] is set to [DYNAMIC], [LIGHT POWER] is set to [NORMAL], [DAYLIGHT VIEW] is set to [OFF], and [AUTO POWER SAVE] is set to [OFF].</li> <li>Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is the average of all products when shipped.</li> <li>Measurement, measuring conditions, and method of notation all comply with American National Standards Institute standards. Value is the average of all products when shipped.</li> <li>Around this time, light output will have decreased to approximately 50 % of its original level ([PICTURE MODE]: [DYNAMIC], [DYNAMIC CONTRAST] set to [2], temperature 30 °C (86 °F), elevation 700 m (2,297 ft) with 0.15 mg/m<sup>3</sup> of particulate matter). Estimated time until light output declines to 50 % varies depending on environment.</li> <li>Resolution decreases when using this function. 6-Point Screen Correction, V/H Keystone Correction, and curved-screen correction are not available when using this function, and range of corner adjustment is limited.</li> <li>When Digital Zoom Extender is set to 80%.</li> <li>4K signals are converted to the projector's resolution upon projection.</li> <li>Depending on the connected CEC command compatible device, the link control may not operate normally.</li> <li>On standby, power supply is available with Quick Startup set to ON or Power Management set to Ready.</li> <li>Requires projector firmware Ver. 2.00 or higher. The optional AJ-WM50 Series Wireless Module does not support IPv6.</li> <li>Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. On-mode power consumption measured at 25 °C (77 °F) operating temperature at an altitude of 700 m (2,297 ft).</li> <li>Filter cleaning cycle varies depending on the environment. The filter can be washed and reused up to two times. Filter cleaning cycle: 20,000 hours (under dust conditions of 0.08 mg/m<sup>3</sup>), 10,000 hours (under dust conditions of 0.15 mg/m<sup>3</sup>).</li> <li>Average value. May differ depending on the actual unit.</li> <li>Light output is limited at operating temperatures higher than 30 °C (86 °F), and projectors cannot be operated at altitudes higher than 2,700 m (8,858 ft) above sea level.</li> <li>When the optional AJ-WM50 Series Wireless Module is attached, the operating temperature range becomes 0–40 °C (32–104 °F).</li> <li>When using Presenter Light Software, images are projected with 1280 x 800 dots or 1024 x 768 dots onto the screen. Also, your PC display resolution may be forcibly changed, and audio playback disrupted or become noisy while images and sound are being transmitted.</li> <li>When using the Wireless Projector app, display resolution differs depending on your iOS/Android™ device and the display device. The maximum supported display resolution is WXGA (1280 x 800).</li> </ol> |