



TY-SB01QS

3G-SDI input signal board

TY-SB01QS

<https://latam.connect.panasonic.com/mx/es/products/projectors/ty-sb01qs>

| | |
|------------------------------|--|
| Terminals SDI 1 IN | BNC x 1 : 0.8Vp-p (75Ω) |
| Terminals SDI 2 IN | BNC x 1 : 0.8Vp-p (75Ω) |
| Terminals SDI 3 IN | BNC x 1 : 0.8Vp-p (75Ω) |
| Terminals SDI 4 IN | BNC x 1 : 0.8Vp-p (75Ω) |
| | 3840/60p,50p,30p,25p,24p 4096/60p,50p,30p,25p,24p |
| | Intel® SDM slot specification |
| | BNC x 1 : Active through |
| Audio | 12G-SDI: SMPTE ST 299 (SDI 1 IN Only) 3G-SDI: SMPTE ST 299 (SDI 1 IN Only) HD-SDI: SMPTE ST 299 (SDI 1 IN Only) |
| Video | 12G-SDI: SMPTE ST 2082-1 / 2082-10 (SDI 1 IN Only) 3G-SDI: SMPTE ST 424 / 425 HD-SDI: SMPTE ST 292 Quad Link 3G-SDI : SMPTE ST 424 / 425-5 Quad Link HD-SDI |
| | 1080/60p, 50p, 30p, 25p, 24p, 60i, 50i 2048/60p,50p,30p,25p,24p |
| | 1080/30p, 25p, 24p, 60i, 50i |
| | 48KHz, 20/24bit, 16CH, Synchronized video |
| | 48KHz, 20/24bit, 16CH, Synchronized video |
| | 48KHz, 20/24bit, 8CH, Synchronized video |
| Peso | 0.7 lbs. (300 g) |
| Dimensiones (AnxAIxP) | W 7.68" x H 0.99" x D 4.90" (195 x 25 x 125 mm) |
| Note | This product is a 12G-SDI terminal board that can be used by attaching it to our display. * This product does not work by itself. * This product will not work if it is installed on a product other than the corresponding model. * Please consult with a professional engineer or dealer to install or remove this product from the display. |