



6,000 lm PT-FRQ60 1-Chip DLP™ 4K Projector Delivers Smooth, Detailed Images for an Insightful Visual Experience

PT-FRQ60

Compact 1-Chip DLP™ Projectors Deliver Smooth, Detailed Images for an Insightful Visual Experience

Key Features

1-Chip DLP™ laser projector, 6,000lm brightness

4K (3840 x 2160) output resolution, ideal for museum exhibitions, education, and corporate offices

2.0x zoom lens and wide V/H Lens Shift (V: +71 %, -48 %, H: +34 %, -27 %)

Preactivated upgrade kit for Geometry Manager Pro

Supports 240Hz/1080p high frame rate with minimal input-to-output latency





PT-FRQ60

<https://latam.connect.panasonic.com/mx/es/productos/proyectoros/pt-frq60>

| | |
|--|--|
| Projector type | 1-Chip DLP™ projector |
| Display method | DLP™ chip x 1, DLP™ projection system |
| Display Device -> Panel size | 16.5 mm (0.65 in) diagonal (16:9 aspect ratio) |
| Display Device -> Number of pixels | 1920 x 1080 pixels (If a signal other than 120 Hz/240 Hz is input, it cannot be displayed at this resolution.) |
| Light source | Laser diodes |
| Light output | 6,000 lm |
| Light output (ANSI) | 6,000 lm |
| Light output (Center) *5 | 6,200 lm (Center) |
| Time until light output declines to 50 % | 20,000 hours [NORMAL] |
| -> NORMAL | |
| Time until light output declines to 50 % | 24,000 hours [ECO] |
| -> ECO | |
| Time until light output declines to 50 % | 20,000 hours [QUIET] |
| -> QUIET | |
| Resolution | 4K (3840 x 2160 pixels) (With Quad Pixel Drive) |
| Contrast Ratio (typ.) | 20,000:1 (Full On/Full Off) (When [PICTURE MODE] is set to [DYNAMIC] and [DYNAMIC CONTRAST] is set to [1]. HDMI signal input) |
| Screen size (diagonal) | 1.02-7.62 m (40-300 in), 16:9 aspect ratio |
| Center-to-corner zone ratio | 90% |
| Lens | 2.0x manual zoom (throw ratio: 1.46-2.93:1), manual focus, F 2.0-3.4, f 21.5-43.0 mm |
| Lens shift -> Vertical (from center of screen) | +71 %, -48 % (manual) |
| Lens shift -> Horizontal (from center of screen) | +34 %, -27 % (manual) |
| Keystone correction range | Vertical: ±40 °, Horizontal: ±20 ° |
| Installation | Ceiling/floor, front/rear, free 360-degree installation |
| Terminals -> HDMI™ IN | HDMI™ 19-pin x 2 (Compatible with HDCP 2.3, Deep Color, 4K/60p signal input*6), CEC supported |
| Terminals -> COMPUTER IN (D-SUB 15pin) | D-sub HD 15-pin (female) x 1 (RGB/Y _P R/YC _B C _R) |
| Terminals -> COMPUTER OUT (D-SUB 15pin) | D-sub HD 15-pin (female) x 1 (RGB/Y _P R/YC _B C _R) |
| Terminals -> AUDIO IN (M3 Stereo Mini Jack) | M3 stereo mini-jack x 2 |
| Terminals -> AUDIO OUT (M3 Stereo Mini Jack) | M3 stereo mini-jack x 2 |
| Terminals -> SERIAL IN | D-sub 9-pin (female) x 1 for external control (RS-232C compliant) |
| Terminals -> DIGITAL LINK IN / LAN | RJ-45 x 1 for network and DIGITAL LINK connection (video/network/serial control) (HDBase™ compliant), 100Base-TX (Compatible with PLink™ [Class 2], Art-Net, HDCP 2.3, Deep Color, 4K/60p signal Input*7, Extron XTP®) |
| Terminals -> LAN | RJ-45 x 1 for network connection, 10Base-T, 100Base-TX (Compatible with PLink™ [Class 2], Art-Net) |
| Terminals -> USB TYPE A | USB connector (Type A) x 1 for optional AJ-WM50 Series Wireless Module, for USB memory, and for power supply (DC 5 V, maximum 2 A) |
| Terminals -> SLOT | IPv4, IPv6*8 |
| Protocol versions | IPv4, IPv6*9 |
| Power supply | AC 100-240 V, 50/60 Hz, AC 110 V, 60 Hz (Taiwan) |
| Maximum power consumption | 505 W (5.5-2.4 A) (525 VA) |
| On-mode power consumption (Operating mode) -> Normal | [NORMAL] 445 W |
| On-mode power consumption (Operating mode) -> Eco | [ECO] 355 W |
| On-mode power consumption (Operating mode) -> Quiet | [QUIET] 355 W |
| Standby power consumption -> Normal | 15 W (Standby Mode) [NORMAL] |
| Standby power consumption -> ECO | 0.5 W (Standby Mode) [ECO] |
| Cabinet materials | Molded plastic |
| Filter | No |
| Operation noise -> Normal | 36 dB [NORMAL] |
| Operation noise -> Eco | 36 dB [ECO] |
| Operation noise -> Quiet | 31 dB [QUIET] |
| Dimensions (W x H x D) | 498 x 168 x 492 mm (19 5/8" x 6 5/8" x 19 3/8") |

| | |
|--|--|
| Dimensions (W x H x D) -> Width (not including protruding parts) | 498 mm (19 5/8") |
| Dimensions -> Height (including protruding parts) | 168 mm (6 5/8") |
| Dimensions -> Depth (not including protruding parts) | 492 mm (19 3/8") |
| Weight | Approx. 16.4 kg (36.2 lbs) |
| Operating environment -> Operating temperature | 0-45 °C (32-113 °F) |
| Operating Environment -> Operating humidity (No condensation) | 10-80 % (no condensation) |
| Applicable software | Logo Transfer Software, Multi Monitoring & Control Software, Early Warning Software, Projector Network Setup Software |
| Control function via LAN | Crestron Connected™ v2, Crestron XiO Cloud™*12, Art-Net DMX, AMX® DD, and PJLink™ (Class 2) |
| Footnote Description | <ol style="list-style-type: none"> 1. If a signal other than 120 Hz/240 Hz is input, it cannot be displayed at this resolution. 2. When [PICTURE MODE] is set to [DYNAMIC], [DAYLIGHT VIEW] is set to [OFF], [DYNAMIC CONTRAST] is set to [OFF], [LIGHT OUTPUT] is set to [100%], and [AUTO POWER SAVE] is set to [OFF]. 3. Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is the average of all products when shipped. 4. Measurement, measuring conditions, and method of notation all comply with American National Standards Institute standards. Value is the average of all products when shipped. 5. Average light-output value of all shipped products measured at the center of the screen. 6. Around this time, light output will have decreased to approximately 50 % of its original level ([PICTURE MODE]: [DYNAMIC], [DYNAMIC CONTRAST] set to [2], temperature 30 °C [86 °F], elevation 700 m [2,297 ft] with 0.15 mg/m3 of particulate matter). Estimated time until light output declines to 50 % varies depending on environment. 7. 4K/60p signals are converted to the projector's resolution upon projection. 8. 4K/60p signals are converted to projector's resolution. Supports YPBPR 4:2:0 format only. 9. Main firmware version must be 3.00 or higher. Optional AJ-WM50 Series Wireless Module is not compatible with IPv6. 10. With legs fully retracted. 11. Average value. May differ depending on the actual unit. 12. When using the projector at an altitude lower than 2,700 m (8,858 ft) above sea level, and the operating environment temperature becomes 35 °C (95 °F) or higher, the light output may be reduced to protect the projector. When optional AJ-WM50 Series Wireless Module is attached, operating temperature range becomes 0-40 °C (32-104 °F). 13. Main firmware version must be 3.00 or higher. |