



Short-Throw Zoom Lens for 3-Chip DLP™ Projectors

ET-D3LEW200

The Zero Offset Ultra Short Throw Fixed-Focus Lens is designed for compatibility with RZ21 series, RZ31 series projectors.

Key Features

Minimize Throw Distance, Increase Flexibility

Wide-Range Adjustment After Projector Installation

Lens Design Delivers an Unobstructed View

ET-D3LEW200

<https://latam.connect.panasonic.com/pa/en/et-d3lew200>

Lens type	Short-Throw Zoom Lens
F Value	2.5
Focal Length	13.8–18.1 mm (17/32"–23/32")
Screen Size	200-600 inches
Throw ratio 4K+	0.693–0.913:1
Throw ratio WUXGA	0.645–0.850:1
Throw ratio SXGA+	0.699–0.921:1
Lens-shift*1 Vertical	±59 %
Lens-shift*1 Horizontal	±19 %
Zoom	Yes
Dimensions (W×H×D)	250 × 193 × 495 mm (9 27/32" x 7 19/32" x 19 1/2")
Weight	Approx. 9.0 kg (19.8 lbs)
Compatible projectors	RQ32K/RZ31K Series/RQ22K/RZ21K Series

Note * Value is for ceiling installations using the PT-RQ22K. Lens-shift value will vary by model. Please see the Throw Distance Calculator for more information: <https://panasonic.net/cns/projector/calculator/tdc/>. For floor installations, up and right shift will be defined as a positive value. Down and left shift will be defined as a negative value.