



## Control Panel Standard Type

### AT-KC10C1

The “Kairos Control” panel is available in two models: 24XPT standard layout (AT-KC10C1) and 12XPT compact layout (AT-KC10C2).\* The panels allow functions to be assigned freely. Indicators show the functions assigned to individual buttons. Multi-scene operation is supported with two ME layouts and two faders. Multiple panels can be used simultaneously within a single system.

#### Key Features

---

24XPT standard layout. The panels allow functions to be assigned freely.

---

Multi-scene operation is supported with two ME layouts and two faders.

---

Indicators show the functions assigned to individual buttons.

---

Multiple panels can be used simultaneously within a single system.

---

A transition fader of the panel supports A/B mode in addition to PGM/PST mode.

AT-KC10C1

<https://latam.connect.panasonic.com/pa/en/kc10c1>

<b>General -&gt; Power Requirement</b>	DC 12V, 8.0A
<b>General -&gt; Operating Temperature</b>	0 to 40 °C
<b>General -&gt; Operating Humidity</b>	10% to 90%, no condensation
<b>General -&gt; Weight</b>	Approx. 15.4 kg / 33.95 lb (without accessories & options)
<b>General -&gt; Dimensions</b>	W 1140 mm x H 94 mm x D 420 mm(44.9 x 3.7 x 16.5 inches)(excluding protrusion)
<b>Control Terminals -&gt; LAN (Rear Panel)</b>	RJ-45 x 1, 1GbE
<b>Control Terminals -&gt; USB (Control Panel)</b>	USB2.0 typeA x 1
<b>Control Terminals -&gt; USB (Rear Panel)</b>	USB2.0 typeA x 1
<b>Footnote Description</b>	NDI® is a registered trademark of Vizrt NDI AB in the United States and other countries.