



Control Panel Standard Type

AT-KC10C1

The “Kairos Control” panel is available in two models: 24XPT standard layout (AT-KC10C1) and 12XPT compact layout (AT-KC10C2).* The panels allow functions to be assigned freely. Indicators show the functions assigned to individual buttons. Multi-scene operation is supported with two ME layouts and two faders. Multiple panels can be used simultaneously within a single system.

Key Features

24XPT standard layout. The panels allow functions to be assigned freely.

Multi-scene operation is supported with two ME layouts and two faders.

Indicators show the functions assigned to individual buttons.

Multiple panels can be used simultaneously within a single system.

A transition fader of the panel supports A/B mode in addition to PGM/PST mode.

AT-KC10C1

<https://latam.connect.panasonic.com/pa/en/kc10c1>

General

Power Requirement DC 12V, 8.0A - XLR 4pin x 2 (Redundant)

Operating Temperature 0 to 40 degree Celsius

Operating Humidity 10% to 90% (no condensation)

Weight Approx. 15.4 kg / 33.95 lb

Dimensions (W x H x D) 1140 mm x 94 mm x 420 mm

44.9 in. x 3.7 in. x 16.5 in. Excluding protrusion

Control Terminals

LAN (Rear Panel) RJ-45 x 1, 1GbE

USB (Control Panel) USB2.0 typeA x 1

USB (Rear Panel) USB2.0 typeA x 1