Panasonic CONNECT



Control Panel Standard Type

AT-KC10C1

The “Kairos Control” panel is available in two models: 24XPT standard layout (AT-KC10C1) and 12XPT compact layout (AT-KC10C2).* The panels allow functions to be assigned freely. Indicators show the functions assigned to individual buttons. Multi-scene operation is supported with two ME layouts and two faders. Multiple panels can be used simultaneously within a single system.

Key Features

- 24XPT standard layout. The panels allow functions to be assigned freely.
- Multi-scene operation is supported with two ME layouts and two faders.
- Indicators show the functions assigned to individual buttons.
- Multiple panels can be used simultaneously within a single system.
- A transition fader of the panel supports A/B mode in addition to PGM/PST mode.

Panasonic CONNECT

AT-KC10C1

https://latam.connect.panasonic.com/pa/en/kc10c1

General -> Power Requirement	DC 12V, 8.0A
General -> Operating Temperature	0 to 40 ˚C
General -> Operating Humidity	10% to 90%, no condensation
General -> Weight	Approx. 15.4 kg / 33.95 lb (without accessories & options)
General -> Dimensions	W 1140 mm x H 94 mm x D 420 mm(44.9 x 3.7 x 16.5 inches)(excluding protrusion)
Control Terminals -> LAN (Rear Panel)	RJ-45 x 1, 1GbE
Control Terminals -> USB (Control Panel)	USB2.0 typeA x 1
Control Terminals -> USB (Rear Panel)	USB2.0 typeA x 1
Footnote Description	NDI® is a registered trademark of Vizrt NDI AB in the United States and other countries.