

**Panasonic**  
**CONNECT**



**ET-DLE020**

ET-DLE020

<https://latam.connect.panasonic.com/pa/en/products/projectors/et-dle020>

<b>Lens type</b>	Ultra-Short-Throw Zoom Lens
<b>F Value</b>	2.0
<b>Focal Length</b>	(f) 4.1-4.4 mm
<b>Screen Size</b>	100-400 inches
<b>Throw ratio   WUXGA</b>	0.280-0.299:1
<b>Throw ratio   WXGA</b>	0.294-0.314:1
<b>Throw ratio   XGA</b>	0.290-0.309:1
<b>Lens-shift*1   Vertical</b>	+50 % - -16 %
<b>Lens-shift*1   Horizontal</b>	+10 % - -20 %
<b>Zoom</b>	Yes
<b>Dimensions (W×H×D)</b>	170 × 170 × 389 mm ( 6 11/16" × 6 11/16" × 15 13/32" )
<b>Weight</b>	Approx. 3.2 kg (7.05 lbs)
<b>Applicable projectors*2</b>	PT-RCQ10 / PT-RCQ80 / PT-RZ120 / PT-RZ970 / PT-RW930 / PT-RX110 / PT-RZ870 / PT-RZ770 / PT-RW730 / PT-RZ660 / PT-RW620

**Note** \*1 Value is for ceiling installations at WUXGA resolution. Lens-shift value will vary by model. Please see the Throw Distance Calculator for more information: <https://panasonic.net/cns/projector/calculator/tdc/>. For floor installations, up and right shift will be defined as a positive value. Down and left shift will be defined as a negative value. \*2 Please use this product with the included lens-bracket attachment.