



## LCD Colour Viewfinder

### AK-HVF100

Light weight and high resolution (9-type IPS LCD 1920\*1080, 1,100 TV lines) viewfinder with built-in mechanical lift versatile assist functions

#### Key Features

---

Focus assist functions

---

---

External HD-SDI Input and 12V 4-pin XLR input

---

---

Four assignable function switches

---

---

Contrast, brightness and peaking are adjustable

---



## AK-HVF100

[https://latam.connect.panasonic.com/\\_pa/en/ak-hvf100](https://latam.connect.panasonic.com/_pa/en/ak-hvf100)

<b>General -&gt; Power Supply</b>	DC 12 V (supplied from camera or XLR)
<b>General -&gt; Power Consumption</b>	18 W
<b>General -&gt; Operating Temperature</b>	0 °C to 45 °C (32 °F to 113 °F)
<b>General -&gt; Operating Humidity</b>	10% - 85% (no condensation)
<b>General -&gt; Storage Temperature</b>	-20 °C to 60 °C (-4 °F to 140 °F)
<b>General -&gt; Weight</b>	Approx. 2.6 kg (5.73 lbs.) (not including hood) / Approx. 3.0 kg (6.61 lbs.) (including hood)
<b>General -&gt; Dimensions</b>	W 340 mm x H 234 mm x D 193 mm (13-13/32 inches x 9-7/32 inches x 7-5/8 inches) (not including hood) W 340 mm x H 234 mm x D 231 mm (13-13/32 inches x 9-7/32 inches x 9-1/8 inches) (including hood)
<b>Display Panel -&gt; Dimensions</b>	22.9cm (9.0 inches)
<b>Display Panel -&gt; Number of Pixels</b>	1920 x 1080 (FHD)
<b>Display Panel -&gt; Display Color</b>	Approx. 16.77 million colors
<b>Switch Functions and Connectors -&gt; Operation</b>	<POWER> switch, <MENU> button, <SELECT> dial button, <F1>/<F2>/<F3>/<F4> buttons, <BRIGHT> knob, <CONTRAST> knob, <PEAKING> knob, <INPUT> switch
<b>Switch Functions/Connectors -&gt; Connector</b>	Camera I/F connector (D-sub 29 pins x 1) SDI IN connector (BNC x 1) DC IN connector (XLR 4 pins x 1)
<b>Supported Signal Format -&gt; CAM</b>	1080/59.94i, 1080/50i
<b>Supported Signal Format -&gt; SDI</b>	1080/59.94p, 1080/50p, 1080/59.94i, 1080/50i, 720/59.94p, 720/50p