



Zoom lens for PT-MZ16K/PT-MZ13K/PT-MZ10K

ET-EMU100

Throw Ratio 0.330 – 0.353:1 (Aspect 16:10) 0.329 – 0.353:1 (Aspect 16:9) 0.396 – 0.425:1 (Aspect 4:3)

Key Features

Ultra-Short-Throw Versatility with Zero Offset

Flexibility Streamlines Installation Workflow

Durability for Peace of Mind

ET-EMU100

<https://latam.connect.panasonic.com/pa/es/et-emu100>

| | |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Lens type | Ultra-Short-Throw Zoom Lens |
| F-number | 1.9 |
| Focal length (f) | 7.23–7.73 mm (9/32"–5/16") |
| Screen size | 100–400 inches |
| Throw ratio -> WUXGA | 0.330–0.353:1 |
| Lens-shift -> Vertical | PT-MZ16K/PT-MZ13K/PT-MZ10K : +50 % - -20 % *1 |
| Lens-shift -> Horizontal | PT-MZ16K/PT-MZ13K/PT-MZ10K : ±20 % *1 |
| Zoom | x1.07 |
| Dimensions -> (W) | 200 mm (7 7/8") |
| Dimensions -> (H) | 200 mm (7 7/8") |
| Dimensions -> (D) | 509 mm (20 1/32") |
| Weight | Approx. 7.2 kg (15.87 lbs) |
| Applicable projectors | PT-MZ16KL/PT-MZ13KL/PT-MZ10KL |
| Footnote Description | * When PT-RQ50K's handle is attached, vertical lens-shift range is -8 % - +50 %. Vertical lens-shift range is -50 % - +50 % with PT-RQ50K's supplied handle removed. Please refer to instruction guide for details on how to remove the handle. |