



Procesadores multimedia que simplifican las instalaciones en experiencias inmersivas con multiproyección

ET-FMP50

Procesadores multimedia que simplifican las instalaciones en experiencias inmersivas con multiproyección

Key Features

Flujo de trabajo optimizado para simplificar los procesos

Ajuste de precisión para una calidad excepcional

Reproducción 4K fluida y continua



ET-FMP50

<https://latam.connect.panasonic.com/pa/es/products/projectors/et-fmp50>

Type	Box-type
Video Format	HAP*2 / H.264, 8-bit, 3840 x 2160 pixels, 60p, YPBPR 4:2:0, 300 Mbps / H.265, 8-bit, 4096 x 4096 pixels, 60p, YPBPR 4:2:0, 300 Mbps
Audio Format	AAC-LC, 16-bit, stereo
Almacenamiento	4 TB
Sistema operativo	Linux®
Power Supply	AC 100–240 V, 50/60 Hz
Dimensiones (AnxAlxP)	Approx. 210 mm x 44 mm x 295 mm (8 1/4" x 1 23/32" x 11 5/8") (Excluding feet)
Peso	Approx. 2.0 kg (4.41 lbs) (Excluding AC adapter and cord)
Operating Environment	Operating temperature: 0–40 °C (32–104 °F), operating humidity: 10–80 % (no condensation)
Note	*1 When four HDMI™ outputs are used simultaneously. *2 ET-FMP50 only. Available via a firmware update from CY2025 Q1. *3 For the ET-FMP20 (512 GB) and ET-SBFMP10 (512 GB), approximately 30 GB of the total storage space is allocated for system usage and is unavailable to the user. *4 The operating temperature range may differ according to the specific projector model paired with the ET-SBFMP10