

## Controlador de cámaras remotas

### AW-RP60GJ

Equipado con una pantalla que permite ver los menús de la interfaz gráfica de usuario con una gran nitidez, además de un joystick para un control intuitivo. Controlador compacto de cámaras remotas compatible con PoE\* para conexión con un solo cable.

#### Key Features

---

Equipado con una pantalla LCD de tipo 3,5

---

Funciones de personalización flexibles

---

Nuevo joystick con funcionalidad mejorada

---

Compatible con PoE+/Ajuste de cámara avanzado

---

Control de hasta 200 cámaras de red remotas



## AW-RP60GJ

<https://latam.connect.panasonic.com/pa/es/productos/broadcast-y-proav/aw-rp60gj>

<b>General -&gt; Power Requirements</b>	12 V DC (10.8 V to 13.2 V)
<b>General -&gt; PoE</b>	PoE
	42 V to 57 V DC
<b>General -&gt; Current Consumption</b>	0.9 A (XLR connector input), 0.3 A (PoE power supply)
<b>General -&gt; Ambient Operating Temperature</b>	0 °C to 40 °C (32 °F to 104 °F)
<b>Humidity</b>	
<b>General -&gt; Ambient Operating Humidity</b>	20 % to 90 % (no condensation)
<b>General -&gt; Storage Temperature</b>	-20 °C to 50 °C (-4 °F to 122 °F)
<b>General -&gt; Weight</b>	1.5 kg (3.31 lbs)
<b>General -&gt; Dimensions</b>	W 210 mm x H 92 mm x D 177 mm (8-9/32 inches x 3-5/8 inches x 6-31/32 inches) (excluding protrusions)
<b>General -&gt; LCD Display</b>	3.5 inch LCD (QHD: 960 x 540)
<b>Input Connector -&gt; DC IN</b>	DC 12 V IN, XLR 4-pin
<b>Input/Output Connector -&gt; LAN (IP CONT)</b>	10BASE-T/100BASE-TX, PoE input  Connecting cable: LAN cable, max. 100 m (328 ft)  • When connecting the unit via a switching hub: Straight cable (category 5e), STP (Shielded Twisted Pair) cable recommended  • When connecting the unit directly: Crossover cable (category 5e), STP (Shielded Twisted Pair) cable recommended  • REMOTE: Available only for LAN (RJ45) control
<b>Input/Output Connector -&gt; LAN (SERIAL CONT)</b>	RS-422 (control signals for remote cameras), TALLY OUT  Connecting cable: Straight cable (category 5e), max. 1000 m (3280 ft)  TALLY OUT: Open collector output (negative logic) Maximum voltage resistance DC 24 V, Maximum current 50 mA
<b>Input/Output Connector -&gt; TALLY / GPIO 1</b>	D-sub 25-pin, female, inch thread TALLY IN: Contact input (Status operation) GPIO IN: Contact input (Trigger operation) GPIO OUT: Open collector output (negative logic) Maximum voltage resistance DC 24 V, Maximum current 10 mA
<b>Connection Specifications -&gt; No. of Connectable Cameras</b>	200 (IP), 5 (RS422)
<b>Connection Specifications -&gt; No. of Camera Selection Buttons</b>	5 (6 to 200 controlled from the LCD)
<b>Connection Specifications -&gt; No. of Camera Groups</b>	40 (5 units/group)
<b>Memory -&gt; Preset Memory</b>	100

