Panasonic CONNECT




## Master Setup Unit (MSU)

# AK-MSU1000

Master Setup Unit (MSU) - Maximum of 20 CCU can be connected and controlled from an AK-MSU100 Plus Versatile Assist Functions Transmission Camera System to Be Configured at Low Cost

**Key Features**

- Large scale 7-type color LCD Touch Panel
- Master control of precise camera settings for the entire camera system
- Serial & IP control (6x serial and up to 99 cameras by IP)
- Camera/CCU Information Output (1080i)
- HD SDI Input (Monitoring, 1080i)

Panasonic CONNECT

# AK-MSU1000

https://latam.connect.panasonic.com/pa/es/ak-msu1000

| | |
|---|---|
| **General -> Power Supply** | 12 V DC (Power supply from camera: 10 V - 16 V DC)<br>42 V - 57 V DC (PoE power supply) |
| **General -> Power Consumption** | 1.6 A (Power supply: 12 V DC)<br>0.6 A (PoE+ power supply) |
| **General -> Operating Temperature** | 0 °C to 40 °C (32 °F to 104 °F) |
| **General -> Operating Humidity** | 90% or less |
| **General -> Storage Temperature** | -20 °C to 60 °C (-4 °F to 140 °F) |
| **General -> Weight** | Approx. 4.0 kg (8.82 lb) |
| **General -> Dimensions** | W 482 mm x H 222 mm x D 81.5 mm<br>(18-31/32 inches x 8-3/4 inches x 3-7/32 inches)<br>(Including mounting brackets and dial heights) |
| **Adjustment Functions** | Scene file, ND filter, CC filter, Color temperature (COLOR TEMP), Master gain (MASTER GAIN), Shutter (SHUTTER), Master pedestal (MPED), Iris (IRIS), Camera selection |
| **CCU Control** | RS422 or IP |
| **Maximum Cable Length** | When CCU is connected: 50 m (164 ft) |