



**Zero Offset Ultra Short Throw Fixed-Focus Lens**

## **ET-D3LEU100 ( for 3-Chip DLP™ Projectors )**

Project in tight spaces from very short throw-distances. With zero offset capability, these two lens options widen the versatility of Panasonic's 3-Chip DLP™ lineup.

### **Key Features**

---

Minimize Throw Distance, Increase Flexibility

---

Wide-Range Adjustment After Projector Installation

---

Lens Design Delivers an Unobstructed View

## ET-D3LEU100 ( for 3-Chip DLP™ Projectors )

[https://latam.connect.panasonic.com/\\_pa/es/et-d3leu100for-3-chip-dlptm-projectors](https://latam.connect.panasonic.com/_pa/es/et-d3leu100for-3-chip-dlptm-projectors)

<b>Lens type</b>	Ultra-Short-Throw Lens
<b>F-number</b>	2.5
<b>Focal length (f)</b>	8.0 mm (5/16")
<b>Screen size</b>	200-600 inches
<b>Throw ratio -&gt; 4K+</b>	0.397:1
<b>Throw ratio -&gt; WUXGA</b>	0.370:1
<b>Throw ratio -&gt; SXGA+</b>	0.401:1
<b>Throw ratio -&gt; WXGA</b>	0.413:1
<b>Auto Lens Identification function</b>	PT-RQ32K/RZ31K/RS30K/RQ25K/RZ24K/RQ18K/RZ17K/RZ14K/RQ22K/RZ21K/RS20K
<b>Compatible models</b>	
<b>Lens-shift -&gt; Vertical</b>	±59 % *1
<b>Lens-shift -&gt; Horizontal</b>	+29 % - -5 % *1
<b>Zoom</b>	No
<b>Dimensions -&gt; (W)</b>	275 mm(10 13/16")
<b>Dimensions -&gt; (H)</b>	154 mm(6 1/16")
<b>Dimensions -&gt; (D)</b>	428.7 mm(16 7/8")
<b>Weight</b>	Approx. 8.0 kg (17.6 lbs)
<b>Applicable projectors</b>	RQ35K Series/RQ32K/RZ31K Series/RQ25K Series/RQ22K/RZ21K Series/RZ16K/RZ14K/RQ13K/RZ12K Series/DZ21K2 Series/DZ13K Series
<b>Footnote Description</b>	* Value is for ceiling installations using the PT-RQ22K. Lens-shift value will vary by model. Please see the Throw Distance Calculator for more information. For floor installations, up and right shift will be defined as a positive value. Down and left shift will be defined as a negative value.